


EnCana OIL & GAS (USA) INC.

LOCATION LAYOUT FOR

WELL PAD K22 596
SECTION 22, T5S, R96W, 6th P.M.
NE 1/4 SW 1/4



SCALE: 1" = 60'
DATE: 01-31-07
Drawn By: D.R.B.

Revised: 03-07-07 D.R.B.
Revised: 04-11-07 D.R.B.
Revised: 04-18-07 D.R.B.
Revised: 06-18-07 D.R.B.
Revised: 01-14-09 D.R.B.
Revised: 04-22-09 D.R.B.
Revised: 06-09-09 D.R.B.
Revised: 08-25-09 D.R.B.

NOTE:
Compact in 6" lifts,
and seed ECB infilled
with Flexterra.

0.75 Ac. to Sed. Res. #1
3,600 cu.ft./Ac. Drainage
Vol. = 2,700 cu.ft.
L= 56', W=56', D=6'

0.75 Ac. to Sed. Res. #2
3,600 cu.ft./Ac. Drainage
Vol. = 2,700 cu.ft.
L= 56', W=56', D=6'

NOTE:
Wattle to be installed
25' downhill of slash
and topsoil stockpile.

Sheet 3 of 11

SWMP LEGEND:
CD - CHECK DAM
ECB - EROSION CONTROL
BLANKET
LS - LEVEL SPREADER
SCE - STABILIZED
CONSTRUCTION
ENTRANCE
SedR - SEDIMENT
RESERVOIR
SL - SLASH
ST - SEDIMENT TRAP
T - TERRACING
TB - TOE BERM
VB - VEGETATED BUFFER
W - WATTLE
ECB INFILLED
WITH FLEXTERRA



SCALE
UINTAH ENGINEERING & LAND SURVEYING
85 So. 200 East * Vernal, Utah 84078 * (435) 789-1017

NOTE:
2' Contour Interval.

NOTE:
Obtain Deficit Material
from Existing Location.

NOTES:

FINISHED GRADE ELEV.
FOR PAD EXTENSION = 6525.5'