This drawing is the property of Schlumberger and is not to be reproduced in any form or disclosed to any person without the written permission of Schlumberger. Any person borrowing this drawing accepts it as a confidential document and undertakes not to make any use of it detrimental to the interests of Schlumberger and to return it on demand. Schlumberger will not be responsible for any use made of the information contained in this drawing.

Contractor

Lower Bosque Entrance: 8mi right to Cherry Canyon, stay left at Y, stay on main road for 2.5 miles turn right. Bare location.

Main Pass (1000SPI)

Contractor Eng. Schlumberger
Contractor Engineer
Contractor Truck
Contractor Cartridge
Contractor Sonde
Contractor Serial No.

Logging Date 07-OCT-20
Run Number ONE
Depth Driller 10,120ft
Depth Logger 10,120ft
Bottom Logged Interval 10,120ft
Top Logged Interval 9,000ft
Casing Driller 13.375in @ 1,000ft
Casing Logger 1,000ft
Bit Size 12.25in
Type Fluid in Hole WBM
Density 10.0ppg
Viscosity 50sec/qt
Fluid Loss 4.0cc
Resistivity 0.0ohmm @ 0degF
Source of Sample Circulation
Rm @ Meas Temp 0.0ohmm @ 0degF
Rmf @ Meas Temp 0.0ohmm @ 0degF
Rmc @ Meas Temp 0.0ohmm @ 0degF
Source of Rmf / Rmc Measured / Measured
Rm @ BHT 0.0ohmm @ 0degF
Time Since Circulation 0.0hr
Max Rec Temp 0degF
Equipment Location Midland
Recorded By Cabaniss-Roach
Witnessed By Bob Lindsey

Gamma Ray (GR) (GAPI) 0 150
Caliper 1 (CALI) (in) 6 16
Bit Size (BS) (in) 6 16
Deep Resistivity (RT_HRLT) (ohmm) 0.2 2000
Medium Resistivity (RM_HRLT) (ohmm) 0.2 2000
Shallow Resistivity (RS_HRLT) (ohmm) 0.2 2000
Neutron Porosity (NPHI) (%) 45 -15
Bulk Density (RHOB) (g/cm3) 1.95 2.95
Photoelectric Factor (PEF) (b/e) 0 10

Logging Company Schlumberger
Logging Date 07-OCT-20
Run Number ONE
Depth Driller 10,120ft
Depth Logger 10,120ft
Bottom Logged Interval 10,120ft
Top Logged Interval 9,000ft
Casing Driller 13.375in @ 1,000ft
Casing Logger 1,000ft
Bit Size 12.25in
Type Fluid in Hole WBM
Density 10.0ppg
Viscosity 50sec/qt
Fluid Loss 4.0cc
Resistivity 0.0ohmm @ 0degF
Source of Sample Circulation
Rm @ Meas Temp 0.0ohmm @ 0degF
Rmf @ Meas Temp 0.0ohmm @ 0degF
Rmc @ Meas Temp 0.0ohmm @ 0degF
Source of Rmf / Rmc Measured / Measured
Rm @ BHT 0.0ohmm @ 0degF
Time Since Circulation 0.0hr
Max Rec Temp 0degF
Equipment Location Midland
Recorded By Cabaniss-Roach
Witnessed By Bob Lindsey

Gamma Ray (GR) (GAPI) 0 150
Caliper 1 (CALI) (in) 6 16
Bit Size (BS) (in) 6 16
Deep Resistivity (RT_HRLT) (ohmm) 0.2 2000
Medium Resistivity (RM_HRLT) (ohmm) 0.2 2000
Shallow Resistivity (RS_HRLT) (ohmm) 0.2 2000
Neutron Porosity (NPHI) (%) 45 -15
Bulk Density (RHOB) (g/cm3) 1.95 2.95
Photoelectric Factor (PEF) (b/e) 0 10

Boundary Run 1

Caliper 1 (CALI) (in)

Variable Density

Repeat Section (0PSI)

Contractor Eng. Schlumberger
Contractor Engineer
Contractor Truck
Contractor Cartridge
Contractor Sonde
Contractor Serial No.

Logging Date 07-OCT-20
Run Number ONE
Depth Driller 10,120ft
Depth Logger 10,120ft
Bottom Logged Interval 10,120ft
Top Logged Interval 9,000ft
Casing Driller 13.375in @ 1,000ft
Casing Logger 1,000ft
Bit Size 12.25in
Type Fluid in Hole WBM
Density 10.0ppg
Viscosity 50sec/qt
Fluid Loss 4.0cc
Resistivity 0.0ohmm @ 0degF
Source of Sample Circulation
Rm @ Meas Temp 0.0ohmm @ 0degF
Rmf @ Meas Temp 0.0ohmm @ 0degF
Rmc @ Meas Temp 0.0ohmm @ 0degF
Source of Rmf / Rmc Measured / Measured
Rm @ BHT 0.0ohmm @ 0degF
Time Since Circulation 0.0hr
Max Rec Temp 0degF
Equipment Location Midland
Recorded By Cabaniss-Roach
Witnessed By Bob Lindsey

Gamma Ray (GR) (GAPI) 0 150
Caliper 1 (CALI) (in) 6 16
Bit Size (BS) (in) 6 16
Deep Resistivity (RT_HRLT) (ohmm) 0.2 2000
Medium Resistivity (RM_HRLT) (ohmm) 0.2 2000
Shallow Resistivity (RS_HRLT) (ohmm) 0.2 2000
Neutron Porosity (NPHI) (%) 45 -15
Bulk Density (RHOB) (g/cm3) 1.95 2.95
Photoelectric Factor (PEF) (b/e) 0 10

Boundary Run 1

Caliper 1 (CALI) (in)

Variable Density

Service	Run No.	Remarks	In. ID	Out. ID	In. Lg.
		GR Array (R)	6.75	1.75	5.00
		CMRP-4 (R)	4.00	1.25	23.00
		Dip Tool Head	4.45	1.25	110.00
		CDL-P1 (Head)	5.27	3.75	16.00
		HRLT (Head)	5.27	3.75	23.00
		HNGS (L)	5.00	3.00	23.00

Contractor Schlumberger
Contractor Engineer
Contractor Truck
Contractor Cartridge
Contractor Sonde
Contractor Serial No.

Logging Date 07-OCT-20
Run Number ONE
Depth Driller 10,120ft
Depth Logger 10,120ft
Bottom Logged Interval 10,120ft
Top Logged Interval 9,000ft
Casing Driller 13.375in @ 1,000ft
Casing Logger 1,000ft
Bit Size 12.25in
Type Fluid in Hole WBM
Density 10.0ppg
Viscosity 50sec/qt
Fluid Loss 4.0cc
Resistivity 0.0ohmm @ 0degF
Source of Sample Circulation
Rm @ Meas Temp 0.0ohmm @ 0degF
Rmf @ Meas Temp 0.0ohmm @ 0degF
Rmc @ Meas Temp 0.0ohmm @ 0degF
Source of Rmf / Rmc Measured / Measured
Rm @ BHT 0.0ohmm @ 0degF
Time Since Circulation 0.0hr
Max Rec Temp 0degF
Equipment Location Midland
Recorded By Cabaniss-Roach
Witnessed By Bob Lindsey

Gamma Ray (GR) (GAPI) 0 150
Caliper 1 (CALI) (in) 6 16
Bit Size (BS) (in) 6 16
Deep Resistivity (RT_HRLT) (ohmm) 0.2 2000
Medium Resistivity (RM_HRLT) (ohmm) 0.2 2000
Shallow Resistivity (RS_HRLT) (ohmm) 0.2 2000
Neutron Porosity (NPHI) (%) 45 -15
Bulk Density (RHOB) (g/cm3) 1.95 2.95
Photoelectric Factor (PEF) (b/e) 0 10

Caliper 1 (CALI) (in)

Variable Density