COMPENSATED DENSITY
DUAL INDUCTION

Company
Well
Field
Location
County
State
Other Services
Permanent Datum
Log Measured From
Drilling Measured From
Elev.: K.B.
G.L.
D.F.
Date
Run Number
Depth Driller
Schlumberger Depth
Bottom Logged Interval
Top Logged Interval
Type Fluid in Hole
Salinity, PPM Cl
Density
Viscosity
Fluid Loss
Source of Sample
Rm @ Meas. Temp.
Rmf @ Meas. Temp.
Rmc @ Meas. Temp.
Source of Rmf and Rmc
Rm @ BHT
Time Since Circulation
Time Since Circulation
Max. Rec. Temp. Deg. F
Equipment Number
Location
Recorded By
Witnessed By

Bore-Hole Record
No.
Bit
From
To
Size
Type
Casing Record
No.
Size
Wgt.
From
To
Type Joint
Top
Bottom

Company Bond & Dolly Resources, Inc.
Well Wellington
Field Wellington
County Cimarron
State Oklahoma
Other Services
Permanent Datum Ground Level
Log Measured From K.B.
Drilling Measured From K.B.
Elev.: K.B. 3,812 Ft.
G.L. 3,797 Ft.
D.F.
Date Thu Nov 30, 2006
Run Number ONE
Depth Driller 7,200
Schlumberger Depth
Bottom Logged Interval 7,200
Top Logged Interval 2,000
Type Fluid in Hole Water
Salinity, PPM Cl
Density
Viscosity
Fluid Loss
Source of Sample
Rm @ Meas. Temp.
Rmf @ Meas. Temp.
Rmc @ Meas. Temp.
Source of Rmf and Rmc
Rm @ BHT
Time Since Circulation
Time Since Circulation
Max. Rec. Temp. Deg. F
Equipment Number
Location
Recorded By
Witnessed By

Bore-Hole Record
No. 1
Bit
From Surface
To 7,200
Size 7.875
Type
Casing Record
No. 1
Size 5.500
Wgt. 17.00
From Surface
To 7,200
Type Joint
Top
Bottom

Comments

This log and the information on this tape is recorded and delivered as an instantaneous well log as quickly as possible and as consistent with reasonable care and accuracy in the ability of the engineer or his tools. Schlumberger does not guarantee the accuracy or correctness of any interpretations, and is not liable for any losses or expenses incurred in connection with any use thereof. All interpretations are opinions based on inferences from electrical or other measurements and Schlumberger cannot, and does not warrant the accuracy, correctness or usefulness of any such interpretation, and does not assume any responsibility for any losses or expenses incurred in connection with any such use. This is in accordance with Schlumberger's standard terms and conditions set forth in our current Price Schedule.

Annular volume calculated for 4 1/2" casing
Deepest reading is 7,200'
Thank you for choosing Eurosun!
API-35-123-24189-00

Database File 5995-98
Dataset Pathname pass1
Presentation Format main
Dataset Creation Thu Nov 30, 15:59:05 2006
Charted by Depth in Feet scaled 1:240

Density Caliper (in) 16 / 6
Gamma Ray (GAPI) 150 / 0
SP (mV) 100 / -100

Deep Resistivity (Ohmm) .200 20 Density Porosity (pu) 45 / -15
Medium Resistivity (Ohmm) .200 20 Neutron Porosity (pu) 45 / -15
Shallow Resistivity (Ohmm) .200 20

2,000
2,100
2,200
2,300
2,400
2,500
2,600
2,700
2,800
2,900
3,000
3,100
3,200
3,300
3,400
3,500
3,600
3,700
3,800
3,900
4,000
4,100
4,200
4,300
4,400
4,500
4,600
4,700
4,800
4,900
5,000
5,100
5,200
5,300
5,400
5,500
5,600
5,700
5,800
5,900
6,000
6,100
6,200
6,300
6,400
6,500
6,600
6,700
6,800
6,900
7,000
7,100
7,200

2,100' 0.00 Alarm
2,200' 0.00 Alarm
2,300' 0.00 Alarm
2,400' 0.00 Alarm
2,500' 0.00 Alarm
2,600' 0.00 Alarm
2,700' 0.00 Alarm
2,800' 0.00 Alarm
2,900' 0.00 Alarm
3,000' 0.00 Alarm
3,100' 0.00 Alarm
3,200' 0.00 Alarm
3,300' 0.00 Alarm
3,400' 0.00 Alarm
3,500' 0.00 Alarm
3,600' 0.00 Alarm
3,700' 0.00 Alarm
3,800' 0.00 Alarm
3,900' 0.00 Alarm
4,000' 0.00 Alarm
4,100' 0.00 Alarm
4,200' 0.00 Alarm
4,300' 0.00 Alarm
4,400' 0.00 Alarm
4,500' 0.00 Alarm
4,600' 0.00 Alarm
4,700' 0.00 Alarm
4,800' 0.00 Alarm
4,900' 0.00 Alarm
5,000' 0.00 Alarm
5,100' 0.00 Alarm
5,200' 0.00 Alarm
5,300' 0.00 Alarm
5,400' 0.00 Alarm
5,500' 0.00 Alarm
5,600' 0.00 Alarm
5,700' 0.00 Alarm
5,800' 0.00 Alarm
5,900' 0.00 Alarm
6,000' 0.00 Alarm
6,100' 0.00 Alarm
6,200' 0.00 Alarm
6,300' 0.00 Alarm
6,400' 0.00 Alarm
6,500' 0.00 Alarm
6,600' 0.00 Alarm
6,700' 0.00 Alarm
6,800' 0.00 Alarm
6,900' 0.00 Alarm
7,000' 0.00 Alarm
7,100' 0.00 Alarm
7,200' 0.00 Alarm

Database File 5995-98
Dataset Pathname pass1
Presentation Format main
Dataset Creation Thu Nov 30, 15:59:05 2006
Charted by Depth in Feet scaled 1:240

Density Caliper (in) 16 / 6
Gamma Ray (GAPI) 150 / 0
SP (mV) 100 / -100

Deep Resistivity (Ohmm) .200 20 Density Porosity (pu) 45 / -15
Medium Resistivity (Ohmm) .200 20 Neutron Porosity (pu) 45 / -15
Shallow Resistivity (Ohmm) .200 20

2,000
2,050
2,100
2,150
2,200
2,250
2,300
2,350
2,400
2,450
2,500
2,550
2,600
2,650
2,700
2,750
2,800
2,850
2,900
2,950
3,000
3,050
3,100
3,150
3,200
3,250
3,300
3,350
3,400
3,450
3,500
3,550
3,600
3,650
3,700
3,750
3,800
3,850
3,900
3,950
4,000
4,050
4,100
4,150
4,200
4,250
4,300
4,350
4,400
4,450
4,500
4,550
4,600
4,650
4,700
4,750
4,800
4,850
4,900
4,950
5,000
5,050
5,100
5,150
5,200
5,250
5,300
5,350
5,400
5,450
5,500
5,550
5,600
5,650
5,700
5,750
5,800
5,850
5,900
5,950
6,000
6,050
6,100
6,150
6,200
6,250
6,300
6,350
6,400
6,450
6,500
6,550
6,600
6,650
6,700
6,750
6,800
6,850
6,900
6,950
7,000
7,050
7,100
7,150