

BRAN-DEX

WIRELINE SERVICES

GAMMA-RAY C.C.L

CEMENT BOND - V.D.L.

Company ENCANA ENERGY RESOURCES

Well STATE PETERSON 22-20

Field WATTENBERG

County WELD

State CO

Location:

1946 FULS 2015 FWL
SE NW

PERFORATE

Other Services

PERFORATE

Permanent Datum

SEC 20 TWP 5N RGE 63W

Elevation 4575

Log Measured From

KB

Elevation 4580

Drilling Measured From

KB

E.L. 4575

Date

NOV 11 2004

Run Number

ONE

Depth Chiller

Depth Logger

7326

Bottom Logged Interval

7330

Top Log Interval

5354

Open Hole Size

Type Fluid

Density / Viscosity

Max. Recorded Temp.

239 DEG FH

Estimated Cement Top

Time Well Ready

Time Logger on Bottom

Equipment Number

12

Location

STERLING

Recorded By

DIZMANG

Witnessed By

BRAD BOEHM

Run Number

Bit

From

To

Size

Weight

From

To

Casing Record

Size

Wt/Lf

Top

Bottom

Surface String

Prod. String

Production String

4 1/2

Liner

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

CORRECTED 7 FT UPHOLE TO CORRELATE

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
WVF3	14.17		CHD-None (1)	1.00	1.69	10.00
			CBL-2_OSIE (003)	9.75	2.00	50.00
WVF5	8.17					
CCL	7.32		CCL-Comp275 (CMP02)	1.54	2.75	20.00
CCL	7.32					
GR	5.50		GR-CMP275 (CMP02)	4.38	2.75	30.00
			CENT-A (1)	2.25	1.69	10.00
Dataset: /field/well/run/_plots/_/jobs/_job1 Total Length: 18.92 ft Total Weight: 120.00 lb O.D: 2.75 in						

Database File: state.db
Dataset Pathname: pass8
Presentation Format: cbl35
Dataset Creation: Thu Nov 11 10:46:53 2004 by Log Warrior 7.0 Standar
Charted by: Depth in Feet scaled 1:240

9 Collar Locator -1
0 Gamma Ray 300

0 Amplified Amplitude (mV) 10
0 Amplitude (mV) 100

300 Variable Density 1200

6850
6900
6950
7000
7050
7100
7150
7200
7250
7300

Collar Locator

Gamma Ray

Casing Collars

Amplified Amplitude

Amplitude

9 Collar Locator -1
0 Gamma Ray 300

0 Amplified Amplitude (mV) 10
0 Amplitude (mV) 100

300 Variable Density 1200