PHOENIX SURVEYS, INC.

DUAL INDUCTION CALIPER GAMMA RAY

Company	EnCana Energy Resources Inc.
Well	Sprague 8-4-9
Field	Wattenberg
County	Weld
State	Colorado
Location	Surface: 2295' FNL & 1955' FEL SW NE BHL: 2257' FNL & 1201' FEL SW NW Sec - 9, Twp - 2N, Rge - 67W
Elevation	4972'
Other Services	None

Log Measured From: GL
Drilling Measured From: GL

Date	January 24, 2005
Depth Driller	7630
Bottom Logged Interval	7630
Top Logged Interval	6300
Casing Driller	7630
Casing Logger	7630
Bit Size	7 7/8"
Density Viscosity	9.1#/g 37s
PH Fluid Loss	9.5 6.8cc
Source of Sample	Flowline
Rm @ Meas. Temp.	0.71 @ 77 F
Rmf @ Meas. Temp.	0.56 @ 77 F
Rmc @ Meas. Temp.	1.06 @ 77 F
Source Rmf Rmc	Mea Mea
Rm @ BHT	0.31 @ 150 F
Time Circulation Stopped	1600
Time Logger on Bottom	1930
Maximum Recorded Temperature	150 F
Equipment Number	3147
Location	Brighton, CO
Recorded By	Jeff Hoffman
Witnessed By	Dale Wakefield

>>> Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Annular volume is calculated for 4.5" casing.
Caza Drilling Rig 55
Thank you for using Phoenix Surveys.
API # 05-123-22638-00
CDL & CNL not run due to hole conditions.

Database File: 4881.db
Dataset Pathname: pass3
Presentation Format: DIL
Dataset Creation: Mon Jan 24 15:22:38 2005 by Log 6.2_B4
Charted by: Depth in Feet scaled 1:240

0	GR (GAPI)	200
0	SP (mV)	200
6	Caliper (in)	16

0.2	Deep Resistivity (Ohm-m)	2000
0.2	Medium Resistivity (Ohm-m)	2000
0.2	Shallow Resistivity (Ohm-m)	2000