CASING TALLY

Operator:	Apache Corporation
Well:	Ajax 1-H
Field:	Wildcat
County:	Lincoln
State:	Oklahoma
Rig:	Nabors 712
Date:	2026-04-14

CASING TALLY

Item	Qty	Description	Length (ft)	Depth (ft)
1	1	13-3/8" 54.5# J-55 STC Guide Shoe	1.50	1,500.00
2	1	13-3/8" 54.5# J-55 STC Shoe Joint	43.20	1,498.50
3	1	13-3/8" 54.5# J-55 STC Float Collar	1.40	1,455.30
4	34	13-3/8" 54.5# J-55 STC Casing	1,452.10	1,453.90
5	1	13-3/8" 54.5# J-55 STC Pup Joint	6.20	1.80
6	1	13-3/8" Mandrel Hanger	4.00	0.00

Total Joints Run: 38

Total Casing Length: 1,507.40 ft

Centralizers: 1 per joint on joints 1–12, then every 3rd joint to surface

Cement: Lead 650 sx Class C + 4% gel; Tail 250 sx Class C neat

Bumped Plug: Yes @ 1,000 psi

Floats Held: Yes

Returns to Surface: Yes, 180 bbl

Remarks: Ran casing to TD, circulated 2 hrs, reciprocated pipe 20 ft during cement job.

Prepared by: J. Whitfield, Tool Pusher

CASING TALLY FORM NO. 4 — TYPE STANDARD (DO NOT REPRODUCE)

Item	Qty	Description	Length (ft)	Depth (ft)
1	1	13-3/8" 54.5# J-55 STC Guide Shoe	1.50	1,500.00
2	1	13-3/8" 54.5# J-55 STC Shoe Joint	43.20	1,498.50
3	1	13-3/8" 54.5# J-55 STC Float Collar	1.40	1,455.30
4	34	13-3/8" 54.5# J-55 STC Casing	1,452.10	1,453.90
5	1	13-3/8" 54.5# J-55 STC Pup Joint	6.20	1.80
6	1	13-3/8" Mandrel Hanger	4.00	0.00

Total Joints Run: 38

Total Casing Length: 1,507.40 ft

Centralizers: 1 per joint on joints 1–12, then every 3rd joint to surface

Cement: Lead 650 sx Class C + 4% gel; Tail 250 sx Class C neat

Bumped Plug: Yes @ 1,000 psi

Floats Held: Yes

Returns to Surface: Yes, 180 bbl

Remarks: Ran casing to TD, circulated 2 hrs, reciprocated pipe 20 ft during cement job.

Prepared by: J. Whitfield, Tool Pusher

CASING TALLY FORM NO. 4 — TYPE STANDARD (DO NOT REPRODUCE)

6400

6450

6500

6550

6600

6650

6700

6750

6800

6850

6900

-9 CCL 1

0 GR (GAPI) 165

0 AMPLITUDE (mV) 85

0 AMPLIFIED AMPLITUDE (mV) 30

200 Variable Density 1200