

SD FEDERAL 24-9DL

EXISTING GRADE @ CENTER OF WELL PAD = 7,050.1'

FINISHED GRADE ELEVATION = 7,048.6'

CUT SLOPES = 1.5:1

FILL SLOPES = 1.5:1

TOTAL CUT FOR WELL PAD = 6,599 C.Y.

TOTAL FILL FOR WELL PAD = 4,520 C.Y.






TOPSOIL @ 6" DEPTH = 1,400 C.Y.

SHRINKAGE (10%) = 520 C.Y.

EXCESS MATERIAL = 159 C.Y. + 1,250 C.Y. (PIT)

TOTAL DISTURBANCE = 3.13 ACRES. DISTURBANCE INCLUDES ROAD, PAD, AND SOIL PILES.

WELL PAD LEGEND

-  PROPOSED WELL LOCATION
-  EXISTING CONTOURS (2' INTERVAL)
-  PROPOSED CONTOURS (2' INTERVAL)
-  ECF EROSION CONTROL FENCE
-  STORM WATER CONTROL DITCH

ENTEK GRB, LLC

SD FEDERAL 24-9DL
PROPOSED RIG LAYOUT

2257' FSL, 431' FEL

NE $\frac{1}{4}$ SE $\frac{1}{4}$, SEC 24, T.12N., R.89W., 6th PM
MOFFAT COUNTY, COLORADO

CHOICE ENGINEERING SERVICES

404 "N" Street - Suite 201 | Rock Springs, WY 82901
Phone 307-362-6065 | Fax 307-362-6064

Scale: 1"=60'

Date: 07/10/10

SHEET NO:

4

REVISED:

BY
DATE

