



SD FEDERAL 24-9DL

EXISTING GRADE @ CENTER OF WELL PAD = 7,050.1'
 FINISHED GRADE ELEVATION = 7,048.6'
 CUT SLOPES = 1.5:1
 FILL SLOPES = 1.5:1

TOTAL CUT FOR WELL PAD = 6,599 C.Y.
 TOTAL FILL FOR WELL PAD = 4,520 C.Y.
 TOPSOIL @ 6" DEPTH = 1,400 C.Y.
 SHRINKAGE (10%) = 520 C.Y.
 EXCESS MATERIAL = 159 C.Y. + 1,250 C.Y. (PIT)
 TOTAL DISTURBANCE = 3.13 ACRES. DISTURBANCE
 INCLUDES ROAD, PAD, AND SOIL PILES.

WELL PAD LEGEND

- PROPOSED WELL LOCATION
- EXISTING CONTOURS (2' INTERVAL)
- PROPOSED CONTOURS (2' INTERVAL)
- ECF EROSION CONTROL FENCE
- STORM WATER CONTROL DITCH

ENTEK GRB, LLC

SD FEDERAL 24-9DL
 PROPOSED RIG LAYOUT
 2257' FSL, 431' FEL
 NE $\frac{1}{4}$ SE $\frac{1}{4}$, SEC 24, T.12N., R.89W., 6th PM
 MOFFAT COUNTY, COLORADO

CHOICE ENGINEERING SERVICES

404 "N" Street - Suite 201 | Rock Springs, WY 82901
 Phone 307-362-6065 | Fax 307-362-6064

Scale: 1"=60' Date: 07/10/10

REVISED:

SHEET NO:

4

BY
DATE



0 30 60
 1" = 60'