



02054462

Andrews, David

From: GJRig01@oxy.com
Sent: Sunday, August 08, 2010 6:56 PM
To: Andrews, David
Cc: Brad_Ahquist@Oxy.com; Simon_Benevides@oxy.com; Ronald_Bevans@oxy.com; Dmitry_Smushkov@oxy.com; Linda_Kuether@oxy.com; Daniel_Padilla@oxy.com

Mr. Andrews,

The following 9-5/8" Surface casing string has been set at 2,678' and cemented on Oxy's 609-14 pad:

Well 697-08-64B, API# 05-045-17573-00

TESTED CEMENTING LINES TO 3000 PSI.
PUMPED 20 BBLS FRESH WATER, 20 BBLS OF SUPER FLUSH, 20 BBLS OF FRESH WATER.
CEMENTED 9-5/8" SURFACE CASING WITH:
1030 SACKS - 420 BBLS OF 12.3 PPG - 2.33 CU. FT/SK VERSACEM LEAD WITH TUFF FIBER, 160 SACKS
- 59 BBLS OF 12.8 PPG - 2.07 CU. FT/SK VERSACEM TAIL. DISPLACED WITH 205.5 BBLS FRESH WATER
AT 5-4-2 BPM.
SAW 435 PSI LIFT PRESSURE AT 2 BPM. BUMPED PLUG WITH 1000 PSI.
PRESSURED UP TO 1500 PSI FOR 15 MIN. - GOOD TEST. FLOATS HELD.
CIP AT 1500 HRS 8 AUGUST 2010.
SAW 0 BBLS CEMENT RETURNS TO SURFACE. LOST 502 BBLS OF MUD.
FLUSHED PARASITE LINE WITH SUGAR WATER - BACK PRESSURED VALVE LEAKED AFTERWARDS. PUMPED
27 BBL TOP JOB WITH 3 BBLS BACK TO SURFACE.

If you have any questions please contact OXY DSM

Thanks,

George Lyerly, Marco Silva, Curt Claussen, Victor Benavides