

Kubeczko, Dave

From: Kubeczko, Dave
Sent: Tuesday, August 24, 2010 5:34 PM
To: Kubeczko, Dave
Subject: FW: Williams Production RMT, Federal SR 33-9 Pad, NWSE Sec 9 T7S R94W, Garfield County, Form 2A (#400083908) Review

Scan No 2033321

CORRESPONDENCE

2A#400083908

From: Kubeczko, Dave
Sent: Tuesday, August 24, 2010 5:29 PM
To: Harris, Howard
Subject: Williams Production RMT, Federal SR 33-9 Pad, NWSE Sec 9 T7S R94W, Garfield County, Form 2A (#400083908) Review

Howard,

I have been reviewing the Federal SR 33-9 Pad **Form 2A** (#400083908). COGCC will attach the following conditions of approval (COAs) based on the data Williams has submitted on or attached to the Form 2A prior to passing the Oil and Gas Location Assessment (OGLA) review.

1. **General:** The following conditions of approval (COAs) will apply:

COA 6 - Reserve pit (or any pit that will hold liquids [if constructed]) must be lined or closed loop system (which has been indicated by Williams on the Form 2A) must be implemented during drilling.

COA 23 - Operator must ensure 110 percent secondary containment for any volume of fluids contained at well site during drilling and completion operations; including, but not limited to, construction of a berm or diversion dike, diversion/collection trenches within and/or outside of berms/dikes, site grading, or other comparable measures sufficiently protective of nearby surface water. If fluids are conveyed via pipeline, operator must implement best management practices to contain any unintentional release of fluids.

COA 38 - The moisture content of any drill cuttings in a cuttings pit, trench, or pile shall be as low as practicable to prevent accumulation of liquids greater than de minimis amounts. At the time of closure, the drill cuttings must also meet the applicable standards of table 910-1.

COA 39 - No portion of any pit that will be used to hold liquids shall be constructed on fill material, unless the pit and fill slope are designed and certified by a professional engineer, subject to review and approval by the director prior to construction of the pit. The construction and lining of the pit shall be supervised by a professional engineer or their agent. The entire base of the pit must be in cut.

COA 46 - The location is in an area of high run off/run-on potential; therefore the pad shall be constructed to prevent any stormwater run-on and/or stormwater runoff.

Based on the information provided in the Form 2A (Comments, Section 15) by Williams, COGCC will attach these COAs to the Form 2A permit; Williams does not need to respond, unless Williams has questions or concerns with details in this email. If you have any questions regarding this email, please do not hesitate to call me at (970) 309-2514 (cell), or email. Otherwise I will assume that these COAs are acceptable to Williams. Thanks.

Dave

David A. Kubeczko, PG
Oil and Gas Location Assessment Specialist

Colorado Oil & Gas Conservation Commission
Northwest Area Office

707 Wapiti Court, Suite 204
Rifle, CO 81650
Phone: (970) 625-2497x5
FAX: (970) 625-5682
Cell: (970) 309-2514
dave.kubeczko@state.co.us



 *Please consider the environment before printing this e-mail*