




PETROLEUM DEVELOPMENT CORPORATION
State Contact: David Andrews david.andrews@state.co.us

WELL NAME PUCKETT 21B-24D DATE 09/17/2010
API# 05-045-16108
LEASE# 636800
PERMIT # 20080536



CASING AND HOLE INFORMATION
DEPTH HOLE 2615'
CASING 9 5/8 36# 8rD, ST&C
DEPTH SET 2595'

Cement report

Company : BJ

CASING STRING:

LEAD: Premium Lite Cement plus additives 1494 sacks 12.5 ppg 1.95 yld 519.72 bbl slurry mixed @ 4 bbl/min

TAIL: TYPE III plus additives 170 sacks 14.2 ppg 1.47 yld 30 bbl slurry mixed @ 4 bbl /min

DISPLACED Displaced w/ 206 bbls water @ 7bbls Dwn To 3.06 bbl/min bumped plug w/ 1136 psi Float held no returns.

PRESSURE BEFORE BUMPING PLUG: 232 psi. and bumped plug 1136 psi.

RETURN: No Returns

COMENTS: Top Out to Surface= 846 sks, 14.2# cement Yield 1.47, Cement to surface and did not fall back, all good.

Any Questions or problems please advise

Gene sandefer
970-260-0587