

Berry Petroleum Company  
 OM 03B C10 696  
 API # 05-045-13244-0000  
 NENW Sec 10 Twn 6S Rng 96W  
 Garfield County, Colorado

Prepared Charles Durkoop  
 Updated 6/17/2010

Rig Patterson 175

8147 KB  
 8125 GL  
 22 KB-GL

BHT

TOC @ 3900'

Tight spot @ 8460'

7/23/2008 Spud  
 7/25/2008 Set Surf  
 8/10/2008 Set Prod  
 10/24/2008 Frac 3 Stg  
 11/3/2009 D/O CFP  
 11/11/2009 CIBP over Pers  
 11/12/2009 2000# @ 9131'  
 1/9/2010 D/O CIBP  
 1/9/2010 Land Tbg  
 5/6/2010 PT Csg 7000# @ 9172'  
 5/7/2010 Land Tbg  
 5/19/2010 Frac 4 - 8  
 6/10/2010 D/O CFP  
 6/14/2010 Land Tbg

Marker Jts @ 5245 - 66 &  
 8036 - 58

20" Conductor @ 132'

16" hole @ 3025'  
 69 jts 9-5/8" 36# J-55 surf csg @ 2993.12' w/ 1.9" PS, inj port @ 2651.5'  
 cmtd 1305 sx 11.6 ppg, 3.20 yield lead & 100 sx tail Type III @ 14.2 ppg, 1.52  
 yield

Equipment in Hole	Qty	Length	Depth
KB		22.00	22.00
Tbg Hanger		0.80	22.80
2-3/8" 4.7# N-80 Tbg	304	9542.71	9565.51
F-Nipple 1.81" ID		0.81	9566.32
2-3/8" 4.7# N-80 Tbg	1	15.62	9581.94

Stage 8: 8234 - 8428' @ 2 SPF (30 shots): Frac'd with 162099#'s of 30/50 white sand and 8414 bbls of fluid w/ 500 gals 7.5% acid

Stage 7: 8510 - 8604' @ 2 SPF (30 shots): Frac'd with 153080#'s of 30/50 white sand and 7964 bbls of fluid w/500 gals of 7.5% acid

Stage 6: 8654 - 8786' @ 2 SPF (30 shots): Frac'd with 204,103#'s of 30/50 white sand and 10546 bbls of fluid w/500 gals 7.5% acid

Stage 5: 8838 - 8932' @ 2 SPF (30 shots): Frac'd with 93,096#'s of 30/50 white sand and 5000 bbls of fluid w/ 500 gals of 7.5% acid

Stage 4: 8995 - 9147' @ 2 SPF (30 shots):Frac'd with 107,999#'s of 30/50 white sand and 5738 bbls of fluid w/ 500 gals 7.5% acid

Stage 3: 9193 - 9400' @ 2 SPF (24 shots): Frac'd with 90,098#'s of 30/50 white sand and 2440 bbls of fluid w/750 gal 7.5% acid

Stage 2: 9604 - 9829' @ 2 SPF (24 shots): Frac'd with 87,991#'s of 30/50 white sand & 2430 bbls fluid w/750 gal 7.5% acid

Stage 1: 9985 - 10185' @ 2SPF (24 shots): Frac'd with 104,102#'s of 30/50 white sand & 2929 bbls fluid w/750 gal 7.5% acid

8-3/4" hole @ 6540' & 7-7/8" hole @ 10617'  
 266 jts 4-1/2" 11.6# NS-110 prod csg @ 10489', FC @ 10442'  
 cmtd 665 sx 35/65 POZ Type III @ 12.5 ppg, 2.69 yield

PBTD @ 10450' WL Tag 10/8/08  
 C/O @ 10350' on 6/13/10