THE INFORMATION CONTAINED HEREIN IS PROPRIETARY TO NUWAVE PUMP LLC AND IS NOT TO BE DISCLOSED TO ANY THIRD PARTY WITHOUT THE EXPRESS WRITTEN CONSENT OF NUWAVE PUMP LLC.

NOTE: USE WITH CAMERA CABLE WITH 3/8 HEADPIECE TRIM LOG WITH 10.00 GAUGE RADIUS. NOTE TO BE USED AT 75° F MAX.

MAIN PASS 5" = 100'

MAIN PASS 5" = 100'

MAIN PASS 2.4" = 100'



MAIN PASS 2.4" = 100'

REPEAT PASS 5" = 100'



-27	CCL	3	LTEN	0	AMPx5 (mV)	20
0	GR	150	0 (lb)2000	0	AMP (mV)	100
				380	TT (usec)	180

200	VDL	1200

ROCKY MOUNTAIN WIRELINE SERVICE

REPEAT PASS 5" = 100'

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
CCL	18.75		CCL-TITAN275 (TITAN275_102) Titan 2 3/4" CCL	1.92	2.75	10.00
			TITAN169 Titan 1 11/16" Centralizer	2.17	1.69	5.00
WVF3FT	10.85		CBLTEKCO-TEKCO (TEKCO_8044) DEMO TOOL - DEMINSIONS INVALID	10.00	3.25	50.00
WVF5FT	9.85					
WVFCAL	5.85					
WVFSYNC	5.85		TITAN169 Titan 1 11/16" Centralizer	2.17	1.69	5.00
			GR-TEKCO234 (TEKO234_359) Tekco 2 3/4" Gamma Ray	3.69	2.75	20.00
GR	1.00					

Dataset:	111309_billbarrett_ggumiller_33a_31.db: field/well/dcbl/pass2
Total Length:	19.94 ft
Total Weight:	90.00 lb
O.D.	3.25 in