

NORTH AMERICA - NORTH AMERICA GAS - BP

Datum Elevation: 6,685.0ft
Ground Level: 6,669.0ft
Datum: ROTARY KELL
Report Date: 8/20/2010
Slot No.:

Casing Details	Casing Depths	Wellsketch (8/20/2010)	Equip Depth	Equip. Details	Perforations	STIM	LOG	Hole Depths
CASING PUPJOINT 8.625 in. , J-55, 28	16.5ft		8.0ft	2-7/8"EUE 8RD X7" X 9 HANGER				16.5ft
CASING HANGER 5.5 in. , N-80	16.5ft							
CASING PUPJOINT 8.625 in. , J-55, 28	18.0ft							
CASING JOINTS 8.625 in. , J-55, 28	23.0ft							
CASING JOINTS 5.5 in. , J-55, 15.5	17.7ft							
CASING JOINTS 5.5 in. , J-55, 15.5	20.0ft							
CASING JOINTS 5.5 in. , J-55, 15.5	347.4ft							
CASING JOINTS 8.625 in. , J-55, 28	348.8ft							
FLOAT SHOE 8.625 in. , J-55, 28	389.5ft							
	391.1ft							
			8.9ft	2-7/8"EUE 8RD P-110 6.5# T&C SRL				
CASING JOINTS 5.5 in. , J-55, 15.5	2845.3ft		3392.2ft	2-7/8"EUE 8RD F PROFILE NIPPLE 2.28"ID	3050.0ft			
CASING JOINTS 5.5 in. , J-55, 15.5	2874.9ft						3060.0ft	
MARKER JOINT 5.5 in. , J-55, 15.5	2884.8ft						3100.0ft	
							3110.0ft	
							3220.0ft	
							3230.0ft	
							3250.0ft	
							3260.0ft	
							3355.0ft	
							3365.0ft	
FLOAT COLLAR 5.5 in. , N-80	3550.5ft		3393.3ft	2-7/8"EUE 8RD EXPENDIBLE CHECK				
CASING JOINTS 5.5 in. , J-55, 15.5	3551.7ft		3394.0ft	2-7/8" EUE 8RD N-80 NIPPLE X 12" WITH 1/4" HOLES				
FLOAT SHOE 5.5 in. , N-80	3593.3ft		3425.1ft	2-7/8"EUE 8RD P-110 6.5# T&C SRL				
	3594.8ft		3431.3ft	2-7/8"EUE 8RD J-55				3604.0ft