

**State of Colorado
Oil and Gas Conservation Commission**

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303)894-2100 Fax: (303)894-2109

SUNDRY NOTICE

Submit original plus one copy. This form is to be used for general, technical and environmental sundry information. For proposed or completed operations, describe in full on Technical Information Page (Page 2 of this form.) Identify well or other facility by API Number or by OGCC Facility ID. Operator shall send an informational copy of all sundry notices for wells located in High Density Areas to the Local Government Designee (Rule 603b.)

1. OGCC Operator Number:	28700	4. Contact Name	Lynn Neely
2. Name of Operator:	ExxonMobil Oil Corporation	Phone:	281-654-1949
3. Address:	P. O. Box 4358, COPR-MI-205	Fax:	281-654-1940
City:	Houston	State:	Tx.
		Zip	77210-4358
5. API Number	05-103-10883-00	OGCC Facility ID Number	
6. Well/Facility Name:	Piceance Creek Unit	7. Well/Facility Number	297-13A7
8. Location (Qtr/Qtr, Sec, Twp, Rng, Meridian):	SWNE, Sec. 13, T2S, R97W, 6th P.M.	Surface Eqpm't Diagram	
9. County:	Rio Blanco	10. Field Name:	Piceance Creek
11. Federal, Indian or State Lease Number:	COD-052141	Technical Info Page	X
		Other	

Survey Plat
Directional Survey
Surface Eqpm't Diagram
Technical Info Page
Other

Complete the Attachment Checklist

OP OGCC

General Notice

<input type="checkbox"/> CHANGE OF LOCATION:	Attach New Survey Plat	(a change of surface qtr/qtr is substantive and requires a new permit)	
		FNU/FSL	FEL/FWL
Change of Surface Footage from Exterior Section Lines:			
Change of Surface Footage to Exterior Section Lines:			
Change of Bottomhole Footage from Exterior Section Lines:			
Change of Bottomhole Footage to Exterior Section Lines:			
Bottomhole location Qtr/Qtr, Sec, Twp, Rng, Mer			attach directional survey
Latitude			Distance to nearest property line
Longitude			Distance to nearest bldg, public rd, utility or RR
Ground Elevation			Is location in a High Density Area (rule 603b)?
			Yes/No
			Distance to nearest well same formation
			Surface owner consultation date:

GPS DATA:

Date of Measurement _____ PDOP Reading _____ Instrument Operator's Name _____

<input type="checkbox"/> CHANGE SPACING UNIT	<input type="checkbox"/> Remove from surface bond
Formation	Signed surface use agreement attached
Formation Code	
Spacing order number	
Unit Acreage	
Unit configuration	

<input type="checkbox"/> CHANGE OF OPERATOR (prior to drilling):	<input type="checkbox"/> CHANGE WELL NAME	NUMBER
Effective Date:	From:	
Plugging Bond:	To:	
<input type="checkbox"/> Blanket <input type="checkbox"/> Individual	Effective Date:	

<input type="checkbox"/> ABANDONED LOCATION:	<input type="checkbox"/> NOTICE OF CONTINUED SHUT IN STATUS
Was location ever built?	Date well shut in or temporarily abandoned:
<input type="checkbox"/> Yes <input type="checkbox"/> No	Has Production Equipment been removed from site? <input type="checkbox"/> Yes <input type="checkbox"/> No
Is site ready for inspection? <input type="checkbox"/> Yes <input type="checkbox"/> No	MIT required if shut in longer than two years. Date of last MIT
Date Ready for Inspection:	

<input type="checkbox"/> SPUD DATE:	<input type="checkbox"/> REQUEST FOR CONFIDENTIAL STATUS (6 mos from date casing set)
--	--

<input type="checkbox"/> SUBSEQUENT REPORT OF STAGE, SQUEEZE OR REMEDIAL CEMENT WORK	*submit cbl and cement job summaries
Method used	Cementing tool setting/perf depth
Cement volume	Cement top
Cement bottom	Date

<input type="checkbox"/> RECLAMATION:	Attach technical page describing final reclamation procedures per Rule 1004.
Final reclamation will commence on approximately <input type="checkbox"/> Final reclamation is completed and site is ready for inspection.	

Technical Engineering/Environmental Notice

<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Report of Work Done
Approximate Start Date:	Date Work Completed:
November 2010	

Details of work must be described in full on Technical Information Page (Page 2 must be submitted.)

<input type="checkbox"/> Intent to Recomplete (submit form 2)	<input type="checkbox"/> Request to Vent or Flare	<input type="checkbox"/> E&P Waste Disposal
<input type="checkbox"/> Change Drilling Plans	<input type="checkbox"/> Repair Well	<input type="checkbox"/> Beneficial Reuse of E&P Waste
<input type="checkbox"/> Gross Interval Changed?	<input type="checkbox"/> Rule 502 variance requested	<input type="checkbox"/> Status Update/Change of Remediation Plans
<input type="checkbox"/> Casing/Cementing Program Change	<input checked="" type="checkbox"/> Other: Install Plunger Lift	for Spills and Releases

I hereby certify that the statements made in this form are, to the best of my knowledge, true, correct and complete.

Signed: Lynn Neely Date: 10/29/2010 Email: lynn.r.neely@exxonmobil.comPrint Name: Lynn Neely Title: Regulatory SpecialistCOGCC Approved: [Signature] Title: ETS Date: 11/12/2010

CONDITIONS OF APPROVAL, IF ANY:

TECHNICAL INFORMATION PAGE



FOR OGCC USE ONLY

RECEIVED

NOV 05 2006

OGCC/Rifle Office

1. OGCC Operator Number:	28700	API Number:	05-103-10883-00
2. Name of Operator:	ExxonMobil Oil Corporation OGCC Facility ID # 0		
3. Well/Facility Name:	Piceance Creek Unit	Well/Facility Number:	297-13A7
4. Location (QtrQtr, Sec, Twp, Rng, Meridian):	SWNE, Sec. 13, T2S, R97W, 6th P.M.		

This form is to be completed whenever a Sundry Notice is submitted requiring detailed report of work to be performed or completed. This form shall be transmitted within 30 days of work completed as a "subsequent" report and must accompany Form 4, page 1.

5. DESCRIBE PROPOSED OR COMPLETED OPERATIONS

Plunger lift system will be installed on this well.

Three-phase or "wet gas" measurement meters have been installed on the flowlines for each of the plunger lift systems. This meter will be used for real time surveillance and plunger lift management only. The current well testing and allocation processed currently performed by operations will not change.

PLUNGER LIFT SYSTEM OVERVIEW

Plunger Lift Systems consist of a plunger, often referred to as a piston, two bumper springs, a lubricator to sense and stop the plunger as it arrives at the surface, and a surface controller of which several types are available. Various ancillary and accessory components are used to complement and support various application needs.

In a typical plunger lift operation, the plunger cycles between the lower bumper spring located in the bottom section of the production tubing string and the upper bumper spring located in the surface lubricator on top of the wellhead. In some applications, the lower bumper spring is placed above a gas lift mandrel. As the plunger travels to the surface, it creates a solid interface between the lifted gas below and produced fluid above to maximize lifting energy.

The plunger travels from the bottom of the well to the surface lubricator on the wellhead when the force of the lifting gas energy below the plunger is greater than the liquid load above the plunger. Any gas that bypasses the plunger during the lifting cycle flows up the production tubing and sweeps the area to minimize liquid fallback. The incrementation of the travel cycle is controlled by a surface controller and may be repeated as often as needed.

