

**CURRENT WELL SCHEMATIC**

Well Name Goodman Point #17 (GP #17)

Pilot API # 05-083-06640-00

S/T API # : 05-083-06640-01

Section 31 Township 37N Range 17W

Surface Hole: 2200' FSL, 208' FEL Section 31, T37N R17W NMPM Elevation 6746'

Spud Date: 3/24/2008

Pilot Completion Date: 4/19/2008

S/T Completion Date: 5/13/2008

**Conductor Casing**

Size 14 in

Set at 75 ft

Conductor @ 75 ft

**Conductor Cement**

cement with ready-mix to surface

**Surface Casing**

Size 9-5/8 in

Set at 3154 ft

Wt. 36 ppf Grade K-55 surface to 3154 ft

Hole Size 12-1/4 in

Est. T.O.C. surface ft

Csg Shoe @ 3154 ft

**Surface Cement**

Date Cemented: 3/31/2008

Lead : 1200 sxs 65/35/STD/Poz, 6% Gel, 10# sk Gilsonite,  
1/4# Polyflake

Tail : 200 sxs Class G, 1/8# Polyflake, 1/10% Halad-9

Note : circ 385 sx to pit, top out csg w/ 25 sx Class G

**Production Casing**

Size 7 in

Wt. 29 ppf

Grade 13 CR from surface to 5717 ft

Wt. 32 ppf

Grade 13 CR from 5717 to 7022 ft

Wt. 29 ppf

Grade 13 CR from 7022 to 7935 ft

Hole Size 8-3/4 in

Est. T.O.C. surface ft

**Prod Cement**

Date Cemented: 4/13/2008

Lead: 1800 sx 50/50/G/POZ, 2/10% Versaset  
1/10% Halad-766, 2% Zoneseal 4000, Foamed w/ N2

Tail: 300 sx 50/50/G/POZ, 2/10% Versaset,

1/10% Halad-766

Note : circ 300 sx to pit, top out csg w/ 100 sx Glass G

Tubing NA

Csg Shoe 7935 ft

PBTD/KOP 7940'

Open hole 5-7/8" 7940 - 9150' MD  
TVD 8132'

Pilot Hole TD 8359'