

FORM
2

Rev
12/05

State of Colorado
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80205 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

APPLICATION FOR PERMIT TO:

1. Drill, Deepen, Re-enter, Recomplete and Operate

2. TYPE OF WELL

OIL GAS COALBED OTHER _____
SINGLE ZONE MULTIPLE ZONE COMMINGLE ZONE

Refilling
Sidetrack

Document Number:
400062885
Plugging Bond Surety
20100017

3. Name of Operator: ENCANA OIL & GAS (USA) INC 4. COGCC Operator Number: 100185

5. Address: 370 17TH ST STE 1700
City: DENVER State: CO Zip: 80202-5632

6. Contact Name: MIRACLE PFISTER Phone: (720)876-3761 Fax: (720)876-4861
Email: miracle.pfister@encana.com

7. Well Name: TWIN CREEK Well Number: 12-6D1 (F12E)

8. Unit Name (if appl): HUNTER MESA Unit Number: COC55972E

9. Proposed Total Measured Depth: 6334

WELL LOCATION INFORMATION

10. QtrQtr: SEW Sec: 12 Twp: 7S Rng: 92W Meridian: 6
Latitude: 39.462080 Longitude: -107.618720

Footage at Surface: 2515 feet FNL 1626 feet FWL

11. Field Name: MAMM CREEK Field Number: 52500

12. Ground Elevation: 6143.8 13. County: GARFIELD

14. GPS Data:

Date of Measurement: 08/13/2008 PDOP Reading: 0.0 Instrument Operator's Name: TED TAGGART

15. If well is Directional Horizontal (highly deviated) **submit deviated drilling plan.**

Footage at Top of Prod Zone: FNL/FSL FEL/FWL Bottom Hole: FNL/FSL FEL/FWL
2100 FNL 2010 FWL 2100 FNL 2010 FWL
Sec: 12 Twp: 7S Rng: 92W Sec: 12 Twp: 7S Rng: 92W

16. Is location in a high density area? (Rule 603b)? Yes No

17. Distance to the nearest building, public road, above ground utility or railroad: 1056 ft

18. Distance to nearest property line: 337 ft 19. Distance to nearest well permitted/completed in the same formation: 470 ft

20. LEASE, SPACING AND POOLING INFORMATION

Objective Formation(s)	Formation Code	Spacing Order Number(s)	Unit Acreage Assigned to Well	Unit Configuration (N/2, SE/4, etc.)
Iles	ILES			
Williams Fork	WMFK			

21. Mineral Ownership: Fee State Federal Indian Lease #: _____

22. Surface Ownership: Fee State Federal Indian

23. Is the Surface Owner also the Mineral Owner? Yes No Surface Surety ID#: _____

23a. If 23 is Yes: Is the Surface Owner(s) signature on the lease? Yes No

23b. If 23 is No Surface Owners Agreement Attached or \$25,000 Blanket Surface Bon \$2,000 Surface Bond \$5,000 Surface Bond

24. Using standard QtrQtr, Sec, Twp, Rng format enter entire mineral lease description upon which this proposed wellsite is located (attach separate sheet/map if you prefer):
 T7S-R92W SECTION 1: W2SE, LESS THAT PART OF THE NW/4SE/4 LYING EAST OF A LINE LYING FIVE (5) FEET EASTERLY OF AND PARALLEL TO THE EASTERLY BANK OF EAST DIVIDE CREEK; E2SW SECTION 12: W2NE, E2NW, SWNW, NESW, NWSE.

25. Distance to Nearest Mineral Lease Line: 890 ft 26. Total Acres in Lease: 443

DRILLING PLANS AND PROCEDURES

27. Is H2S anticipated? Yes No If Yes, attach contingency plan.

28. Will salt sections be encountered during drilling? Yes No

29. Will salt (>15,000 ppm TDS CL) or oil based muds be used during drilling? Yes No

30. If questions 27 or 28 are yes, is this location in a sensitive area (Rule 903)? Yes No **If 28, 29, or 30 are "Yes" a pit permit may be required.**

31. Mud disposal: Offsite Onsite
 Method: Land Farming Land Spreading Disposal Facility Other: _____

Note: The use of an earthen pit for Recompletion fluids requires a pit permit (Rule 905b). If air/gas drilling, notify local fire officials.

Casing Type	Size of Hole	Size of Casing	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top
CONDUCTOR	20	16	LINEPIPE		40	5	40	0
SURF	12+1/4	9+5/8	36		1,112	536	1,112	0
1ST	7+7/8	4+1/2	11.6		6,334	648	6,334	0

32. BOP Equipment Type: Annular Preventer Double Ram Rotating Head None

33. Comments Top of cement for production casing will be 500' above the top of gas. Related Form 2A Doc # is 400060081.

34. Location ID: _____

35. Is this application in a Comprehensive Drilling Plan ? Yes No

36. Is this application part of submitted Oil and Gas Location Assessment ? Yes No

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Miracle Pfister

Title: Regulatory Analyst Date: 5/19/2010 Email: miracle.pfister@encana.com

Based on the information provided herein, this Application for Permit-to-Drill complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: David S. Nesline Director of COGCC Date: 1/31/2011

API NUMBER
05 045 20393 00

Permit Number: _____ Expiration Date: 1/30/2013

CONDITIONS OF APPROVAL, IF ANY: _____

All representations, stipulations and conditions of approval stated in the Form 2A for this location shall constitute representations, stipulations and conditions of approval for this Form 2 Permit-to-Drill and are enforceable to the same extent as all other representations, stipulations and conditions of approval stated in this Permit-to-Drill.

- 1) COMPLIANCE WITH THE MOST CURRENT REVISION OF THE NORTHWEST COLORADO NOTIFICATION POLICY IS REQUIRED.
- 2) GARFIELD COUNTY RULISON FIELD NOTICE TO OPERATORS. NOTE: ALL NOTICES SHALL BE GIVEN VIA E-MAIL. SEE ATTACHED NOTICE
- 3) NEW MAMM CREEK FIELD NOTICE TO OPERATORS APPLIES TO THIS WELL. NOTE: ALL NOTICES SHALL BE GIVEN VIA E-MAIL. SEE ATTACHED NOTICE
- 4) THE PROPOSED SURFACE CASING IS MORE THAN 50' BELOW THE DEPTH OF THE DEEPEST WATER WELL WITHIN 1 MILE OF THE SURFACE LOCATION WHEN CORRECTED FOR ELEVATION DIFFERENCES. THE DEEPEST WATER WELL WITHIN 1 MILE IS 450 FEET DEEP.
- 5) SUBMIT PASON OR EQUIVALENT MUD LOG DATA FROM SURFACE TO TOTAL WELL DEPTH WITH THE REQUEST TO COMPLETE.
- 6) SUBMIT ALL ELECTRONIC DRILLING RECORDER DATA IN ADDITION TO A MUD/DRILLING LOG FROM SURFACE TO TOTAL DEPTH DRILLED FOR THE FIRST WELL DRILLED ON THIS PAD WITH THE FOLLOWING CURVATURE DATA: RATE OF PENETRATION (ROP), GAS, MUD VOLUME, TORQUE, DIFFERENTIAL PRESSURE AND WEIGHT ON BIT (WOB).
- 7) SUBMIT THE FOLLOWING OPEN-HOLE LOGS ON THE SURFACE HOLE FOR THE FIRST WELL DRILLED ON THIS PAD, VIA EMAIL TO COGCC WESTERN COLORADO ENGINEERING SUPERVISOR, WITHIN 24 HRS OF RUNNING AND WITH FORM 5: SPONTANEOUS POTENTIAL, GAMMA RAY, FORMATION DENSITY, COMPENSATED NEUTRON, AND RESISTIVITY (TRIPLE COMBO).
- 8) SUBMIT THE FOLLOWING OPEN-HOLE LOGS ON THE PRODUCTION HOLE, FOR AT LEAST ONE WELL PER PAD (ON THE F12E, PREFERABLY ONE OF THE WELLS BEING DRILLED TO THE NORTHWEST OF THE PAD), FROM TOTAL WELL DEPTH TO SURFACE CASING SHOE WITH FORM 5: SPONTANEOUS POTENTIAL, GAMMA RAY, FORMATION DENSITY, COMPENSATED NEUTRON, AND RESISTIVITY (TRIPLE COMBO).
- 9) 80% EXCESS CEMENT, OVER THE CALCULATED VOLUME REQUIRED TO FILL THE ENTIRE ANNULUS, IS REQUIRED TO BE PUMPED ON THE SURFACE CASING CEMENT JOB. SUBMIT CEMENT TICKETS AS AN ATTACHMENT TO THE REQUEST TO COMPLETE, FOR VERIFICATION OF CEMENT VOLUMES.
- 10) IF LOST CIRCULATION OF 20 BBL/HR OR MORE IS EXPERIENCED AT ANY TIME DURING THE DRILLING OF THIS WELL, OPERATOR SHALL STOP DRILLING, PUMP LOST CIRCULATION MATERIAL AS NEEDED.
- 11) IF LOST CIRCULATION OF 100+ BBL WITHIN 24 HR OR MAJOR GAS (GAS OVER 1800 UNITS WHILE DRILLING) OCCURS AT A TRUE VERTICAL DEPTH LESS THAN 4200', OPERATOR SHALL NOTIFY COGCC'S WESTERN COLORADO ENGINEERING SUPERVISOR WITHIN 24 HOURS, AND PRIOR TO RUNNING CASING, TO DISCUSS THE OPTIONS FOR UTILIZING A DV TOOL ON PRODUCTION OR INTERMEDIATE CASING.
- 12) PRODUCTION CASING CEMENT TOP MUST BE 500' ABOVE THE SHALLOWEST GAS SIGNATURE OBSERVED ON MUD LOGS OR OPEN-HOLE LOGS. THE SHALLOWEST GAS SIGNATURE, AS DEFINED BY 2500 UNITS, DEPTH SHALL BE REPORTED ON THE REQUEST TO COMPLETE.
- 13) SURFACE CASING SHALL BE SET A MINIMUM OF 50' BELOW THE MOLINA MEMBER OF THE WASATCH FORMATION. THE MOLINA AND ATWELL GULCH MEMBERS OF THE WASATCH FORMATION TOPS SHALL BE REPORTED ON THE REQUEST TO COMPLETE.
- 14) SUBMIT 48 HOUR NOTICES, VIA EMAIL, FOR RUNNING AND CEMENTING ALL CASING STRINGS AND PERFORMING A WELL CONTROL DRILL TO COGCC'S GARFIELD COUNTY FIELD INSPECTOR, COGCC'S NORTHWEST AREA FIELD INSPECTION SUPERVISOR, AND COGCC'S WESTERN COLORADO ENGINEERING SUPERVISOR. CONTACT INFORMATION FOR NOTICES CAN BE FOUND ON COGCC'S CURRENT NOTIFICATION POLICY.
- 15) FRESH WATER DRILLING MUD MUST BE UTILIZED DURING THE DRILLING OF THE SURFACE CASING

INTERVAL, AS OPPOSED TO WATER ONLY. MUD THAT HAS BEEN USED TO DRILL A PRODUCTION INTERVAL MAY NOT BE REUSED TO DRILL ANOTHER SURFACE INTERVAL.

16)CENTRALIZER SYSTEMS MUST BE DESIGNED TO ACHIEVE A MINIMUM OF 50% STANDOFF ON ALL CASING STRINGS. REPORT CENTRALIZER PLACEMENT AND CALCULATED STANDOFF ON THE REQUEST TO COMPLETE.

17)RUN A CEMENT EVALUATION TOOL ON ALL CASING STRINGS, BEFORE DRILL OUT OF EACH SHOE, FROM FLOAT COLLAR TO SURFACE. TIMING OF THE LOGS SHALL BE BASED ON COMPRESSIVE STRENGTH TESTS OF SLURRIES PROVIDED BY CEMENT SERVICE PROVIDER. ALL LOGS SHALL BE PROVIDED WITH THE REQUEST TO COMPLETE

18)UTILIZE INTERMEDIATE CASING IF THE FORMATION INTEGRITY TEST FAILS OR IF THE SURFACE CASING REQUIRES PERFORATION AND CEMENT SQUEEZING.

19)SUBMIT DAILY DRILLING REPORTS TO COGCC WITH THE REQUEST TO COMPLETE.

20)SUBMIT DAILY WELL STIMULATION REPORTS TO COGCC WITH THE FORM 5 DRILLING COMPLETION REPORT.

21)COLLECT SAMPLES FOR LABORATORY ANALYSIS FROM THE 2 DOMESTIC WATER WELLS LOCATED WITHIN ½ MILE OF THE F12E WELL PAD (LANGEgger AND EICHER WELLS) AND EXISTING MONITORING WELLS (MW-2 AND (MW-4) PRE-AND POST-DRILLING OF GAS WELLS TWIN CREEK 12-4A1, TWIN CREEK 12-4D1, TWIN CREEK 12-5A2, TWIN CREEK 12-5A1, AND TWIN CREEK 12-5D1. WATER SAMPLE ANALYSIS MUST INCLUDE DISSOLVED METHANE, BTEX, MAJOR ANIONS AND CATIONS. IF THE CONCENTRATION OF DISSOLVED METHANE IS >1.1 MG/L, COLLECT A SAMPLE FOR ANALYSIS OF GAS COMPOSITION AND OF THE STABLE ISOTOPES OF METHANE.

22)CONDUCT DOCUMENTED VISUAL MONITORING OF WEST DIVIDE CREEK (WDC) AND OTHER SURFACE STREAMS AND PONDS IN SECTION 12, R7S T92W FOR THE PRESENCE OF NATURAL GAS, AIR, OR OTHER GAS BUBBLES WHILE DRILLING AND FRACING GAS WELLS TWIN CREEK 12-4A1, TWIN CREEK 12-4D1, TWIN CREEK 12-5A2, TWIN CREEK 12-5A1, AND TWIN CREEK 12-5D1.

23)INCREASE FREQUENCY AND FOCUS OF DOCUMENTED VISUAL MONITORING OF WDC IN SECTIONS 12, R7S T92W WHEN THE BOREHOLE OF ANY GAS WELL BEGINS TO PASS BENEATH WDC.

24)IF VISUAL MONITORING OR ANY OTHER OBSERVATION INDICATES THAT THERE IS AN INCREASE IN THE PRESENCE NATURAL GAS, AIR, OTHER GAS OR FLUID DISCHARGING INTO WDC, OTHER SURFACE WATER, OR GROUND WATER WHILE DRILLING AND FRACING, NOTIFY COGCC STAFF AND LANDOWNER AS SOON AS PRACTICAL, BUT NO LATER THAN 24 HOURS AFTER OBSERVATION

25)IF VISUAL MONITORING OR ANY OTHER OBSERVATION INDICATES THAT THERE IS AN INCREASE IN THE PRESENCE OF NATURAL GAS, AIR, OTHER GAS, OR FLUID DISCHARGING INTO WDC, OTHER SURFACE WATER, OR GROUND WATER DURING DRILLING AND FRACING, SUBMIT THE CHEMICAL INVENTORY (REFER TO RULE 205.C) TO THE COGCC AS SOON AS PRACTICAL, BUT NO LATER THAN 24 HOURS AFTER OBSERVATION.

26)IF VISUAL MONITORING OR ANY OTHER OBSERVATION INDICATES THAT THERE IS AN INCREASE IN THE PRESENCE OF NATURAL GAS, AIR, OTHER GAS, OR FLUID DISCHARGING INTO WDC, OTHER SURFACE WATER, OR GROUND WATER DURING DRILLING AND FRACING, COLLECT SAMPLES FOR LABORATORY ANALYSIS FROM SURFACE WATER BODIES AND ALL WELLS IDENTIFIED IN COA ENV-1. THE SAMPLES SHALL BE ANALYZED FOR THE PARAMETER LIST IDENTIFIED IN COA ENV-1 AND OTHER PARAMETERS AGREED TO BASED ON THE CHEMICAL INVENTORY OR OTHER PROCESS KNOWLEDGE.

27)PROVIDE A SCHEDULE AND LOCATIONS FOR VISUAL MONITORING OF WDC AND SURFACE WATER BODIES. THE SCHEDULE WILL BE APPROVED BY COGCC STAFF PRIOR TO INITIATION OF DRILLING ACTIVITIES.

Attachment Check List

Att Doc Num	Name
400062885	FORM 2 SUBMITTED
400062979	PLAT
400062980	DEVIATED DRILLING PLAN
400062982	30 DAY NOTICE LETTER
400062983	SURFACE AGRMT/SURETY
400062984	LEGAL/LEASE DESCRIPTION
400062986	LEGAL/LEASE DESCRIPTION

Total Attach: 7 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Agency	WO LETTER RESPONSE	8/16/2010 10:34:26 AM
Permit	WO LETTER RESPONSE MAMM CREEK ISSUE DO NOT PROCESS AT THIS TIME ; 6/29/10 BY	

Total: 2 comment(s)

BMP

<u>Type</u>	<u>Comment</u>

Total: 0 comment(s)