
Schlumberger
Dual Induction Spherically Focused Log
Run No. : ONE
Depth Driller : 1,000 m
Depth Logger : 1,000 m
Bottom Log Interval : 1,000 m
Top Log Interval : 0 m
Casing Driller : 0 m @ 0 m
Casing Logger : 0 m @ 0 m
Bit Size : 0 mm
Type Fluid in Hole : WATER BASED MUD
Density : 1.0 g/cm3
Viscosity : 0 s
Fluid Loss : 0 cm3
Source of Sample : CIRCULATION
Rm @ Meas. Temp : 0 ohm-m @ 0 °C
Rmf @ Meas. Temp : 0 ohm-m @ 0 °C
Rmc @ Meas. Temp : 0 ohm-m @ 0 °C
Source Rmf : Rmc :
Rm @ BHT : 0 ohm-m @ 0 °C
Time Since Circulation : 0 hr
Time on Bottom : 0 hr
Max. Recorded Temp : 0 °C
Equipment Number : 0
Location : 0
Recorded By : 0
Witnessed By : 0

6400

6500

6600

Gamma Ray

TT3FT

CCL

3' Amplitude

Amplified Amplitude

Variable Density

14	Collar Locator	-1
0	Gamma Ray (GAPI)	180
280	TT3FT (usec)	180

0	Amplified Amplitude (mV)	30
0	3' Amplitude (mV)	100

200	Variable Density	1200