

# MATERIAL SAFETY DATA SHEET

OSHA - Meets 29 CFR 1910.1200 Standards



## HMIS HAZARD RATINGS

HEALTH	2	* = Chronic Health Hazard	2 = MODERATE
FLAMMABILITY	0	0 = INSIGNIFICANT	3 = HIGH
PHYSICAL HAZARD	0	1 = SLIGHT	4 = EXTREME

## TRANSPORTATION INFORMATION

PROPER SHIPPING NAME:	Corrosive liquid, n.o.s. (hydrochloric acid, hydroxyacetic acid)		
HAZARD CLASS / PKG GRP:	8 / II	REF:	49 CFR 173.154, .202, .242
IDENTIFICATION NUMBER:	UN 1760	LABEL:	CORROSIVE

## SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST)

**LIQUID ACID DESCALER**

Page 1 of 2

MANUFACTURER'S NAME

Cotey Chemical Corporation

EMERGENCY TELEPHONE NUMBER

Infotrac (800) 535-5053 Outside USA (352) 323-3500

ADDRESS (NUMBER, STREET, P.O. BOX)

4410 M.L.K. Blvd.

TELEPHONE NUMBER FOR INFORMATION

(800) 457-2096

(CITY, STATE AND ZIP CODE)

Lubbock, TX 79404-

DATE PREPARED: March 25, 2009

SUPERSEDES: October 3, 2007

## SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS

(SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))

CAS #

%

(OPTIONAL)

OSHA PEL

ACGIH TWA

SARA

RQ

PPM

MG/M3

PPM

MG/M3

TITLE III

LBS

Hydroxyacetic acid

79-14-1

10 - 30

not established

Hydrochloric acid (a,b,c)

7647-01-0

10 - 30

5C

7C

5C

5000

(a) The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment of the Reportable Quantity (RQ for this mixture = 20,000 lbs) or greater amounts, according to 40 CFR 302.

(b) A "C" in the OSHA PEL or ACGIH TWA column indicates ceiling limits, the concentration that should not be exceeded during any part of the working exposure.

(c) OSHA proposed a regulation (29 CFR 1910.119) to monitor and control safety at certain types of industrial facilities. Compliance is triggered by specified quantities of specific chemicals. Minimum threshold quantity for this Highly Hazardous Chemical is 5,000 lbs.

## SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE

INHALATION: Corrosive and irritating to upper respiratory tract.

EMERGENCY AND FIRST AID PROCEDURES

Remove affected person to fresh air; if breathing has not returned to normal within a few minutes after exposure, get medical attention.

SKIN: Corrosive and irritating; chemical burns may result from contact.

Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

EYES: CORROSIVE; Contact with eyes is painful and irritating and will cause chemical burns.

Remove contact lenses. Immediately flush eyes for 15 minutes in clear running water while holding eyelids open; seek medical attention immediately.

INGESTION: Corrosive and irritating to digestive tract; vomiting may occur.

Drink two glasses of water followed by milk, milk of magnesia or other non-alcoholic liquids; DO NOT induce vomiting; seek medical attention immediately.

HEALTH HAZARDS (ACUTE AND CHRONIC): Corrosive to skin and eyes; prolonged inhalation of this product may cause ulcers to the upper respiratory tract, no long term health effects are known at this time, however, repeated contact with eyes may cause severe irritation.

CARCINOGENICITY

NTP?

No

IARC MONOGRAPHS?

No

OSHA REGULATED?

No

California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986 - there are no reportable chemicals present known to the state to cause cancer or reproductive toxicity.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin, eye, or respiratory disorders may become aggravated through prolonged exposure.

ISSUED: January 3, 2011



MATERIAL SAFETY DATA SHEET			
IDENTITY (AS USED ON LABEL AND LIST) LIQUID ACID DESCALER		Page 2 of 2 Date: March 25, 2009	
<b>SECTION 4 - FIRE FIGHTING MEASURES</b>			
FLASH POINT (METHOD USED) Non-flammable	NFPA RATING None	FLAMMABLE LIMITS LEL: Not applicable UEL: Not applicable	
EXTINGUISHING MEDIA Carbon dioxide, water, water fog, dry chemical, chemical foam			
SPECIAL FIRE FIGHTING PROCEDURES Keep containers cool with water spray to prevent container rupture due to steam buildup; CAUTION - material is corrosive.			
UNUSUAL FIRE AND EXPLOSION HAZARDS None			
<b>SECTION 5 - ACCIDENTAL RELEASE MEASURES</b>			
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: CAUTION - CORROSIVE. Wash small spills to sanitary sewer. Confine large spill, soak up with approved absorbent, shovel product into approved container; for spills in excess of allowable limits (RQ) notify the National Response Center (800) 424 - 8802; refer to CERCLA 40 CFR 302 for detailed instructions concerning reporting requirements.			
<b>SECTION 6 - HANDLING AND STORAGE</b>			
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. CAUTION - material is corrosive. Keep this and other chemicals out of reach of children.			
<b>SECTION 7 - EXPOSURE CONTROLS / PERSONAL PROTECTION</b>			
RESPIRATORY PROTECTION (SPECIFY TYPE): None required while threshold limits (Section 2) are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.			
VENTILATION	LOCAL EXHAUST: Required MECHANICAL (GENERAL): Yes	SPECIAL: To maintain minimum TWA and STEL levels. OTHER: Engineering and work controls as required.	
PROTECTIVE GLOVES: Neoprene or rubber gloves with cuffs.		EYE PROTECTION: Goggles with side shields; safety eyebath nearby.	
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Coveralls, apron, or other equipment should be worn to minimize skin contact.			
WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.			
<b>SECTION 8 - PHYSICAL / CHEMICAL PROPERTIES</b>			
BOILING POINT 212° F	SPECIFIC GRAVITY (WATER = 1) 1.190		
VAPOR PRESSURE (MM Hg) 17 mm Hg @ 20 ° C	pH < 1.0		
VAPOR DENSITY (AIR = 1) > 1	EVAPORATION RATE (WATER = 1) < 1		
SOLUBILITY IN WATER Complete	% VOLATILE (BY WEIGHT) 100%		
APPEARANCE AND ODOR Pale yellow liquid, burnt sugar odor			
<b>SECTION 9 - STABILITY AND REACTIVITY</b>			
STABILITY	UNSTABLE: STABLE: X	CONDITIONS TO AVOID: Extreme temperatures	
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids, strong alkalis			
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, chlorine, hydrocarbons, fumes, and smoke may be produced.			
HAZARDOUS POLYMERIZATION	MAY OCCUR: WILL NOT OCCUR: X	CONDITIONS TO AVOID: None	
<b>SECTION 10 - DISPOSAL CONSIDERATIONS</b>			
WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations for corrosive materials. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals.			
The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.			