

VISIBLE IMPROVEMENTS

1. THE BESTWAY DIRECTIONAL #1 LOCATION REFERENCE POINT WAS PERMANENTLY SET WITH A 5/8" REBAR AND WILL BE MAINTAINED THROUGH THE CONSTRUCTION/DRILLING OF THE ENTIRE WELL PAD.
2. ALL DISTANCES AND BEARINGS REPORTED IN THE VISIBLE IMPROVEMENTS TABLE ARE MEASURED FROM THE WELL REFERENCE POINT.

VISIBLE IMPROVEMENTS TABLE			
#	DESCRIPTION	DISTANCE	BEARING
1	HOUSE	600'	SW
2	HOUSE	530'	SW
3	HOUSE	580'	SW
4	HOUSE	440'	SW
5	HOUSE	505'	SW
6	HOUSE	580'	SW
7	HOUSE	555'	S
8	HOUSE	485'	S
9	HOUSE	415'	S
10	HOUSE	400'	SE
11	HOUSE	470'	SE
12	HOUSE	445'	SE
13	HOUSE	510'	SE
14	HOUSE	530'	SE

VISIBLE IMPROVEMENTS TABLE			
#	DESCRIPTION	DISTANCE	BEARING
15	HOUSE	605'	SE
16	HOUSE	655'	SE
17	HOUSE	675'	E
18	HOUSE	630'	SW
19	SHED	555'	SW
20	SHED	560'	SW
21	SHED	600'	W
22	SS MANHOLE	575'	SW
23	SS MANHOLE	415'	SW
24	SS MANHOLE	415'	SE
25	SS MANHOLE	575'	SE
26	SS MANHOLE	650'	SE
27	POWER POLE	490'	SW
28	POWER POLE	495'	SW

VISIBLE IMPROVEMENTS TABLE			
#	DESCRIPTION	DISTANCE	BEARING
29	POWER POLE	400'	SW
30	POWER POLE	370'	S
31	POWER POLE	395'	SE
32	POWER POLE	440'	SE
33	POWER POLE	560'	SE
34	POWER POLE	630'	SE
35	POWER POLE	325'	SE
36	POWER POLE	540'	SW
37	WATER WELLS	590'	NW
38	O&G WELL	700'	NE
39	4TH STREET	305'	S
40	PROPERTY LINE	69'	S

LOCATION
NE/4, SEC 2, T5N, R66W

