

**COMPACT WELL SHUTTLE  
COMPENSATED SONIC  
LOG**

COMPANY **EXXON MOBIL CORPORATION**  
 WELL **FREEDOM RANCH UNIT 197-33B8**  
 FIELD **PICEANCE CREEK**  
 PROVINCE/COUNTY **RIO BLANCO**  
 COUNTRY/STATE **U.S.A. / COLORADO**  
 LOCATION **SHL: 2397' FNL & 1406' FEL**

LSD SEC TWP RGE Other Services  
 33 1S 97W MPD/MDN  
 MAI/MFE

API Number 05-103-1142100  
 Permit Number 05-103-1142100

Permanent Datum G.L., Elevation 6446 feet  
 Log Measured From K.B. @ 30 FEET above Permanent Datum  
 Drilling Measured From K.B.

Date	20-FEB-2010	Elevations:	KB	6476.00
Run Number	TWO	DF	6475.00	
Depth Driller	12830.00	GL	6446.00	
Depth Logger	12796.00			
First Reading	12781.00			
Last Reading	8655.00			
Casing Driller	8657.00			
Casing Logger	8655.00			
Bit Size	6.125			
Hole Fluid Type	LSND			
Density / Viscosity	9.80 lb/USg	48.00 CP		
PH / Fluid Loss	9.40	7.50 ml/30Min		
Sample Source	FLOWLINE			
Rm @ Measured Temp	2.34 @ 78.0	ohm-m		
Rmf @ Measured Temp	1.87 @ 78.0	ohm-m		
Rmc @ Measured Temp	2.80 @ 78.0	ohm-m		
Source Rmf / Rmc	CALC	CALC		
Rm @ BHT	0.775 @242.0	ohm-m		
Time Since Circulation	.5 HOURS			
Max Recorded Temp	242.00	deg F		
Equipment Name	COMPACT			
Equipment / Base	13038	GDUCT		
Recorded By	C. PHILLIPS			
Witnessed By	C. JARVIS			
Last Title	Last Line			

BOREHOLE RECORD			Last Edited: 20-FEB-2010 17:56
Bit Size inches	Depth From feet	Depth To feet	
6.125	8657.00	12830.00	

CASING RECORD				
Type	Size inches	Depth From feet	Shoe Depth feet	Weight pounds/ft
INTERMED	7.000	0.00	8657.00	26.00

**REMARKS**

TOOLS: COMPACT WELL SHUTTLE. GAMMA RAY, NEUTRON, DENSITY, FOCUSED ELECTRIC, SONIC, AND INDUCTION RAN IN COMBINATION.

HARDWARE: DENSITY: 4 INCH PROFILE PLATE USED.  
 FOCUSED ELECTRIC: INLINE CENTRALIZERS USED.  
 SONIC: INLINE CENTRALIZERS USED.  
 INDUCTION: INLINE CENTRALIZERS USED.  
 DUAL BOWSPRINGS USED FOR ECENTRALIZATION OF POROSITY TOOLS.

2.65 G/CC DENSITY MATRIX USED TO CALCULATE POROSITY.

ALL INTERVALS LOGGED AND SCALED PER CUSTOMER'S REQUEST.

DEPTH CONTROL TAKEN FROM PIPE STRAP AND TIED INTO INTERMEDIATE LOG.

TOTAL HOLE VOLUME FROM T.D. TO SURFACE CASING = 955 CUBIC FEET

ANNULAR HOLE VOLUME FROM T.D. TO SURFACE CASING BASED ON 4.5" PRODUCTION CASING = 495 CUBIC FEET

ENGINEER(S): C. PHILLIPS, M. RICHINS

OPERATOR: D. GARVIN

SERVICE ORDER: #3521370


RIG: HP 321



\*\*\*Sonic Delta T corrected in Houston Subsurface Evaluation Services Center.

All interpretations are opinions based on inferences from electrical or other measurements and we cannot, and do not, guarantee the accuracy or correctness of any interpretations, and we shall not, except in the case of gross or wilful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions in our price schedule.

2 INCH MAIN LOG 1: 600

Depth Based Data - Merged File Plotted on 26-FEB-2010 07:31  
 Filename: C:\DOCUME~1\Hopkinjg\LOCALS~1\Temp\Weatherford PreView\0\depth\_dtc\_repair.mge Merged on 25-FEB-2010 12:26  
 System Versions: Merged 24-NOV-2009 Plotted with 10.01.0765





8800

214

8900

215

9000

217

9100

218



9200


219

9300


Delta I Compressional


Sandstone Sonic Porosity











239

11600

239

11700

239

11800

239

11900

240

12000

239


← Bit Size


← Density Caliper

← Gamma Ray

Delta T Compressional

Sandstone Sonic Porosity







Depth Based Data - Merged File  
 Filename: C:\DOCUME~1\Hopkinjg\LOCALS~1\Temp\Weatherford PreView\0\depth\_dtc\_repair.mge  
 System Versions: Merged 24-NOV-2009 Plotted with 10.01.0765  
 Plotted on 26-FEB-2010 07:31  
 Merged on 25-FEB-2010 12:26

**5 INCH MAIN LOG**

Depth Based Data - Merged File  
 Filename: C:\DOCUME~1\Hopkinjg\LOCALS~1\Temp\Weatherford PreView\0\depth\_dtc\_repair.mge  
 System Versions: Merged 24-NOV-2009 Plotted with 10.01.0765  
 Plotted on 26-FEB-2010 07:31  
 Merged on 25-FEB-2010 12:26





Borehole  
Temp in  
deg F

Replay  
Scale  
1:240




C8650g  
Shoe



210°


8700

212°

8750







216°

9000

216°

9050


217°



9100


217°

9150

218°







221°

9450

222°

9500


222°

9550



223°


9600

Sandstone Sonic Porosity →




→ Transit Time






9900  
225°  
9950  
226°  
10000  
227°  
10050  
227°



← Bit Size  
← Density Caliper  
← Gamma Ray

Delta-T Compressional  
Sandstone Sonic Porosity  
6' Transit Time  
Transit Time  
4' Transit Time  
3' Transit Time



228°

10100

228°

10150


229°



10200


229°

10250

230°







231°

10550

232°


10600



232°

10650

233°

10700





233°

10750

233°

10800

234°

10850

234°

10900

235°

10950

← Bit Size

← Density Caliper

← Gamma Ray

Delta T Compressional



Sandstone Sonic Porosity


6' Transit Time



5' Transit Time

4' Transit Time

3' Transit Time







11400

238°

11450

238°

11500

239°

11550

239°

11600

← Bit Size

Delta T Compressional →



Sandstone Sonic Porosity →



6' Transit Time →

5' Transit Time →

4' Transit Time →

3' Transit Time →





239°

11850

239°

11900

240°


11950

240°

12000

240°

12050



12050

239°

12100

239°


12150


239°

12200

238°

12250





238°

12300

238°

12350


237°


12400

236°

12450

235°





12500

235°

12550

235°


12600


235°

12650

242°

12700





12750

12800

12808

DSC  
in  
Feet

← Timing Marks  
every 60.0 sec


Gamma Ray(GRGC)  
API  
0 75 150  
150 225 300

Density Caliper(CLDC)  
inches  
4 9 14

Bit Size(BIT)  
inches  
4 9 14

Borehole  
Temp in  
deg F

Replay  
Scale  
1:240



Sandstone Sonic Porosity(SPRS)  
v/v  
0.30 0.20 0.10 0.00 -0.10

Delta T Compressional(DTP)  
140 115 90 65 40

3' Transit Time(TR21)  
microseconds  
1100 600 100

4' Transit Time(TR11)  
microseconds  
1100 600 100

5' Transit Time(TR22)  
microseconds  
1100 600 100

6' Transit Time(TR12)  
microseconds  
1100 600 100

↑ **5 INCH MAIN LOG** ↑

**BEFORE SURVEY CALIBRATION**

C:\DOCUME~1\Hopkinjg\LOCALS~1\Temp\Weatherford PreView\0\depth.dta

**General Constants All 000** Last Edited on 20-FEB-2010,04:45

**General Parameters**

Mud Resistivity	2.340	ohm-metres
Mud Resistivity Temperature	78.000	degrees F
Water Level	0.000	feet
Density/Neutron Processing	Wet Hole	

**Hole/Annular Volume and Differential Caliper Parameters**

HVOL Method	0	
HVOL Caliper 1	Density Caliper	
HVOL Caliper 2	None	
Annular Volume Diameter	4.500	inches
Caliper for Differential Caliper	Density Caliper	

**Rwa Parameters**

Porosity used	Base Density Porosity
Resistivity used	Deep Induction
RWA Constant A	0.610
RWA Constant M	2.150

**Down-hole Tension Calibration SMS 000** Field Calibration on 25-JAN-2010 11:38

Reading No	Measured	Calibrated (lbs)
1	14334.21	0.00
2	15360.88	400.00

**Gamma Calibration MCG 342** Field Calibration on 19-FEB-2010,22:21

	Measured	Calibrated (API)
Background	86	58
Calibrator (Gross)	1023	684
Calibrator (Net)	937	626

**Gamma Constants MCG 342** Last Edited on 20-FEB-2010,04:45

Gamma Calibrator Number	GRC-005	
Mud Density	1.00	gm/cc
Caliper Source for Processing	Density Caliper	
Tool Position	Eccentred	
Concentration of KCl	0.00	kppm

**SP Calibration MCG 342** Field Calibration on 19-FEB-2010,22:21

	Measured	Calibrated (mV)
Reference 1	100.0	100.0
Reference 2	-100.0	-100.0

**High Resolution Temperature Calibration MCG 342** Field Calibration on 19-FEB-2010,22:22

	Measured	Calibrated(Deg F)
Lower	10.00	10.00
Upper	100.00	100.00

**High Resolution Temperature Constants MCG 342** Last Edited on 8-DEC-2009,15:54

Pre-filter Length	11
-------------------	----

**Neutron Calibration MDN 250** Base Calibration on 25-AUG-2009 11:29  
Field Check on 19-FEB-2010 21:40

Base Calibration

Measured      Calibrated (cps)

	Near	Far	Near	Far
	2977	91	3714	110
Ratio	32.702		33.764	

Field Calibrator at Base

	Calibrated (cps)
	1610      2357
Ratio	0.683

Field Check

	Calibrated (cps)
	1694      2474
Ratio	0.684

Neutron Constants MDN 250

Last Edited on 19-FEB-2010,22:22

Neutron Source Id	755	
Neutron Jig Number	6532	
Epithermal Neutron	No	
Caliper Source for Processing	Density Caliper	
Stand-off	0.00	inches
Mud Density	1.00	gm/cc
Limestone Sigma	7.10	cu
Sandstone Sigma	7.00	cu
Dolomite Sigma	4.70	cu
Formation Pressure Source	None	
Formation Pressure	N/A	kpsi
Temperature Source	Constant Value	
Temperature	20.00	degrees F
Mud Salinity	0.00	kppm
Formation Fluid Salinity Source	None	
Formation Fluid Salinity	N/A	kppm
Barite Mud Correction	Not Applied	

FE Calibration MFE 236

Base Calibration on 5-DEC-2009 15:33  
Field Check on 19-FEB-2010 21:54

Base Calibration		
	Measured	Calibrated (ohm-m)
Reference 1	0.0	0.0
Reference 2	963.9	126.8
Base Check		281.2
Field Check		281.4

FE Constants MFE 236

Last Edited on 19-FEB-2010,22:22

Running Mode	No Sleeve
MFE K Factor	0.1268
Caliper Source for FE correction	Density Caliper
Caliper Value for FE correction	N/A
Rm Source for FE correction	Temperature Corr
Temp. for Rm Corr.	MCG External Temperature
Stand-off	1.0
	inches

Sonic Constants MSS 221

Last Edited on 19-FEB-2010,22:22

Maximum Boundary Contrast	60.00	micro-sec/ft
Fluid Transit Time	189.00	micro-sec/ft
Limestone Transit Time	47.50	micro-sec/ft
Sandstone Transit Time	55.50	micro-sec/ft
Dolomite Transit Time	43.50	micro-sec/ft
Sonic used for Porosities	3-5' Compensated Sonic	
Correction for Sonde Skew	Applied	
Cycle Stretch Algorithm	Applied	
MN3FT	N/A	micro-sec
MX3FT	N/A	micro-sec
Hunt-Raymer Constant	83.13	micro-sec/ft

Sonde Mode	Full Waveform
Hole Type	Open Hole

Sonde Parameters

	Measured	Calibrated
Offset	0.0000	0.0000
Free Pipe	0.0000	0.0000

Peak Amplitude Source 0

Waveform	Start Time (micro-sec)	Width (micro-sec)	Pre Gain	Start Gain	Discriminator (mV)
3'	N/A	N/A	N/A	N/A	N/A
4'	N/A	N/A	N/A	N/A	N/A
5'	N/A	N/A	N/A	N/A	N/A
6'	N/A	N/A	N/A	N/A	N/A

Processed Fixed Gate Parameters

Waveform Used For Processing	3 foot			
Start Time (micro-sec)	End Time (micro-sec)	Discriminator (mV)	Depth (ft)	
0.00	0.00	0.00	0.00	
0.00	0.00	0.00	0.00	
0.00	0.00	0.00	0.00	
0.00	0.00	0.00	0.00	
0.00	0.00	0.00	0.00	

Full Waveform Parameters

Use 3' Waveform to derive TR	Yes
Use 4' Waveform to derive TR	Yes
Use 5' Waveform to derive TR	Yes
Use 6' Waveform to derive TR	Yes
3' Waveform Discriminator Level	0.30 mV
4' Waveform Discriminator Level	0.30 mV
5' Waveform Discriminator Level	0.15 mV
6' Waveform Discriminator Level	0.15 mV
3' Waveform Filter	None
4' Waveform Filter	None
5' Waveform Filter	None
6' Waveform Filter	None
Semblance Level	0.50
Semblance Window Width	120.00 micro-sec
Sonic 1 Despiker	30.48 micro-sec/ft
Sonic 2 Despiker	30.48 micro-sec/ft

Induction Calibration MAI 287

Base Calibration on 9-FEB-2010,13:46  
Field Check on 19-FEB-2010 21:56

Base Calibration

Test Loop Calibration	Measured		Calibrated (mmho/m)	
	Low	High	Low	High
Channel 1	16.6	472.0	9.3	966.2
2	6.0	384.6	7.6	821.4
3	3.3	258.9	5.2	566.0
4	2.2	137.2	2.6	279.2

Array Temperature 77.0 Deg F

Channel	Base Check (mmho/m)		Field Check (mmho/m)	
	Low	High	Low	High
1	15.0	3831.4	12.3	3832.4
2	31.9	3493.7	29.6	3494.9
3	30.7	3046.7	28.7	3047.8
4	19.7	2010.9	18.4	2011.6
Deep	18.3	1971.3	16.9	1972.0
Medium	45.6	4058.0	43.0	4059.7
Shallow	48.2	5177.1	44.9	5178.9

Array Temperature 44.0 42.0 Deg F

Induction Constants MAI 287

Last Edited on 19-FEB-2010,22:23

Induction Model	VECTAR
Caliper for Borehole Corr.	Density Caliper
Hole Size for Borehole Correction	N/A inches
Tool Centred	No
Stand-off Type	Fins

Stand-off	0.50	inches
Number of Fins on Stand-off	6.0000	
Stand-off Fin Angle	60.00	degrees
Stand-off Fin Width	0.5000	inches
Borehole Corr. Rm Source	Temperature Corr	
Temp. for Rm Corr.	MCG External Temperature	
Squasher Start	0.0020	mhos/metre
Squasher Offset	0.0000	mhos/metre

Borehole Normalisation

DRM1	0.0000	DRC1	0.0000
DRM2	0.0000	DRC2	0.0000
MRM1	0.0000	MRC1	0.0000
MRM2	0.0000	MRC2	0.0000
SRM1	0.0000	SRC1	0.0000
SRM2	0.0000	SRC2	0.0000

Calibration Site Corrections

Channel 1	0.00	mmhos/metre
Channel 2	0.00	mmhos/metre
Channel 3	0.00	mmhos/metre
Channel 4	0.00	mmhos/metre

Apparent Porosity and Water Saturation Constants

Archie Constant (A)	1.00	
Cementation Exponent (M)	2.00	
Saturation Exponent (N)	2.00	
Saturation of Water for Apor	100.00	percent
Resistivity of Water for Apor and Sw	0.05	ohm-m
Resistivity of Mud Filtrate for Sw	0.00	ohm-m

High Resolution Temperature Calibration MAI 287

Field Calibration on 19-FEB-2010,21:56

	Measured	Calibrated(Deg F)
Lower	10.00	10.00
Upper	50.00	50.00

High Resolution Temperature Constants MAI 287

Last Edited on 9-FEB-2010,13:50

Pre-filter Length	11
-------------------	----

Caliper Calibration MPD 220

Base Calibration on 20-JAN-2010 13:56

Field Calibration on 19-FEB-2010,21:52

Base Calibration		Measured	Calibrator Size (in)
Reading No			
1		14272	4.00
2		22416	5.96
3		30368	7.98
4		38432	9.86
5		47536	11.88
6		N/A	N/A

Field Calibration		Measured Caliper (in)	Actual Caliper (in)
		5.97	5.96

Photo Density Calibration MPD 220

Base Calibration on 13-FEB-2010,09:45

Field Check on 19-FEB-2010 21:45

Density Calibration		Measured		Calibrated (sdu)	
Base Calibration		Near	Far	Near	Far
Reference 1	45083	16661	53115	19186	
Reference 2	21601	2751	25020	2536	

Field Check at Base	1285.0	1528.4
Field Check	1290.9	1536.3

PE Calibration

Base Calibration	Measured	Calibrated
------------------	----------	------------

Base Calibration	WS	measured WH	Ratio	Calibrated Ratio
Background	230	1135		
Reference 1	16270	44889	0.367	0.320
Reference 2	6180	21438	0.293	0.272

Field Check at Base  
230.1      1134.6

Field Check  
232.7      1138.6

### Density Constants MPD 220

Last Edited on 19-FEB-2010,21:45

Density Source Id	271	
Nylon Calibrator Number	507	
Aluminium Calibrator Number	507	
Density Shoe Profile	4 inch	
Caliper Source for Processing	Density Caliper	
PE Correction to Density	Not Applied	
Mud Density	1.17	gm/cc
Mud Density Z/A Correction	1.11	
Mud Filtrate Density	1.00	gm/cc
Dry Hole Mud Filtrate Density	1.00	gm/cc
DNCT	0.00	gm/cc
CRCT	0.00	gm/cc
Density Z/A Correction	Standard	
Matrix Density (gm/cc)	Depth (ft)	
2.65	0.00	
0.00	0.00	
0.00	0.00	
0.00	0.00	
0.00	0.00	
0.00	0.00	
0.00	0.00	
0.00	0.00	
0.00	0.00	

## DOWNHOLE EQUIPMENT

C:\DOCUME~1\Hopkinjg\LOCALS~1\Temp\Weatherford PreView\0\depth.dta

Shuttle Running Tool 3.5" (SRT A)  
SRT 1    Length: 0.33 ft    Weight: 37.5 lb

MBS-A.A 400v Compact Battery Sub  
MBS 52    Length: 14.24 ft    Weight: 105.8 lb

Compact Gamma  
MCG 342    Length: 8.70 ft    Weight: 63.9 lb

Compact Memory Sub A.C  
MMS 21    Length: 3.12 ft    Weight: 30.9 lb


SKJ-D.A Compact Knuckle Joint  
SKJ 172    Length: 2.17 ft    Weight: 24.3 lb

SHA-J.A Compact Swivel Head Adaptor  
SHA 214    Length: 2.30 ft    Weight: 22.0 lb

MIS-D.A Compact Inline Bowspring sub  
MIS 315    Length: 5.70 ft    Weight: 33.1 lb

Compact Neutron  
MDN 250    Length: 5.04 ft    Weight: 50.7 lb

Compact Density/Caliper  
MPD 220    Length: 9.59 ft    Weight: 90.4 lb



MIS-D.A Compact Inline Bowspring sub  
 MIS 442 Length: 5.70 ft Weight: 33.1 lb

SHA-J.A Compact Swivel Head Adaptor  
 SHA 316 Length: 2.30 ft Weight: 22.0 lb

SKJ-D.A Compact Knuckle Joint  
 SKJ 154 Length: 2.17 ft Weight: 24.3 lb

MIS-B Compact Inline Standoff sub  
 MIS 277 Length: 2.14 ft Weight: 15.4 lb

Compact Focused Electric  
 MFE 236 Length: 6.03 ft Weight: 48.5 lb


MIS-B Compact Inline Standoff sub  
 MIS 182 Length: 2.14 ft Weight: 15.4 lb

Compact Sonic  
 MSS 221 Length: 12.52 ft Weight: 72.8 lb

MIS-B Compact Inline Standoff sub  
 MIS 365 Length: 2.14 ft Weight: 15.4 lb

Compact Induction  
 MAI 287 Length: 10.81 ft Weight: 48.5 lb

Total Length: 97.12 ft Weight: 754.0 lb



**COMPANY** EXXON MOBIL CORPORATION  
**WELL** FREEDOM RANCH UNIT 197-33B8  
**FIELD** PICEANCE CREEK  
**PROVINCE/COUNTY** RIO BLANCO  
**COUNTRY/STATE** U.S.A. / COLORADO

Elevation Kelly Bushing	6476.00	feet	First Reading	12781.00	feet
Elevation Drill Floor	6475.00	feet	Depth Driller	12830.00	feet
Elevation Ground Level	6446.00	feet	Depth Logger	12796.00	feet



**COMPACT WELL SHUTTLE  
 COMPENSATED SONIC  
 LOG**