



Well Header Setup				
Well Name 596-31A-18		MOC UWI		
Original KB Elevation (ft) 8,442.00	Spud Date 9/11/2008	Rig Release Date		
Qtr/Qtr, Block, Sec, Town, Range NWNE SEC 31 T5S R96W		Latitude (°) 39.576550	Longitude (°) -108.208170	
Wellbore Sections Setup				
Parent Wellbore 596-31A-18	Kick Off Depth (ftKB) 0.0	Vertical Section Direction (°) 190.06		
Section Des	Size (in)	Act Top (ftKB)	Act Btm (ftKB)	
Conductor	22	24.0	120.0	
Surface	16	120.0	2,894.0	
Production 1	8 3/4	2,894.0	9,531.0	
Production 1	7 7/8	9,531.0	9,909.0	
Plug Back Total Depths				
Date	Depth (ftKB)	Method	Com	
	9,867.0			
Zones				
Zone Name	Top (ftKB)	Btm (ftKB)	Com	
Casing Data				
Conductor				
Casing Description Conductor		Run Date 1/5/2008	Set Depth (ftKB) 120.0	
Item Des	OD (in)	ID (in)	Len (ft)	
Casing Joints	20	19.124	96.00	
Surface				
Casing Description Surface		Run Date 9/14/2008	Set Depth (ftKB) 2,834.8	
Item Des	OD (in)	ID (in)	Len (ft)	
Casing Hanger	9 5/8	8.921	9.00	
Casing Joints	9 5/8	8.921	2,665.98	
Air collar	9 5/8	8.921	1.40	
Casing Joints	9 5/8	8.921	43.08	
Float Jt	9 5/8	8.921	44.70	
Float Collar	9 5/8	8.921	1.30	
Shoe Jt	9 5/8	8.921	43.35	
Float Shoe	9 5/8	8.921	2.00	
Structural				
Casing Description Structural		Run Date 10/31/2008	Set Depth (ftKB) 9,853.4	
Item Des	OD (in)	ID (in)	Len (ft)	
Casing Hanger	4 1/2	4.000	6.82	
Pup Jt.	4 1/2	4.000	2.18	
Casing Joints	4 1/2	4.000	6,977.86	
Marker Joint B	4 1/2	4.000	21.19	
Casing Joints	4 1/2	4.000	1,483.09	
Marker Joint A	4 1/2	4.000	22.21	
Casing Joints	4 1/2	4.000	1,229.18	
Float Joint	4 1/2	4.000	21.11	
Float Collar	4 1/2	4.000	0.87	
Casing Joints	4 1/2	4.000	42.38	
Shoe Joint	4 1/2	4.000	21.23	
Float Shoe	4 1/2	4.000	1.24	
Cement Data				
Conductor, 120.0ftKB				
Description Conductor Cement	String Conductor, 120.0ftKB	Wellbore 596-31A-18	Type Casing	
Stg #	Description	Top (ftKB)	Btm (ftKB)	Full Retur... Vol...
	Conductor Cement	24.0	120.0	No

