






Well Name: SG 11-23
 Surface Location: GV 18-23 Pad
 North American Datum 1983 , US State Plane 1983 , Colorado Central Zone
 Ground Elevation: 5134.0
 +N/-S +E/-W Northing Easting Latitude Longitude Slot
 0.0 0.0 1590861.50 2270829.70 39° 25' 38.044 N 108° 4' 54.116 W A9
 KELLY BUSHING @ 5158.0usft (H&P 289 (24' RKB) kjs)



Project: SG 23-07S-096W
 Site: GV 18-23 Pad
 Well: SG 11-23
 Design #1 06Apr11 kjs



Azimuths to True North
 Magnetic North: 10.40°
 Magnetic Field
 Strength: 52276.4snT
 Dip Angle: 65.69°
 Date: 2/4/2011
 Model: IGRF2005-10

ANNOTATIONS

TVD	MD	Inc	Azi	+N/-S	+E/-W	VSec	Departure	Annotation
120.0	120.0	0.00	0.00	0.0	0.0	0.0	0.0	Start Build 3.50
291.1	291.4	6.00	298.00	4.2	-7.9	8.7	9.0	Begin 3.5°/100 Build & Turn
795.7	816.1	24.13	312.03	89.6	-112.7	143.8	144.3	Hold 24.13 Inclination
2438.5	2616.2	24.13	312.03	582.3	-659.2	879.6	880.2	Start Drop -1.50
4000.0	4224.7	0.00	0.00	805.8	-907.1	1213.3	1213.9	Vertical
4100.0	4324.7	0.00	0.00	805.8	-907.1	1213.3	1213.9	Top Gas
5700.0	5924.7	0.00	0.00	805.8	-907.1	1213.3	1213.9	TD at 5924.7

PICEANCE VLY NAD 83

SG 23-07S-096W

GV 18-23 Pad

SG 11-23 - Slot A9

Wellbore #1

Plan: Design #1 06Apr11 kjs

Standard Planning Report - Geographic

26 May, 2011

Williams

Planning Report - Geographic

Database:	Compass R5000 WIN AUTH	Local Co-ordinate Reference:	Well SG 11-23 - Slot A9
Company:	PICEANCE VLY NAD 83	TVD Reference:	KELLY BUSHING @ 5158.0usft (H&P 289 (24' RKB) kjs)
Project:	SG 23-07S-096W	MD Reference:	KELLY BUSHING @ 5158.0usft (H&P 289 (24' RKB) kjs)
Site:	GV 18-23 Pad	North Reference:	True
Well:	SG 11-23	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1 06Apr11 kjs		

Project	SG 23-07S-096W, Garfield County, CO, 23-07S-096W		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	Colorado Central Zone		Using geodetic scale factor

Site	GV 18-23 Pad				
Site Position:		Northing:	1,590,884.00 usft	Latitude:	39° 25' 38.266 N
From:	Map	Easting:	2,270,829.40 usft	Longitude:	108° 4' 54.128 W
Position Uncertainty:	0.0 usft	Slot Radius:	13.200 in	Grid Convergence:	-1.628 °

Well	SG 11-23 - Slot A9					
Well Position	+N/-S	0.0 usft	Northing:	1,590,861.50 usft	Latitude:	39° 25' 38.044 N
	+E/-W	0.0 usft	Easting:	2,270,829.70 usft	Longitude:	108° 4' 54.116 W
Position Uncertainty		0.0 usft	Wellhead Elevation:		Ground Level:	5,134.0 usft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2005-10	2/4/2011	10.404	65.688	52,276

Design	Design #1 06Apr11 kjs			
Audit Notes:				
Version:	Phase:	PLAN	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.0	0.0	0.0	311.62

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.000	
120.0	0.00	0.00	120.0	0.0	0.0	0.00	0.00	0.00	0.000	
291.4	6.00	298.00	291.1	4.2	-7.9	3.50	3.50	0.00	298.000	
816.1	24.13	312.03	795.7	89.6	-112.7	3.50	3.46	2.68	18.342	
2,616.2	24.13	312.03	2,438.5	582.3	-659.2	0.00	0.00	0.00	0.000	
4,224.7	0.00	0.00	4,000.0	805.8	-907.1	1.50	-1.50	0.00	180.000	
5,924.7	0.00	0.00	5,700.0	805.8	-907.1	0.00	0.00	0.00	0.000	

Williams
Planning Report - Geographic

Database:	Compass R5000 WIN AUTH	Local Co-ordinate Reference:	Well SG 11-23 - Slot A9
Company:	PICEANCE VLY NAD 83	TVD Reference:	KELLY BUSHING @ 5158.0usft (H&P 289 (24' RKB) kjs)
Project:	SG 23-07S-096W	MD Reference:	KELLY BUSHING @ 5158.0usft (H&P 289 (24' RKB) kjs)
Site:	GV 18-23 Pad	North Reference:	True
Well:	SG 11-23	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1 06Apr11 kjs		

Planned Survey									
Measured Depth (usft)	Inclination (")	Azimuth (")	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
0.0	0.00	0.00	0.0	0.0	0.0	1,590,861.50	2,270,829.70	39° 25' 38.044 N	108° 4' 54.116 W
120.0	0.00	0.00	120.0	0.0	0.0	1,590,861.50	2,270,829.70	39° 25' 38.044 N	108° 4' 54.116 W
Start Build 3.50									
291.4	6.00	298.00	291.1	4.2	-7.9	1,590,865.93	2,270,821.91	39° 25' 38.085 N	108° 4' 54.217 W
Begin 3.5°/100 Build & Turn									
816.1	24.13	312.03	795.7	89.6	-112.7	1,590,954.27	2,270,719.63	39° 25' 38.929 N	108° 4' 55.552 W
Hold 24.13 Inclination									
864.6	24.13	312.03	840.0	102.9	-127.4	1,590,967.96	2,270,705.28	39° 25' 39.061 N	108° 4' 55.740 W
Top of "G" Sand									
916.0	24.13	312.03	886.9	117.0	-143.0	1,590,982.48	2,270,690.07	39° 25' 39.200 N	108° 4' 55.939 W
9 5/8"									
974.2	24.13	312.03	940.0	132.9	-160.7	1,590,998.89	2,270,672.88	39° 25' 39.357 N	108° 4' 56.164 W
Base of "G" Sand									
2,616.2	24.13	312.03	2,438.5	582.3	-659.2	1,591,462.29	2,270,187.32	39° 25' 43.799 N	108° 5' 2.518 W
Start Drop -1.50									
2,844.9	20.70	312.03	2,650.0	640.7	-724.0	1,591,522.50	2,270,124.23	39° 25' 44.376 N	108° 5' 3.343 W
Mesaverde									
4,224.7	0.00	0.00	4,000.0	805.8	-907.1	1,591,692.70	2,269,945.90	39° 25' 46.007 N	108° 5' 5.677 W
Vertical									
4,324.7	0.00	0.00	4,100.0	805.8	-907.1	1,591,692.70	2,269,945.90	39° 25' 46.007 N	108° 5' 5.677 W
Top Gas - Approx. Top Gas									
5,294.7	0.00	0.00	5,070.0	805.8	-907.1	1,591,692.70	2,269,945.90	39° 25' 46.007 N	108° 5' 5.677 W
Cameo Coals									
5,824.7	0.00	0.00	5,600.0	805.8	-907.1	1,591,692.70	2,269,945.90	39° 25' 46.007 N	108° 5' 5.677 W
Rollins SS									
5,924.7	0.00	0.00	5,700.0	805.8	-907.1	1,591,692.70	2,269,945.90	39° 25' 46.007 N	108° 5' 5.677 W
TD at 5924.7 - TD									

Design Targets									
Target Name	Dip Angle (")	Dip Dir. (")	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
- hit/miss target									
- Shape									
Top Gas (25' Radius) S	0.00	0.00	4,100.0	805.8	-907.1	1,591,692.70	2,269,945.90	39° 25' 46.007 N	108° 5' 5.677 W
- plan hits target center									
- Circle (radius 25.0)									

Casing Points					
Measured Depth (usft)	Vertical Depth (usft)	Name	Casing Diameter (in)	Hole Diameter (in)	
916.0	886.9	9 5/8"	9.625	12.250	

Williams
Planning Report - Geographic

Database:	Compass R5000 WIN AUTH	Local Co-ordinate Reference:	Well SG 11-23 - Slot A8
Company:	PICEANCE VLY NAD 83	TVD Reference:	KELLY BUSHING @ 5158.0usft (H&P 289 (24' RKB) kjs)
Project:	SG 23-07S-096W	MD Reference:	KELLY BUSHING @ 5158.0usft (H&P 289 (24' RKB) kjs)
Site:	GV 18-23 Pad	North Reference:	True
Well:	SG 11-23	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1 06Apr11 kjs		

Formations					
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (")	Dip Direction (")
864.6	840.0	Top of "G" Sand			
974.2	940.0	Base of "G" Sand			
2,844.9	2,650.0	Mesaverde			
4,324.7	4,100.0	Approx. Top Gas			
5,294.7	5,070.0	Cameo Coals			
5,824.7	5,600.0	Rollins SS			
5,924.7	5,700.0	TD			

Plan Annotations				
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
120.0	120.0	0.0	0.0	Start Build 3.50
281.4	291.1	4.2	-7.9	Begin 3.5"/100 Build & Turn
816.1	795.7	89.6	-112.7	Hold 24.13 Inclination
2,616.2	2,438.5	582.3	-659.2	Start Drop -1.50
4,224.7	4,000.0	805.8	-907.1	Vertical
4,324.7	4,100.0	805.8	-907.1	Top Gas
5,924.7	5,700.0	805.8	-907.1	TD at 5924.7