PSI
PRECISION SURVEYS INC.

COMPENSATED DENSITY
HIGH RESOLUTION INDUCTION

Company: Bonanza Creek Energy, Inc.
Field: Wattenberg
Location: Sec 19, T3N, R67W, 6th PM
County: Weld
State/Province: Colorado
Date: 3/4/2011
Time:
Run Number: One
Depth Reference: KB
Elevation: 4,871.00 ft
Permanent Datum: Ground Level
Log Measured From: KB
Above Permanent Datum: 16.00 ft
Drilling Measured From: KB
Casing Record: 8.625" @ 1,000.00 ft
Bit Record: 7.875" @ 7,700.00 ft
Type Fluid in Hole: Water Based Mud
Density: 8.60 lb/gal
Viscosity: 28.00 s/qt
Fluid Loss: 8.00 cc
Source of Sample: Pit
Rm @ Measured Temp: 0.000 @ 0.00 °F
Rmf @ Measured Temp: 0.000 @ 0.00 °F
Rmc @ Measured Temp: 0.000 @ 0.00 °F
Source of Rmf and Rmc: Measured
Rm @ BHT: 0.000 @ 0.00 °F
Time Since Circulation: 0.00 hr
Time on Bottom: 03/04/2011 08:00
Max Recorded Temperature: 0.00 °F
Equipment Number: 1103
Location: Greeley, CO
Recorded By: Mike Zimmerman
Witnessed By: Jeff Hall

Comments

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Annular volume calculated for 4.5" casing
Mid Continent Rig
Thank you for using Phoenix Surveys!
API #: 05-123-32713-0000

Database File: 1103dl.db
Dataset Pathname: pass1
Presentation Format: pdc1
Dataset Creation: Mon Mar 21 14:00:10 2011
Charted by: Depth in Feet scaled 1:240

0 Density Caliper (in) 10
50 Gamma Ray (GAPI) 150
100 SP (mV) 200

ABAM (ft)

0 Deep Resistivity (Ohm-m) 200
2 Medium Resistivity (Ohm-m) 200
2 Shallow Resistivity (Ohm-m) 200
2 Rt (Ohm-m) 200

0 Density Porosity (pu) 45
30 Neutron Porosity (pu) -15

1400
1450
1500
1550
1600
1650
1700
1750
1800
1850
1900
1950
2000
2050
2100
2150
2200
2250
2300
2350
2400
2450
2500
2550
2600
2650
2700
2750
2800
2850
2900
2950
3000
3050
3100
3150
3200
3250
3300
3350
3400
3450
3500
3550
3600
3650
3700
3750
3800
3850
3900
3950
4000
4050
4100
4150
4200
4250
4300
4350
4400
4450
4500
4550
4600
4650

2.71 LB Mahs
2.55 SS Mahs

Database File: 1103dl.db
Dataset Pathname: pass1
Presentation Format: pdc1
Dataset Creation: Mon Mar 21 14:00:10 2011
Charted by: Depth in Feet scaled 1:240

0 Caliper (in) 10
0 Gamma Ray (GAPI) 150
100 SP (mV) 200

0 Deep Resistivity (Ohm-m) 200
2 Medium Resistivity (Ohm-m) 200
2 Shallow Resistivity (Ohm-m) 200
2 Rt (Ohm-m) 200

0 Density Porosity (pu) 45
30 Neutron Porosity (pu) -15

6300
6350
6400
6450
6500
6550
6600
6650
6700
6750
6800
6850

2.71 LB Mahs
Mahs Change @ 6600'
2.55 SS Mahs
2.71 LB Mahs

Caliper
Gamma Ray
SP
Deep Resistivity
Medium Resistivity
Shallow Resistivity
Density Porosity
Neutron Porosity
Rt
Logged to TD 6850'