

HILCORP ENERGY

8-5/8" 24# @ 169'
cmt'd w/ 95sx

Estimated pipe tally:

| | |
|------------------------------|----------------|
| KB-THF | 8 |
| 186 jts 2-3/8" 4.7# J-55 tbg | 5909 |
| 4 1/2" x 2 3/8" TAC | 5911.75 |
| 4 jts 2-3/8" 4.7# J-55 tbg | 6037.75 |
| SN | 6038.55 |
| Perf Sub | 6041.55 |
| 1 jt slotted MA | 6066.55 |

NOTE: Tbg/rod/pump configuration based on last well setting (9/21/2010)

TOC @ 5330' (CBL)

4-1/2" 10.5# K-55 @ 6190'
cmt'd w/ 200sx.

Rod String:

| | |
|----------------------------------|---------------|
| KB-THF | 8 |
| 22' X 1-1/4" polish rod | 18 |
| 1-2' 7/8" pony rods | 20 |
| 1 x 6' & 1 x 8' x 7/8" pony rods | 34 |
| 90 x 7/8" "D" rods | 2284 |
| 149 x 3/4" "D" rods | 6009 |
| 1.4' Hooks on-off tool | 6010.4 |
| 1 x 3/4" "D" rod | 6035.4 |
| 1 x 3/4" X 2' sub | 6037.4 |
| 2" x 1-1/4" x 16' RHAC THD Pump | 6040.4 |

TAC @ 5,911' RKB

4 jts 2-3/8" 4.7# J-55 tbg

SN @ 6,041.7' RKB

MA @ 6,068' RKB (EOT)

'D" Sand perms 6,022'-6,038' @ 4 SPF

'J" Sand perms 6,112'-6,118' @ 4 SPF

PBTD=6,090' (CIBP + Cmt)

TD=6,200'

WELL NAME/NUMBER

Jeri #1

DESCRIPTION

1980' FSL & 663' FWL, Sec. 21 T1S-R58W
Adams Co., CO

KB = 4949'

THF = 4941'

CHF = 4937'

FIELD/LEASE/AREA

Hoffman Creek

PREPARED BY

LED

APPROVED/DATE

9/25/2010

GL = 4936'

Serial Nbr.

API Nbr. 05-001-05467