PSI
PHOENIX SURVEYS INC.

HIGH RESOLUTION INDUCTION
COMPENSATED NEUTRON

Company: Bonanza Creek Energy Operating
Field: Wildcat
Well: North Platte 34-33
County: Weld
State/Province: Colorado
Other Services: Dual Induction, Compensated Neutron, Gamma Ray, Caliper
Sec.: 33 Twp.: 7N Rge.: 63W
API #: 05-123-33990
Permanent Datum: Ground Level
Elevation: 4,914 ft
Log Measured From: Kelly Bushing
4,939 ft above Permanent Datum
Drilling Measured From: Kelly Bushing
Date: 10-Jul-15
Run Number: ONE
Depth Driller: 6,940 ft
Depth Logger: 6,940 ft
Bottom Logged Interval: 6,940 ft
Top Logged Interval: 3,400 ft
Type Fluid in Hole: Water Based Mud
Salinity: 1,000 ppm
Density: 8.4 lb/gal
Viscosity: 28 s/qt
Fluid Loss: 8.4 cc
Source of Sample: Flowline
Rm @ Meas. Temp.: 0.1 @ 70 °F
Rmf @ Meas. Temp.: 0.08 @ 70 °F
Rmc @ Meas. Temp.: 0.12 @ 70 °F
Source of Rmf / Rmc: Measured / Measured
Rm @ BHT: 0.05 @ 160 °F
Time Since Circulation: 4 hrs
Max. Rec. Temp.: 160 °F
Equipment / Location: 5 / Greeley
Recorded By: Jeff Hall
Witnessed By: Jeff Hall

Comments

Annular volume calculated for 4.5" casing
Ensign Rig 7
Thank you for using Phoenix Surveys!
API # 05-123-33990

Database File: 11770.db
Dataset Pathname: open
Presentation Format: ps01
Dataset Creation: Mon Jul 27 08:45:30 2015
Charted by: Depth in Feet scaled 1:240

Density Caliper (in) 16 | Deep Resistivity (Ohm-m) .2000 | Density Porosity (pu) 45
Gamma Ray (GAPI) 150 | Medium Resistivity (Ohm-m) .2000 | Neutron Porosity (pu) -15
SP (mV) 200 | Shallow Resistivity (Ohm-m) .2000 | Neutron Porosity (pu) -15
ABAV (ES) | R6 (Ohm-m) .200

3,400
3,450
3,500
3,550
3,600
3,650
3,700
3,750
3,800
3,850
3,900
3,950
4,000
4,050
4,100
4,150
4,200
4,250
4,300
4,350
4,400
4,450
4,500
4,550
4,600
4,650
4,700
4,750
4,800
4,850
4,900
4,950
5,000
5,050
5,100
5,150
5,200
5,250
5,300
5,350
5,400
5,450
5,500
5,550
5,600
5,650
5,700
5,750
5,800
5,850
5,900
5,950
6,000
6,050
6,100
6,150
6,200
6,250
6,300
6,350
6,400
6,450
6,500
6,550
6,600
6,650
6,700
6,750
6,800
6,850
6,900
6,940

2.50 SS Walks

Density Caliper (in) 16 | Deep Resistivity (Ohm-m) .2000 | Density Porosity (pu) 45
Gamma Ray (GAPI) 150 | Medium Resistivity (Ohm-m) .2000 | Neutron Porosity (pu) -15
SP (mV) 200 | Shallow Resistivity (Ohm-m) .2000 | Neutron Porosity (pu) -15
ABAV (ES) | R6 (Ohm-m) .200

6,000
6,050
6,100
6,150
6,200
6,250
6,300
6,350
6,400
6,450
6,500
6,550
6,600
6,650
6,700
6,750
6,800
6,850
6,900
6,940

2.71 LS Walks

3.47 Walks Change

2.50 SS Walks

Logger's TD 6941'