
Schlumberger
Compensated Neutron Formation Density
Gamma Ray Neutron Density
Company : CHEVRON U.S.A.
Well : CHEVRON ET AL
Field : WILDCAT
County : LOS ANGELES
State : CALIFORNIA
Location : 1 MILE NORTH OF CHEVRON ET AL
Other Services : DIL
Permanent Datum : GROUND LEVEL
Elevation : 0 FT
Log Measured From : KELLY BUSHING
Drilling Measured From : KELLY BUSHING
Elevation : K.B. 0 FT
D.F. 0 FT
G.L. 0 FT
Date : 10-JUL-78
Run Number : ONE
Depth-Driller : 10,000 FT
Depth-Logger : 10,000 FT
Bottom Logged Interval : 10,000 FT
Top Logged Interval : 1,000 FT
Casing-Driller : 13.375 IN @ 1,000 FT
Casing-Logger : 13.375 IN @ 1,000 FT
Bit Size : 12.25 IN
Type Fluid in Hole : LIGNOSULFONATE
Density : 10.0 LB/G
Viscosity : 40 S
PH : 10.5
Fluid Loss : 6.0 C3
Source of Sample : FLOWLINE
Rm @ Meas. Temp : 0.75 @ 80 DF
Rmf @ Meas. Temp : 0.60 @ 80 DF
Rmc @ Meas. Temp : 1.00 @ 80 DF
Source of Rmf : MEASURED
Source of Rmc : MEASURED
Rm @ BHT : 0.40 @ 200 DF
Time Since Circulation : 24 HRS
Max. Rec. Temp. : 200 DF
Equipment Number : 3207
Location : 1 MILE NORTH OF CHEVRON ET AL
Recorded By : R. SMITH
Witnessed By : J. JONES
LOS ANGELES TO SCENIC DR
ACROSS CITY LIMITS
LOS ANGELES
LOS ANGELES COUNTY, CALIFORNIA
Gamma Ray (API)
Caliper (IN)
Neutron Porosity (PU)
Density (G/C3)
Resistivity (OHMM)
Delta Rho (G/C3)
Photoelectric Factor (B/E)
Neutron Porosity (PU)
Density (G/C3)
Caliper (IN)
Gamma Ray (API



Drilling Fluid Type	Water Based Mud
Density (ppg)	9.2
Funnel Visc (s)	40
MBT	2.5
PH	9.5
Mud Salinity	1000 mg/l
Fluid Loss	4.8
Solids	3.5%
Sand	0.5%

Drilling Fluid Type	Water Based Mud
Density (ppg)	9.2
Funnel Visc (s)	40
MBT	2.5
PH	9.5
Mud Salinity	1000 mg/l
Fluid Loss	4.8
Solids	3.5%
Sand	0.5%