
Schlumberger
Gamma Ray (GAPI)
Caliper (IN)
Bit Size (IN)
Deep Resistivity (OHMM)
Medium Resistivity (OHMM)
Shallow Resistivity (OHMM)
Neutron Porosity (DEC)
Density (G/C3)
Photoelectric Factor (B/E)
Delta Rho (G/C3)
Gamma Ray (GAPI)
Caliper (IN)
Bit Size (IN)
Deep Resistivity (OHMM)
Medium Resistivity (OHMM)
Shallow Resistivity (OHMM)
Neutron Porosity (DEC)
Density (G/C3)
Photoelectric Factor (B/E)
Delta Rho (G/C3)
MAIN PASS
MAIN PASS
MAIN PASS



RMWS

REPEAT PASS

Client: Rig_BARRETT CONTRACTOR
Drilled Interval: 1700'-2000'
Logged Interval: 1700'-2000'
Casing Size: 13 3/8" OH 12.25 BIT to 1748 TD CASING TEST
Comments: 1700' TO 2000' REPEAT PASS



RMWS

FREE PIPE PASS

Client: Rig_BARRETT CONTRACTOR
Drilled Interval: 1700'-2000'
Logged Interval: 1700'-2000'
Casing Size: 13 3/8" OH 12.25 BIT to 1748 TD CASING TEST
Comments: 1700' TO 2000' FREE PIPE PASS



RMWS

TEMP PASS

Client: Rig_BARRETT CONTRACTOR
Drilled Interval: 1700'-2000'
Logged Interval: 1700'-2000'
Casing Size: 13 3/8" OH 12.25 BIT to 1748 TD CASING TEST
Comments: 1700' TO 2000' TEMP PASS



Section	Offset (ft)	Schematic	Description	Len (ft)	ID (in)	OD (in)
			TOOL END ASSEMBLY, 1.69 OD TOOL	1.54	1.69	3.00
			3D CALIPER ARM 1 (1.69 OD TOOL) 3D CALIPER ARM 2	1.58	1.69	10.00
TOOL	28.91		3D CALIPER ARM 3 (1.69 OD TOOL)	1.61	0.13	10.00
			SPACER (1.69 OD TOOL)	0.42	0.38	10.00
28.91 (ft)	11.74		IMAGE SENSOR (1.69 OD TOOL)	0.47	0.13	10.00
40.65 (ft)	11.74					
52.39 (ft)	11.74					
64.13 (ft)	11.74					
75.87 (ft)	11.74					
87.61 (ft)	11.74					
99.35 (ft)	11.74					
111.09 (ft)	11.74		SPACER (1.69 OD TOOL)	0.42	0.38	10.00
			TOOL END ASSEMBLY (1.69 OD TOOL)	1.69	1.69	3.00
TOT	4.38		3D CALIPER ARM 1 (1.69 OD TOOL)	1.58	1.69	10.00
Sensor	4.38		3D CALIPER ARM 2 (1.69 OD TOOL)	1.61	1.69	10.00
Sensor	4.38		3D CALIPER ARM 3 (1.69 OD TOOL)	0.13	1.69	10.00
TOOL	0.00					

Tension Offset (ft) Schematic

Company:	Rig_BARRETT CONTRACTOR
Well:	13 3/8" OH 12.25 BIT to 1748 TD
Field:	1700'-2000'
County:	1700'-2000'
State:	
Country:	

RMWS