THIS PLAN AND INFORMATION CONTAINED HEREIN IS RECOMMENDED BASED ON INFORMATION AND DATA GIVEN TO US AT THE TIME OF PREPARATION. THE ACCURACY OF ANY RECOMMENDATION IS DEPENDENT UPON THE ACCURACY AND DETAIL OF THE INFORMATION AND DATA SUPPLIED TO US. THE RECOMMENDATIONS ARE OFFERED IN GOOD FAITH AND BELIEVED TO BE CORRECT BUT WE DO NOT GUARANTEE THE RESULTS OBTAINED. PLEASE REMEMBER THAT THE SAFETY OF PERSONNEL AND EQUIPMENT IS DEPENDENT ON PROPER WELL CONTROL PRACTICES AND THE JUDGEMENT OF THE PERSONNEL AT THE WELL SITE. WE ASSUME NO LIABILITY FOR DAMAGES INCURRED DIRECTLY OR INDIRECTLY AS A RESULT OF OPERATIONS CONDUCTED ON THE BASIS OF RECOMMENDATIONS MADE BY OUR PERSONNEL.

CONFIDENTIAL

Annular volume calculated for a 4.52" casing
Ensign Drilling Rig 122
Total Depth (TVD) = 10,000' (Surface)
+/- 4,391 (22-1/4 Hole) bit
No Ragged Due to Hole Conditions.

Database File: 1122-B
Client: EOG
Field: Eagle Ford
Structure / Slot: Plan #1 rev 1 / R & S 99H & 76H
Created / Last Revised: 10-Jul-2015 / Plan #1 rev 1 (10-Jul-2015)

Gravity Calibrated: No
Declination (+E/W): 6.000
Dip Angle: 60.000°
Magnetic Field: 48,000nT

Grid Meridian: 97.500°
Grid Convention: Add 6.000° to Grid North to obtain Magnetic Direction
Shallow Reference: 0.00 ft rel. MSL
Rig Datum: 2,000.00 ft above MSL

Gravity Calibrated: No
Declination (+E/W): 6.000
Dip Angle: 60.000°
Magnetic Field: 48,000nT

Grid Meridian: 97.500°
Grid Convention: Add 6.000° to Grid North to obtain Magnetic Direction
Shallow Reference: 0.00 ft rel. MSL
Rig Datum: 2,000.00 ft above MSL

Database File: 1122-B
Client: EOG
Field: Eagle Ford
Structure / Slot: Plan #1 rev 1 / R & S 99H & 76H
Created / Last Revised: 10-Jul-2015 / Plan #1 rev 1 (10-Jul-2015)

Gravity Calibrated: No
Declination (+E/W): 6.000
Dip Angle: 60.000°
Magnetic Field: 48,000nT

Grid Meridian: 97.500°
Grid Convention: Add 6.000° to Grid North to obtain Magnetic Direction
Shallow Reference: 0.00 ft rel. MSL
Rig Datum: 2,000.00 ft above MSL

Gravity Calibrated: No
Declination (+E/W): 6.000
Dip Angle: 60.000°
Magnetic Field: 48,000nT

Grid Meridian: 97.500°
Grid Convention: Add 6.000° to Grid North to obtain Magnetic Direction
Shallow Reference: 0.00 ft rel. MSL
Rig Datum: 2,000.00 ft above MSL