

WELLBORE DIAGRAM
PROPOSED P&A WELLBORE DIAGRAM

712' FSL & 605' FWL

Operator:	Koch Exploration Company
Well Name:	WRD Fed M-17-2-96N
Lease Number:	C-0127535
Location:	SWSW Sec. 17-T2N-R96W
Field:	White River Dome
County, State:	Rio Blanco, CO
API Number:	05-103-09511
Diagram Date:	10/18/2011

KB 6184'

GL 6173'

Well History

Spud Date:	9/3/1991
Date TD Reached:	9/23/1991
Completion Date:	12/6/1991
Recomplete:	8/14/2001

8-5/8" 24# csg set @ 718'
 cmd w/ 521 sx 75/25 Poz

Spot cement across surf csg shoe from 668-768'

Run scraper
 Run CIT from 6520' to surface
 Based on CIT, spot cement over defected casing, minimum 50' above an

2nd Stage cmd w/
 330 sx Thixotropic to 3160'

DV Tool @ 4786'

315sx Thixotropic to 6370'

Cement Existing perfs; resulting TOC @ 6400'

6452-7382'

Cement Retainer @ 7405'

7415-7442' (cement squeezed)

5-1/2" 20# csg set @ 7563'

PBTD 7405'

TD 7570'

