



## **EOG Resources**

**Weld Co., CO**

**Sec 26-T12N-R63W**

**Fox Creek #03-26H**

**STK #1**

**Survey: Survey #1**

## **Standard Survey Report**

**26 June, 2011**



<b>Company:</b>	EOG Resources	<b>Local Co-ordinate Reference:</b>	Well Fox Creek #03-26H
<b>Project:</b>	Weld Co., CO	<b>TVD Reference:</b>	Fox Creek 3-26H KBE @ 5439.0ft (SST 56)
<b>Site:</b>	Sec 26-T12N-R63W	<b>MD Reference:</b>	Fox Creek 3-26H KBE @ 5439.0ft (SST 56)
<b>Well:</b>	Fox Creek #03-26H	<b>North Reference:</b>	True
<b>Wellbore:</b>	STK #1	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	STK #1	<b>Database:</b>	Local

<b>Project</b>	Weld Co., CO		
<b>Map System:</b>	US State Plane 1927 (Exact solution)	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	NAD 1927 (NADCON CONUS)		
<b>Map Zone:</b>	Colorado North 501		

<b>Site</b>	Sec 26-T12N-R63W		
<b>Site Position:</b>		<b>Northing:</b>	
<b>From:</b>	Lat/Long	<b>Easting:</b>	
<b>Position Uncertainty:</b>	0.0 ft	<b>Slot Radius:</b>	
		<b>Latitude:</b>	
		<b>Longitude:</b>	
		<b>Grid Convergence:</b>	1.00

<b>Well</b>	Fox Creek #03-26H		
<b>Well Position</b>	+N/-S	0.0 ft	<b>Northing:</b> 599,967.81 ft
	+E/-W	0.0 ft	<b>Easting:</b> 2,305,940.49 ft
<b>Position Uncertainty</b>	0.0 ft	<b>Wellhead Elevation:</b>	ft
		<b>Latitude:</b>	40° 58' 30.190 N
		<b>Longitude:</b>	104° 23' 31.610 W
		<b>Ground Level:</b>	5,418.0 ft

<b>Wellbore</b>	STK #1		
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination</b>
			(°)
	IGRF2010-14	06/20/11	8.71
			<b>Dip Angle</b>
			(°)
			67.57
			<b>Field Strength</b>
			(nT)
			53,462

<b>Design</b>	STK #1		
<b>Audit Notes:</b>			
<b>Version:</b>	1.0	<b>Phase:</b>	ACTUAL
		<b>Tie On Depth:</b>	7,863.0
<b>Vertical Section:</b>	<b>Depth From (TVD)</b>	<b>+N/-S</b>	<b>+E/-W</b>
	(ft)	(ft)	(ft)
	0.0	0.0	0.0
			<b>Direction</b>
			(°)
			321.77

<b>Survey Program</b>	<b>Date</b>	06/26/11		
<b>From</b>	<b>To</b>	<b>Survey (Wellbore)</b>	<b>Tool Name</b>	<b>Description</b>
(ft)	(ft)			
1,584.0	7,863.0	Survey #1 (Hz)	MWD	
7,893.0	12,092.0	Survey #1 (STK #1)	MWD	

<b>Survey</b>											
<b>Measured</b>	<b>Inclination</b>	<b>Azimuth</b>	<b>Vertical</b>	<b>Subsea</b>	<b>+N/-S</b>	<b>+E/-W</b>	<b>Vertical</b>	<b>Dogleg</b>	<b>Build</b>	<b>Turn</b>	
<b>Depth</b>	<b>(°)</b>	<b>(°)</b>	<b>Depth</b>	<b>Depth</b>	<b>(ft)</b>	<b>(ft)</b>	<b>Section</b>	<b>Rate</b>	<b>Rate</b>	<b>Rate</b>	
<b>(ft)</b>			<b>(ft)</b>	<b>(ft)</b>			<b>(ft)</b>	<b>(°/100ft)</b>	<b>(°/100ft)</b>	<b>(°/100ft)</b>	
7,863.0	85.90	320.90	7,445.2	2,006.2	527.5	-373.7	645.6	0.00	0.00	0.00	
7,893.0	84.40	319.90	7,447.7	2,008.7	550.5	-392.8	675.5	6.00	-5.00	-3.33	
7,925.0	83.60	318.10	7,451.1	2,012.1	574.5	-413.6	707.3	6.13	-2.50	-5.63	
7,956.0	83.50	317.80	7,454.6	2,015.6	597.4	-434.3	738.0	1.01	-0.32	-0.97	
7,988.0	82.10	318.10	7,458.6	2,019.6	621.0	-455.5	769.7	4.47	-4.38	0.94	
8,019.0	81.60	318.20	7,463.0	2,024.0	643.9	-476.0	800.3	1.64	-1.61	0.32	
8,051.0	81.20	317.90	7,467.7	2,028.7	667.4	-497.2	831.9	1.56	-1.25	-0.94	
8,083.0	80.60	318.10	7,472.8	2,033.8	690.9	-518.3	863.4	1.97	-1.88	0.63	
8,114.0	81.50	318.10	7,477.6	2,038.6	713.7	-538.8	894.0	2.90	2.90	0.00	

<b>Company:</b>	EOG Resources	<b>Local Co-ordinate Reference:</b>	Well Fox Creek #03-26H
<b>Project:</b>	Weld Co., CO	<b>TVD Reference:</b>	Fox Creek 3-26H KBE @ 5439.0ft (SST 56)
<b>Site:</b>	Sec 26-T12N-R63W	<b>MD Reference:</b>	Fox Creek 3-26H KBE @ 5439.0ft (SST 56)
<b>Well:</b>	Fox Creek #03-26H	<b>North Reference:</b>	True
<b>Wellbore:</b>	STK #1	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	STK #1	<b>Database:</b>	Local

Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	Subsea Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
8,146.0	82.60	318.20	7,482.1	2,043.1	737.3	-559.9	925.6	3.45	3.44	0.31
8,178.0	83.00	318.70	7,486.1	2,047.1	761.0	-581.0	957.3	1.99	1.25	1.56
8,210.0	82.70	318.90	7,490.0	2,051.0	784.9	-601.9	989.0	1.12	-0.94	0.63
8,241.0	82.30	318.80	7,494.1	2,055.1	808.1	-622.1	1,019.7	1.33	-1.29	-0.32
8,272.0	82.00	318.80	7,498.3	2,059.3	831.2	-642.3	1,050.4	0.97	-0.97	0.00
8,304.0	81.70	318.80	7,502.9	2,063.9	855.0	-663.2	1,082.0	0.94	-0.94	0.00
8,335.0	82.50	319.20	7,507.1	2,068.1	878.2	-683.3	1,112.7	2.88	2.58	1.29
8,367.0	82.50	319.60	7,511.3	2,072.3	902.3	-704.0	1,144.4	1.24	0.00	1.25
8,398.0	82.30	319.70	7,515.4	2,076.4	925.7	-723.9	1,175.1	0.72	-0.65	0.32
8,430.0	81.80	319.40	7,519.8	2,080.8	949.8	-744.4	1,206.8	1.82	-1.56	-0.94
8,462.0	82.40	320.10	7,524.2	2,085.2	974.0	-764.9	1,238.4	2.87	1.88	2.19
8,494.0	82.10	320.10	7,528.5	2,089.5	998.3	-785.3	1,270.1	0.94	-0.94	0.00
8,525.0	82.60	320.90	7,532.7	2,093.7	1,022.0	-804.8	1,300.9	3.02	1.61	2.58
8,557.0	82.50	321.30	7,536.8	2,097.8	1,046.7	-824.7	1,332.6	1.28	-0.31	1.25
8,589.0	83.70	321.50	7,540.7	2,101.7	1,071.5	-844.5	1,364.3	3.80	3.75	0.63
8,620.0	83.90	321.80	7,544.0	2,105.0	1,095.7	-863.7	1,395.2	1.16	0.65	0.97
8,652.0	83.90	321.70	7,547.4	2,108.4	1,120.7	-883.4	1,427.0	0.31	0.00	-0.31
8,683.0	83.50	321.30	7,550.8	2,111.8	1,144.8	-902.5	1,457.8	1.82	-1.29	-1.29
8,715.0	83.10	321.30	7,554.5	2,115.5	1,169.6	-922.4	1,489.6	1.25	-1.25	0.00
8,747.0	84.40	321.50	7,558.0	2,119.0	1,194.5	-942.3	1,521.4	4.11	4.06	0.63
8,778.0	84.40	321.80	7,561.1	2,122.1	1,218.7	-961.4	1,552.2	0.96	0.00	0.97
8,809.0	83.80	321.50	7,564.2	2,125.2	1,242.9	-980.5	1,583.1	2.16	-1.94	-0.97
8,841.0	84.80	321.90	7,567.4	2,128.4	1,267.8	-1,000.3	1,614.9	3.36	3.13	1.25
8,873.0	85.60	322.20	7,570.1	2,131.1	1,293.0	-1,019.9	1,646.8	2.67	2.50	0.94
8,905.0	85.90	322.80	7,572.5	2,133.5	1,318.3	-1,039.3	1,678.7	2.09	0.94	1.88
8,936.0	87.00	323.20	7,574.4	2,135.4	1,343.0	-1,057.9	1,709.6	3.77	3.55	1.29
8,968.0	88.70	324.10	7,575.6	2,136.6	1,368.8	-1,076.9	1,741.6	6.01	5.31	2.81
9,000.0	90.20	324.40	7,575.9	2,136.9	1,394.7	-1,095.6	1,773.6	4.78	4.69	0.94
9,032.0	89.80	324.20	7,575.9	2,136.9	1,420.7	-1,114.2	1,805.5	1.40	-1.25	-0.63
9,064.0	89.80	324.10	7,576.0	2,137.0	1,446.7	-1,133.0	1,837.5	0.31	0.00	-0.31
9,095.0	89.90	324.10	7,576.1	2,137.1	1,471.8	-1,151.2	1,868.5	0.32	0.32	0.00
9,127.0	89.50	323.40	7,576.3	2,137.3	1,497.6	-1,170.1	1,900.5	2.52	-1.25	-2.19
9,159.0	89.20	322.40	7,576.6	2,137.6	1,523.1	-1,189.4	1,932.5	3.26	-0.94	-3.13
9,191.0	88.80	321.90	7,577.2	2,138.2	1,548.4	-1,209.0	1,964.5	2.00	-1.25	-1.56
9,223.0	89.40	322.90	7,577.7	2,138.7	1,573.7	-1,228.5	1,996.4	3.64	1.88	3.13
9,254.0	89.50	323.20	7,578.0	2,139.0	1,598.5	-1,247.2	2,027.4	1.02	0.32	0.97
9,286.0	89.90	324.60	7,578.1	2,139.1	1,624.3	-1,266.0	2,059.4	4.55	1.25	4.38
9,317.0	89.80	324.40	7,578.2	2,139.2	1,649.6	-1,284.0	2,090.4	0.72	-0.32	-0.65
9,349.0	89.40	323.60	7,578.4	2,139.4	1,675.5	-1,302.8	2,122.4	2.80	-1.25	-2.50
9,380.0	89.90	324.90	7,578.6	2,139.6	1,700.6	-1,320.9	2,153.3	4.49	1.61	4.19
9,412.0	90.20	324.90	7,578.6	2,139.6	1,726.8	-1,339.3	2,185.3	0.94	0.94	0.00
9,443.0	90.20	324.60	7,578.5	2,139.5	1,752.1	-1,357.2	2,216.2	0.97	0.00	-0.97

<b>Company:</b>	EOG Resources	<b>Local Co-ordinate Reference:</b>	Well Fox Creek #03-26H
<b>Project:</b>	Weld Co., CO	<b>TVD Reference:</b>	Fox Creek 3-26H KBE @ 5439.0ft (SST 56)
<b>Site:</b>	Sec 26-T12N-R63W	<b>MD Reference:</b>	Fox Creek 3-26H KBE @ 5439.0ft (SST 56)
<b>Well:</b>	Fox Creek #03-26H	<b>North Reference:</b>	True
<b>Wellbore:</b>	STK #1	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	STK #1	<b>Database:</b>	Local

Survey

Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	Subsea Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
9,475.0	90.20	325.00	7,578.4	2,139.4	1,778.3	-1,375.7	2,248.2	1.25	0.00	1.25
9,507.0	89.70	326.70	7,578.4	2,139.4	1,804.7	-1,393.6	2,280.1	5.54	-1.56	5.31
9,539.0	89.50	327.10	7,578.6	2,139.6	1,831.6	-1,411.1	2,312.0	1.40	-0.63	1.25
9,570.0	89.20	326.60	7,579.0	2,140.0	1,857.5	-1,428.1	2,342.9	1.88	-0.97	-1.61
9,602.0	88.80	326.10	7,579.6	2,140.6	1,884.1	-1,445.8	2,374.7	2.00	-1.25	-1.56
9,633.0	88.70	326.10	7,580.2	2,141.2	1,909.9	-1,463.1	2,405.6	0.32	-0.32	0.00
9,664.0	89.10	327.00	7,580.8	2,141.8	1,935.7	-1,480.2	2,436.5	3.18	1.29	2.90
9,696.0	89.10	327.20	7,581.3	2,142.3	1,962.6	-1,497.5	2,468.4	0.62	0.00	0.63
9,727.0	88.90	327.10	7,581.9	2,142.9	1,988.6	-1,514.4	2,499.3	0.72	-0.65	-0.32
9,759.0	88.50	326.60	7,582.6	2,143.6	2,015.4	-1,531.9	2,531.1	2.00	-1.25	-1.56
9,791.0	88.80	327.00	7,583.3	2,144.3	2,042.2	-1,549.4	2,563.0	1.56	0.94	1.25
9,828.0	88.70	327.20	7,584.2	2,145.2	2,073.2	-1,569.5	2,599.8	0.60	-0.27	0.54
9,854.0	90.30	327.70	7,584.4	2,145.4	2,095.2	-1,583.5	2,625.7	6.45	6.15	1.92
9,882.0	91.00	328.40	7,584.1	2,145.1	2,118.9	-1,598.3	2,653.5	3.54	2.50	2.50
9,917.0	91.10	328.70	7,583.4	2,144.4	2,148.8	-1,616.5	2,688.3	0.90	0.29	0.86
9,949.0	90.80	328.30	7,582.9	2,143.9	2,176.0	-1,633.2	2,720.0	1.56	-0.94	-1.25
9,981.0	90.70	327.90	7,582.5	2,143.5	2,203.2	-1,650.2	2,751.8	1.29	-0.31	-1.25
10,012.0	90.30	327.30	7,582.2	2,143.2	2,229.4	-1,666.8	2,782.7	2.33	-1.29	-1.94
10,044.0	90.30	327.10	7,582.0	2,143.0	2,256.3	-1,684.1	2,814.5	0.62	0.00	-0.63
10,076.0	91.00	327.30	7,581.7	2,142.7	2,283.2	-1,701.4	2,846.4	2.28	2.19	0.63
10,107.0	90.70	327.00	7,581.2	2,142.2	2,309.2	-1,718.2	2,877.3	1.37	-0.97	-0.97
10,139.0	90.60	326.70	7,580.8	2,141.8	2,336.0	-1,735.7	2,909.1	0.99	-0.31	-0.94
10,170.0	90.60	326.40	7,580.5	2,141.5	2,361.9	-1,752.8	2,940.0	0.97	0.00	-0.97
10,201.0	90.90	327.40	7,580.1	2,141.1	2,387.8	-1,769.8	2,970.9	3.37	0.97	3.23
10,233.0	90.70	326.70	7,579.7	2,140.7	2,414.7	-1,787.2	3,002.7	2.27	-0.63	-2.19
10,265.0	90.10	326.30	7,579.4	2,140.4	2,441.4	-1,804.8	3,034.6	2.25	-1.88	-1.25
10,296.0	89.70	326.90	7,579.5	2,140.5	2,467.2	-1,821.9	3,065.5	2.33	-1.29	1.94
10,328.0	89.90	327.30	7,579.6	2,140.6	2,494.1	-1,839.3	3,097.4	1.40	0.63	1.25
10,360.0	89.70	326.80	7,579.7	2,140.7	2,521.0	-1,856.7	3,129.3	1.68	-0.63	-1.56
10,392.0	87.70	326.70	7,580.5	2,141.5	2,547.7	-1,874.2	3,161.1	6.26	-6.25	-0.31
10,423.0	87.40	326.40	7,581.8	2,142.8	2,573.6	-1,891.3	3,192.0	1.37	-0.97	-0.97
10,455.0	88.40	326.10	7,582.9	2,144.0	2,600.2	-1,909.1	3,223.9	3.26	3.13	-0.94
10,486.0	89.70	326.40	7,583.5	2,144.5	2,625.9	-1,926.3	3,254.8	4.30	4.19	0.97
10,518.0	90.10	326.20	7,583.5	2,144.5	2,652.5	-1,944.0	3,286.7	1.40	1.25	-0.63
10,550.0	89.70	325.70	7,583.6	2,144.6	2,679.1	-1,961.9	3,318.6	2.00	-1.25	-1.56
10,581.0	89.40	325.80	7,583.8	2,144.8	2,704.7	-1,979.4	3,349.5	1.02	-0.97	0.32
10,613.0	89.60	326.30	7,584.1	2,145.1	2,731.2	-1,997.3	3,381.4	1.68	0.63	1.56
10,645.0	89.40	326.50	7,584.4	2,145.4	2,757.9	-2,015.0	3,413.3	0.88	-0.63	0.63
10,677.0	90.20	327.80	7,584.5	2,145.5	2,784.8	-2,032.3	3,445.2	4.77	2.50	4.06
10,709.0	91.10	329.40	7,584.1	2,145.1	2,812.1	-2,049.0	3,476.9	5.74	2.81	5.00
10,740.0	91.20	329.00	7,583.5	2,144.5	2,838.7	-2,064.9	3,507.7	1.33	0.32	-1.29
10,772.0	91.10	328.40	7,582.9	2,143.9	2,866.0	-2,081.5	3,539.4	1.90	-0.31	-1.88
10,804.0	90.90	327.70	7,582.3	2,143.3	2,893.2	-2,098.4	3,571.2	2.27	-0.63	-2.19



<b>Company:</b>	EOG Resources	<b>Local Co-ordinate Reference:</b>	Well Fox Creek #03-26H
<b>Project:</b>	Weld Co., CO	<b>TVD Reference:</b>	Fox Creek 3-26H KBE @ 5439.0ft (SST 56)
<b>Site:</b>	Sec 26-T12N-R63W	<b>MD Reference:</b>	Fox Creek 3-26H KBE @ 5439.0ft (SST 56)
<b>Well:</b>	Fox Creek #03-26H	<b>North Reference:</b>	True
<b>Wellbore:</b>	STK #1	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	STK #1	<b>Database:</b>	Local

Survey											
Measured Depth (ft)	Inclination (°)	Azimuth (°)	Vertical Depth (ft)	Subsea Depth (ft)	+N/-S (ft)	+E/-W (ft)	Vertical Section (ft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	
10,836.0	90.60	327.50	7,581.9	2,142.9	2,920.2	-2,115.6	3,603.1	1.13	-0.94	-0.63	
10,868.0	90.50	327.90	7,581.6	2,142.6	2,947.2	-2,132.7	3,634.9	1.29	-0.31	1.25	
10,899.0	90.70	327.80	7,581.3	2,142.3	2,973.5	-2,149.2	3,665.7	0.72	0.65	-0.32	
10,930.0	90.60	327.20	7,580.9	2,141.9	2,999.6	-2,165.8	3,696.6	1.96	-0.32	-1.94	
10,962.0	90.10	326.80	7,580.7	2,141.7	3,026.5	-2,183.2	3,728.4	2.00	-1.56	-1.25	
10,994.0	89.70	326.40	7,580.8	2,141.8	3,053.2	-2,200.9	3,760.3	1.77	-1.25	-1.25	
11,026.0	89.60	326.20	7,581.0	2,142.0	3,079.8	-2,218.6	3,792.2	0.70	-0.31	-0.63	
11,057.0	90.10	325.60	7,581.0	2,142.0	3,105.5	-2,236.0	3,823.1	2.52	1.61	-1.94	
11,089.0	89.90	325.60	7,581.0	2,142.0	3,131.9	-2,254.1	3,855.1	0.63	-0.63	0.00	
11,120.0	89.80	325.60	7,581.1	2,142.1	3,157.5	-2,271.6	3,886.0	0.32	-0.32	0.00	
11,152.0	90.70	325.00	7,581.0	2,142.0	3,183.8	-2,289.8	3,917.9	3.38	2.81	-1.88	
11,183.0	90.80	325.00	7,580.6	2,141.6	3,209.2	-2,307.6	3,948.9	0.32	0.32	0.00	
11,215.0	90.40	324.40	7,580.2	2,141.2	3,235.3	-2,326.1	3,980.8	2.25	-1.25	-1.88	
11,247.0	90.20	323.50	7,580.1	2,141.1	3,261.1	-2,344.9	4,012.8	2.88	-0.63	-2.81	
11,278.0	90.00	323.90	7,580.0	2,141.0	3,286.1	-2,363.3	4,043.8	1.44	-0.65	1.29	
11,310.0	89.80	323.60	7,580.1	2,141.1	3,311.9	-2,382.2	4,075.8	1.13	-0.63	-0.94	
11,342.0	89.20	322.90	7,580.4	2,141.4	3,337.6	-2,401.3	4,107.8	2.88	-1.88	-2.19	
11,374.0	90.10	323.10	7,580.5	2,141.5	3,363.1	-2,420.6	4,139.8	2.88	2.81	0.63	
11,406.0	89.70	322.80	7,580.6	2,141.6	3,388.7	-2,439.9	4,171.7	1.56	-1.25	-0.94	
11,437.0	90.00	321.40	7,580.7	2,141.7	3,413.1	-2,458.9	4,202.7	4.62	0.97	-4.52	
11,469.0	89.50	320.80	7,580.8	2,141.8	3,438.0	-2,479.0	4,234.7	2.44	-1.56	-1.88	
11,500.0	90.50	320.90	7,580.8	2,141.8	3,462.1	-2,498.6	4,265.7	3.24	3.23	0.32	
11,532.0	90.40	320.20	7,580.6	2,141.6	3,486.8	-2,518.9	4,297.7	2.21	-0.31	-2.19	
11,564.0	90.80	320.90	7,580.2	2,141.2	3,511.5	-2,539.2	4,329.7	2.52	1.25	2.19	
11,595.0	91.30	320.90	7,579.7	2,140.7	3,535.5	-2,558.8	4,360.7	1.61	1.61	0.00	
11,627.0	91.30	320.90	7,578.9	2,139.9	3,560.4	-2,579.0	4,392.7	0.00	0.00	0.00	
11,659.0	91.20	320.40	7,578.2	2,139.2	3,585.1	-2,599.2	4,424.7	1.59	-0.31	-1.56	
11,691.0	91.30	320.00	7,577.5	2,138.5	3,609.7	-2,619.7	4,456.7	1.29	0.31	-1.25	
11,722.0	91.10	319.90	7,576.9	2,137.9	3,633.4	-2,639.7	4,487.6	0.72	-0.65	-0.32	
11,754.0	91.00	320.00	7,576.3	2,137.3	3,657.9	-2,660.2	4,519.6	0.44	-0.31	0.31	
11,786.0	90.80	319.80	7,575.8	2,136.8	3,682.4	-2,680.9	4,551.6	0.88	-0.63	-0.63	
11,817.0	90.70	319.90	7,575.4	2,136.4	3,706.1	-2,700.8	4,582.6	0.46	-0.32	0.32	
11,849.0	90.50	319.30	7,575.1	2,136.1	3,730.4	-2,721.6	4,614.6	1.98	-0.63	-1.88	
11,880.0	89.80	317.90	7,575.0	2,136.0	3,753.7	-2,742.1	4,645.5	5.05	-2.26	-4.52	
11,912.0	89.40	316.70	7,575.2	2,136.2	3,777.2	-2,763.8	4,677.4	3.95	-1.25	-3.75	
11,943.0	89.40	316.60	7,575.5	2,136.5	3,799.7	-2,785.1	4,708.3	0.32	0.00	-0.32	
11,975.0	89.40	316.70	7,575.9	2,136.9	3,823.0	-2,807.0	4,740.2	0.31	0.00	0.31	
12,007.0	88.90	316.20	7,576.3	2,137.3	3,846.2	-2,829.1	4,772.0	2.21	-1.56	-1.56	
12,039.0	88.80	316.40	7,577.0	2,138.0	3,869.3	-2,851.2	4,803.9	0.70	-0.31	0.63	
Projection to Bit											
12,092.0	88.80	316.40	7,578.1	2,139.1	3,907.7	-2,887.7	4,856.6	0.00	0.00	0.00	

<b>Company:</b>	EOG Resources	<b>Local Co-ordinate Reference:</b>	Well Fox Creek #03-26H
<b>Project:</b>	Weld Co., CO	<b>TVD Reference:</b>	Fox Creek 3-26H KBE @ 5439.0ft (SST 56)
<b>Site:</b>	Sec 26-T12N-R63W	<b>MD Reference:</b>	Fox Creek 3-26H KBE @ 5439.0ft (SST 56)
<b>Well:</b>	Fox Creek #03-26H	<b>North Reference:</b>	True
<b>Wellbore:</b>	STK #1	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	STK #1	<b>Database:</b>	Local

Survey Annotations				
Measured Depth	Vertical Depth	Local Coordinates		Comment
0	0	+N/-S	+E/-W	
12,092.0	7,578.1	3,907.7	-2,887.7	Projection to Bit

Checked By: \_\_\_\_\_ Approved By: \_\_\_\_\_ Date: \_\_\_\_\_

