

THIS DOCUMENT IS THE PROPERTY OF HALLIBURTON ENERGY SERVICES, INC. AND IS LOANED SUBJECT TO RETURN UPON DEMAND. THE INFORMATION CONTAINED HEREIN IS CONFIDENTIAL AND NOT TO BE DISCLOSED TO ANY UNAUTHORIZED PERSON WITHOUT THE WRITTEN CONSENT OF HALLIBURTON ENERGY SERVICES, INC.

THREE CYCLONE DIVISIONS EXPANSION WELL SERVICES
EXPLORATION AND PRODUCTION DEPARTMENT, CYCLONE DIVISIONS
MAIN PASS BLOCK 69, OFFSHORE, LA
WELL: MP 69 #A-14 ST BP01

Company: Three Cyclone Divisions Expansion Well Services
Well: MP 69 #A-14 ST BP01
Field: Main Pass Block 69
Location: Offshore, LA
Date: 14-Jan-2026
Run: 1 of 1

Logging Suite: Triple Combo + Sonic + Dipole Shear
Tool String: HALS-DSI-HNGS-HLDS-APS-HRLA
Logging Engineer: Cpt. Rex Halliburton
Recorded Mode: Main Log Down

Curve	Min	Max	Units
GR	0	150	API
CALI	6	16	in
BS	6	16	in
RT	0.2	2000	ohm.m
RM	0.2	2000	ohm.m
RS	0.2	2000	ohm.m
NPHI	0.45	-0.15	v/v
DPHI	0.45	-0.15	v/v
RHOB	1.95	2.95	g/cc
PEF	0	10	b/e
DRHO	0.25	-0.25	g/cc
DTC	140	40	us/ft
DTS	240	80	us/ft

Depth Reference: Rotary Kelly Bushing (RKB) at 0 ft above Mean Sea Level
Permanent Datum: Mean Sea Level
Elevation: KB 0 ft / GL -78 ft



Database File: c:\dbs\Hendrickson01-12pt.db
Dataset Pathname: open
Dataset Creation: Mon Feb 28 11:54:55 2010 by Log Rec Datasfrom 10391

Gamma Ray Calibration Report

Calibration Report

Serial Number: MGamma
Tool Model: GR/CCL
Calibration Date: Fri May 21 08:37:36 2010

Calibrator Value: 1.0 GAPI

Background Reading: 0.0 GA
Background Subtract: Y

Sensitivity: 1.0000 GAPI/cps

CBL Calibration Report

Serial Number: 1
Tool Model: Twin3_OD
Calibration Date: Fri May 21 08:37:36 2010

Fluid Info: N
Casing Diameter: 4.500 in

F Running F Running

Digital Zero: 0.302 0.302 mV
Transmitter Amplitude: 0.997 0.997 mV
Receiver at Signal Zero: 0.000 0.000 V
Receiver at Max Pipe: 1.000 1.000 V

Gain: 32.002 32.461
Offset: 0.000 0.044