

**APPLICATION FOR PERMIT TO:**

1.  **Drill,**       Deepen,       Re-enter,       Recomplete and Operate

2. TYPE OF WELL

OIL       GAS       COALBED       OTHER \_\_\_\_\_

SINGLE ZONE       MULTIPLE       COMMINGLE

Refiling   
Sidetrack

Document Number:  
400233311

PluggingBond SuretyID  
20010124

3. Name of Operator: KERR-MCGEE OIL & GAS ONSHORE LP      4. COGCC Operator Number: 47120

5. Address: P O BOX 173779  
City: DENVER      State: CO      Zip: 80217-3779

6. Contact Name: Cheryl Light      Phone: (720)929-6461      Fax: (720)929-7461  
Email: cheryl.light@anadarko.com

7. Well Name: CAMP      Well Number: 36N-26HZ

8. Unit Name (if appl): \_\_\_\_\_      Unit Number: \_\_\_\_\_

9. Proposed Total Measured Depth: 11968

**WELL LOCATION INFORMATION**

10. QtrQtr: NENE      Sec: 26      Twp: 3N      Rng: 66W      Meridian: 6  
Latitude: 40.201631      Longitude: -104.737555

Footage at Surface:      667      feet      FNL      733      feet      FEL

11. Field Name: WATTENBERG      Field Number: 90750

12. Ground Elevation: 5013      13. County: WELD

14. GPS Data:  
Date of Measurement: 11/11/2011      PDOP Reading: 1.3      Instrument Operator's Name: OWEN McKEE

15. If well is  Directional       Horizontal (highly deviated)      **submit deviated drilling plan.**

Footage at Top of Prod Zone:      FNL/FSL      FEL/FWL      Bottom Hole:      FNL/FSL      FEL/FWL

634      FNL      2260      FEL      460      FSL      2260      FEL

Sec: 26      Twp: 3N      Rng: 66W      Sec: 26      Twp: 3N      Rng: 66W

16. Is location in a high density area? (Rule 603b)?       Yes       No

17. Distance to the nearest building, public road, above ground utility or railroad: 907 ft

18. Distance to nearest property line: 642 ft      19. Distance to nearest well permitted/completed in the same formation(BHL): 461 ft

**LEASE, SPACING AND POOLING INFORMATION**

Objective Formation(s)	Formation Code	Spacing Order Number(s)	Unit Acreage Assigned to Well	Unit Configuration (N/2, SE/4, etc.)
NIOBRARA	NBRR		320	W/2E/2, E/2W/2

21. Mineral Ownership:       Fee       State       Federal       Indian      Lease #: \_\_\_\_\_

22. Surface Ownership:       Fee       State       Federal       Indian

23. Is the Surface Owner also the Mineral Owner?       Yes       No      Surface Surety ID#:

23a. If 23 is Yes: Is the Surface Owner(s) signature on the lease?       Yes       No

23b. If 23 is No:  Surface Owners Agreement Attached or       \$25,000 Blanket Surface Bond       \$2,000 Surface Bond       \$5,000 Surface Bond

24. Using standard QtrQtr, Sec, Twp, Rng format enter entire mineral lease description upon which this proposed wellsite is located (attach separate sheet/map if you prefer):

Please see attached Oil and Gas Lease.

25. Distance to Nearest Mineral Lease Line: 371 ft 26. Total Acres in Lease: 560

### DRILLING PLANS AND PROCEDURES

27. Is H2S anticipated?  Yes  No If Yes, attach contingency plan.

28. Will salt sections be encountered during drilling?  Yes  No

29. Will salt (>15,000 ppm TDS CL) or oil based muds be used during drilling?  Yes  No

30. If questions 28 or 29 are yes, is this location in a sensitive area (Rule 901.e)?  Yes  No

31. Mud disposal:  Offsite  Onsite

If 28, 29, or 30 are "Yes" a pit permit may be required.

Method:  Land Farming  Land Spreading  Disposal Facility Other: \_\_\_\_\_

Note: The use of an earthen pit for Recompletion fluids requires a pit permit (Rule 905b). If air/gas drilling, notify local fire officials.

Casing Type	Size of Hole	Size of Casing	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top
SURF	12+1/4	9+5/8	36.0	0	900	670	900	0
1ST	8+3/4	7	26.0	0	7,790	770	7,790	
1ST LINER	6+1/8	4+1/2	11.6	6718	11,968			

32. BOP Equipment Type:  Annular Preventer  Double Ram  Rotating Head  None

33. Comments No conductor casing will be used. At the time of permitting, the operator has identified the following well(s) as being within close proximity of the proposed well: CAMP 36N-26HZ• CAMP 21-26• CAMP 21-26X• CAMP 7-26• CAMP 10-26CAMP 37N-26HZ• CAMP 39-26• HSR-SHOWALTER 16-26• CAMP 37-26CAMP 38C-26HZ• CAMP 38N-26HZ• CAMP 39-26CAMP 38N-26HZ• CAMP 38C-26HZ• CAMP 39-26Camp 15N-26HZ• CAMP-C1• LEWIS CAMP-C2

34. Location ID: 327420

35. Is this application in a Comprehensive Drilling Plan ?  Yes  No

36. Is this application part of submitted Oil and Gas Location Assessment ?  Yes  No

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Cheryl Light

Title: Sr. Regulatory Analyst Date: 12/16/2011 Email: DJRegulatory@anadarko.com

Based on the information provided herein, this Application for Permit-to-Drill complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: David S. Neslin Director of COGCC Date: 1/15/2012

**API NUMBER**  
05 123 34950 00

Permit Number: \_\_\_\_\_ Expiration Date: 1/14/2014

#### CONDITIONS OF APPROVAL, IF ANY:

All representations, stipulations and conditions of approval stated in the Form 2A for this location shall constitute representations, stipulations and conditions of approval for this Form 2 Permit-to-Drill and are enforceable to the same extent as all other representations, stipulations and conditions of approval stated in this Permit-to-Drill.

- 1) Provide 24 hour notice of MIRU to Mike Hickey via e-mail at mike.hickey@state.co.us.
- 2) Comply with Rule 317.i and provide cement coverage from the end of the production casing to a minimum of 200' above the Niobrara. Verify coverage with a cement bond log.
- 3) Comply with Rule 321. Run and submit Directional Survey from the end of production casing to base of surface casing. Ensure that the wellbore complies with setback requirements in commission orders or rules prior to producing the well.

**Attachment Check List**

Att Doc Num	Name
2113199	WAIVERS
2481356	SURFACE CASING CHECK
400233311	APD APPROVED
400233317	DEVIATED DRILLING PLAN
400233319	PLAT
400233320	TOPO MAP
400233321	30 DAY NOTICE LETTER
400233322	SURFACE AGRMT/SURETY
400233323	OIL & GAS LEASE
400233324	PROPOSED SPACING UNIT
400233325	OTHER
400241131	FORM 2 SUBMITTED

Total Attach: 12 Files

**General Comments**

<b><u>User Group</u></b>	<b><u>Comment</u></b>	<b><u>Comment Date</u></b>
Permit	Final review complete	1/10/2012 9:39:00 AM
Permit	Added BMP's, waivers, and comment about close proximity of proposed well as directed by opr. Ready to pass pending public comment 1/9/12.	12/21/2011 11:00:22 AM
Permit	Requested HZ BMP's from Opr.	12/19/2011 1:41:47 PM

Total: 3 comment(s)

## BMP

<u>Type</u>	<u>Comment</u>
Drilling/Completion Operations	<ol style="list-style-type: none"><li>1. At least seven (7) days prior to fracture stimulation, the operator is to notify all operators of non-operated wells within 300 feet of the wellbore to be fracture stimulated of the anticipated date stimulation date and the recommended best management practice to shut-in all wells within 300' of the stimulated wellbore completed in the same formation.</li><li>2. The operator will monitor the bradenhead pressure of all wells operated by the operator within 300 feet of the well to be fracture stimulated.</li><li>3. Bradenhead pressure gauges are to be installed 24 hours prior to stimulation. The gauges are to read at least once during every 24-hour period until 24-hours after stimulation is completed (post flowback). The gauges are to be of the type able to read current pressure and record the maximum encountered pressure in a 24-hour period. The gauge is to be reset between each 24-hour period. The pressures are to be recorded and saved. Alternate electronic measurement may be used to record the prescribed pressures. Data shall be kept for a period of one year.</li><li>4. If at any time during stimulation or the 24-hour post-stimulation period, the bradenhead annulus pressure of the treatment well or offset wells increases more than 200 psig, as per Rule 341, the operator of the well being stimulated shall verbally notify the Director as soon as practicable, but no later than twenty-four (24) hours following the incident. Within fifteen (15) days after the occurrence, the operator shall submit a Sundry Notice, Form 4, giving all details, including corrective actions taken.</li></ol>
Drilling/Completion Operations	"Prior to drilling operations, Operator may perform an anti-collision review of existing offset wells that have the potential of being within close proximity of the proposed well. This anti-collision review may include MWD or gyro surveys and surface locations of the offset wells with included error of uncertainty per survey instrument, and compared against the proposed wellpath with its respective error of uncertainty. If current surveys do not exist for the offset wells, Operator may have gyro surveys conducted to verify bottomhole location. The proposed well may only be drilled if the anti-collision review results indicate that the risk of collision is sufficiently low as defined by the anti-collision plan, with separation factors greater than 1.5, or if the risk of collision has been mitigated through other means including shutting in wells, plugging wells, increased drilling fluid in the event of lost returns or as is appropriate for the specific situation. In the event of an increased risk of collision, that risk will be mitigated to prevent harm to people, the environment or property. For the proposed well, upon conclusion of drilling operations, an as-constructed directional survey will be submitted to COGCC with the Form 5. "

Total: 2 comment(s)