

WELLBORE DIAGRAM

Operator: EnCana Oil & Gas (USA) Inc.
 Well Name: Parker 2-4-33
 Location: SENW Sec 33 T3N R67W 6th PM
 Field: Wattenberg
 County: Weld
 API Number: 05-123-24751-00
 Diagram Date: 06/12/2007
 Rev: 1/31/2012

FORMATIONS

Sussex 4206'
 Shannon 4748'
 Niobrara 7082'
 Codell 7328'
 J Sand 7770'

KB 4816'
 GL 7937'

Well History

Spud Date 03/13/2007
 TD Reached 03/20/2007
 Rig Released 03/21/2007
 Completion Date
 First Sales: 04/02/2007

13 jts 8.625" 24# N-80 LT&C (csg @ 519'; cmt w/ 190 sx)
 Type III lead; 100 sx Type III tail

CIBP

Set @ 7410 on 12/5/11

CFP

Set @ 7200 on 12/5/11

CFP

Set @ 7450 on 3/27/07
 Drilled out 4/10/07

CFP

Set @ 7250 on 3/27/07
 Drilled out 4/10/07

7124-7144' Niobrara Perfs shot 03/28/07, 4 spf, 40 holes
 Frac'd w/ 165,492 gal frac fluid and 196,201 # sand

Niobrara Refrac 12/05/2011
 Frac'd w/ 128,661 gal frac fluid and 250,940 # sand

7330-7350' Codell Perfs shot 03/28/07, 4 spf, 80 holes
 Frac'd w/ 118,513 gal frac fluid and 252,000 # sand

Codell Refrac 12/05/2011
 Frac'd w/ 134,530 gal frac fluid and 249,480 # sand

7784-7812' J Sand Perfs shot 03/23/07, 4 spf, 56 holes
 Frac'd w/ 177,779 gal frac fluid and 250,180 # sand

PBTD 7896'

7937'

189 jts 4.5" 11# I-80 LT&C csg @ 7907'
 Cmt w/ 285 sx G 50/50 Poz