

# Hilcorp – Niobrara Recomplete 2011

Spud Date: 2/17/1995  
 Compl. Date: 3/23/1995

12-1/4" bit

8-5/8" 24# J-55 @ 448'  
 Cmt'd to surface w/ 315 sx

DV Tool @ 1808'  
 Cmt'd to surface w/ 615 sx  
 15.85 POZ A

TOC @ 6730' by CBL

Niobrara Perfs  
 7200'-7220' 1 SPF  
 7265'-7288' 4 SPF

CIBP 7760'

7-7/8" bit

4-1/2" 11.6# I-80 @ 8015'  
 Cmt'd w/ 215 sx Class G

TAC @ 7,757' w/ 15k# tension

SN @ 7,885'  
 EOT @ 7919'

"D" Sand perfs 7,820'-7,830' @ 4 SPF  
 Frac'd w/ 56k# 20/40 Sd & 24k# 20/40 Carbolite

PBTD = 7,970' (F III)  
 TD = 8,028'

WELL NAME/NUMBER  
**HSR Nazareus 16-8**

DESCRIPTION  
**SESE Sec. 8 T2S R64W, Adams Cty., CO**

KB = 5263  
 THF = 5257'  
 CHF = 5254'  
 GL = 5253'  
 Serial Nbr.  
 API Nbr. 05-001-09309

FIELD/LEASE/AREA  
**Trapper South**

PREPARED BY  
 LED

APPROVED/DATE  
 10/6/2010