
Gamma Ray (API)
Caliper (in)
Bit Size (in)
Density (g/cm3)
Neutron Porosity (dec)
Photoelectric Factor (b/e)
Resistivity (ohmm)
Deep Resistivity (ohmm)
Medium Resistivity (ohmm)
Shallow Resistivity (ohmm)
Spontaneous Potential (mV)
Delta Rho (g/cm3)
Rate of Penetration (m/h)
Mud Weight (ppg)
Mud Type
Mud Resistivity (ohmm)
Mud Filtrate Resistivity (ohmm)
Mud Cake Resistivity (ohmm)
Mud Temperature (degC)
Mud Filtrate Temperature (degC)
Mud Cake Temperature (degC)
Max Recorded Temperature (degC)
Circulation Stopped Time
Logger on Bottom Time
Unit Number
Location
Recorded By
Witnessed By
Run Number
Depth Driller (m)
Depth Logger (m)
Bottom Logged Interval (m)
Top Logged Interval (m)
Casing Driller Size @ Depth (in) @ (m)
Casing Logger Size @ Depth (in) @ (m)
Bit Size (in)
Type Fluid in Hole
Density (ppg)
Viscosity (s)
PH
Fluid Loss (ml)
Source of Sample
Rm @ Measured Temperature (ohmm) @ (degC)
Rmf @ Measured Temperature (ohmm) @ (degC)
Rmc @ Measured Temperature (ohmm) @ (degC)
Source of Rmf and Rmc
Rm @ BHT (ohmm)
Time Since Circulation (hr)
Max Recorded Temperature (degC)
Equipment;


5600
5650
5700
5750
5800
5850
5900
5950
6000
6050
6100
6150
6200
6250
6300
6350
6400
6450
6500
6550
6600
6650
FLAG
6700
6750
6800
6850
6900
6950
FLAG
7000
7050
7100
Loggers TD @ 7118'
400
Travel Time (usec)
200 0.5 CCL 1.0
Amplitude (mV)
100 200
Variable Density
1200
30
Collar Locator
-0.05
0
Gamma Ray (GAPI)
200