
Triple Combo Gamma Ray Neutron Density
Triple Combo Gamma Ray Neutron Density
Triple Combo Gamma Ray Neutron Density



Company: [redacted]
Well: [redacted]
Field: [redacted]
Location: [redacted]
Logging Date: 2022-03-15 08:38
Run Number: 1
Depth Driller: 10,000 ft
Depth Logger: 10,000 ft
Bottom Log Interval: 10,000 ft
Top Log Interval: 9,000 ft
Drilling Fluid Type: Water Based Mud
Drilling Fluid Density: 9.2 ppg
Max Recorded Temperature: 210 °F
Max Recorded Pressure: 4,800 psi
Tool String: Triple Combo
Tool Serial Number: 1234
Tool Length: 45 ft
Tool Weight: 1,200 lb
Tool Diameter: 3.625 in
Tool Max Temperature: 350 °F
Tool Max Pressure: 20,000 psi
Tool Max Speed: 3,600 ft/hr
Tool Min Speed: 1,800 ft/hr
Tool Max Tension: 30,000 lb
Tool Min Tension: 5,000 lb
Tool Max Current: 2.5 A
Tool Min Current: 1.5 A
Tool Max Voltage: 600 V
Tool Min Voltage: 300 V
Tool Max Frequency: 1,000 Hz
Tool Min Frequency: 500 Hz
Tool Max Power: 1,500 W
Tool Min Power: 750 W
Tool Max Resistance: 1,000 ohm
Tool Min Resistance: 500 ohm
Tool Max Capacitance: 1,000 pF
Tool Min Capacitance: 500 pF
Tool Max Inductance: 1,000 mH
Tool Min Inductance: 500 mH
Tool Max Conductance: 1,000 mS
Tool Min Conductance: 500 mS
Tool Max Susceptibility: 1,000 SI
Tool Min Susceptibility: 500 SI
Tool Max Permeability: 1,000 H/m
Tool Min Permeability: 500 H/m
Tool Max Permittivity: 1,000 F/m
Tool Min Permittivity: 500 F/m
Tool Max Resistivity: 1,000 ohm-m
Tool Min Resistivity: 500 ohm-m
Tool Max Conductivity: 1,000 S/m
Tool Min Conductivity: 500 S/m