

Well

Operator
Location
County
State
Field

ECHEVERRIA 14-2

EnCana Oil & Gas (USA) Inc.
SWSW Section 2-T2N-R67W
Weld
Colorado
Wattenberg

Footages: 462' FSL & 460' FWL
Spud Date: 09-28-1999
TD Date: 10-02-1999

Log Tops

Sussex	4314'
Shannon	4849'
Niobrara	7136'
Codell	7398'
J 3 Sand	7867'

CIBP

Set @ 7460' on 1-19-12
Drilled out 2/28/12

CFP

Set @ 7330' 1/19/12
Drilled out 2/28/12

CFP

Set @ 7290' on 01-19-09
Drilled out on 01-22-09

CBP

Set @ 7500' on 01-08-09.
Drilled out

Production Tubing

2-3/8", Set @ 7824
2/28/12'

Surface Casing and Cement

8 5/8", 24#, landed @ 763', cemented with 495 sxs

Main Hole

7-7/8" to TD

Production Casing and Cement

4-1/2", 11.6#, landed @ 8024', cemented with 250 sxs

DV tool

Set @ 5099', cemented above DV tool with 250 sxs

Niobrara Refrac

Refrac'd from 7190' - 7206' with 140,327 gal frac fluid and 251,300# sand. 01-19-12

Codell Tri-frac

Frac'd 7398' - 7418' with 121,939 gal frac fluid and 251,780# sand. 01-19-12

Perf'd the Niobrara from 7190' - 7206' @ 2 spf, 32 shots.
Frac'd the Niobrara with 149,736 gal 18# Vistar cross linked gel Hybrid containing 250,540# sand. 01-19-09

Re-frac'd the Codell from 7398' - 7418' with 113,400 gal frac fluid containing 250,580# sand. 01-19-09

Perf'd the Codell from 7398' - 7418', 80 holes
Frac'd the Codell with 128,856 gals Frac fluid and 310,080# sand. 03/24/01

Perf'd the J Sand from 7846' - 7904' @ 2 spf, 100 holes
Frac'd the J Sand with 223,050 gals Primagel G Frac gel 27, 25. 1 ppg thru 5 ppg. and 539,000# 20/40 frac sand. 10-15-99

8020' — Driller's
TD

Rev 4/27/12 jw