

Kubeczko, Dave

From: Kubeczko, Dave
Sent: Tuesday, May 01, 2012 2:58 PM
To: Kubeczko, Dave
Subject: FW: Williams Production RMT, Federal RGU 33-36-198 Pad , Lot 10 Sec 36 T1S R98W, Garfield County, Form 2A #400264299 Review

Categories: Orange - Operator Correspondence, Brown - 2A Review Email to Operator

Scan No 2034323 CORRESPONDENCE 2A#400264299

From: Kubeczko, Dave
Sent: Sunday, April 22, 2012 5:53 PM
To: 'howard.harris@williams.com'
Subject: Williams Production RMT, Federal RGU 33-36-198 Pad , Lot 10 Sec 36 T1S R98W, Garfield County, Form 2A #400264299 Review

Howard,

I have been reviewing the Federal RGU 33-36-198 Pad **Form 2A** (#400264299). COGCC would like to attach the following conditions of approval (COAs) based on the information WPX Energy Rocky Mountain has submitted on or attached to the Form 2A prior to passing the Oil and Gas Location Assessment (OGLA) review.

1. **General:** The following conditions of approval (COAs) will apply:
 - COA 5** - Operator must implement best management practices to contain any unintentional release of fluids, including any fluids conveyed via temporary surface pipelines.
 - COA 9** - Reserve pit, or any other pit used to contain/hold fluids, if constructed, must be lined or a closed loop system (as indicated on the Form 2A Permit) must be implemented during drilling.
 - COA 23** - Operator must ensure secondary containment for any volume of fluids contained at well site during drilling and completion operations; including, but not limited to, construction of a berm or diversion dike, diversion/collection trenches within and/or outside of berms/dikes, site grading, or other comparable measures (i.e., best management practices (BMPs) associated with stormwater management) sufficiently protective of nearby surface water. Any berm constructed at the well pad location will be stabilized, inspected at regular intervals (at least every 14 days), and maintained in good condition.
 - COA 25** - Flowback and stimulation fluids must be sent to tanks, separators, or other containment/filtering equipment before the fluids can be placed into any pipeline or pit located on the well pad or into tanker trucks for offsite disposal. The flowback and stimulation fluid tanks, separators, or other containment/filtering equipment must be placed on the well pad in an area with additional downgradient perimeter berming. The area where flowback fluids will be stored/reused must be constructed to be sufficiently impervious to contain any spilled or released material.
 - COA 38** - The moisture content of any drill cuttings in a cuttings pit, trench, or pile shall be as low as practicable to prevent accumulation of liquids greater than de minimis amounts. At the time of closure, the drill cuttings must also meet the applicable standards of table 910-1.

Based on the information provided in the Form 2A by WPX, COGCC will attach these COAs to the Form 2A permit, WPX does not need to respond, unless WPX has questions or concerns with details in this email. If you have any questions regarding this email, please do not hesitate to call me at (970) 309-2514 (cell), or email. Thanks.

Dave

David A. Kubeczko, PG

Oil and Gas Location Assessment Specialist

Colorado Oil & Gas Conservation Commission
Northwest Area Office
707 Wapiti Court, Suite 204
Rifle, CO 81650
Phone: (970) 625-2497x5
FAX: (970) 625-5682
Cell: (970) 309-2514
dave.kubeczko@state.co.us



 *Please consider the environment before printing this e-mail*