

BISON OIL WELL CEMENTING, INC.

1738 Wynkoop St., Ste. 102
Denver, Colorado 80202
Phone: 303-296-3010
Fax: 303-298-8143
E-mail: bisonoil1@qwestoffice.net

TREATMENT REPORT

REF. INVOICE # 10708
LOCATION WCR 59+48
FOREMAN Calvin Reimers

DATE	1-5-12	WELL NAME	Maxley C 01-24D	SECTION	1	TWP	4N	RGE	64W	COUNTY	Weld	FORMATION	
------	--------	-----------	-----------------	---------	---	-----	----	-----	-----	--------	------	-----------	--

CHARGE TO	11:30 AM	TIME ARRIVED ON LOCATION
Mailing Address		STATE ZIP CODE
CITY		
CONTRACTOR	54XON Rtg 143	DISTANCE TO LOCATION
OWNER	8:00 PM	TIME LEFT LOCATION

HOLE SIZE	12 1/4	TUBING SIZE	PERFORATIONS		SURFACE PIPE ANNULUS LONG	THEORETICAL	INSTRUCTED
TOTAL DEPTH	700	TUBING DEPTH	SHOTS/FT				
POTD 657.20		TUBING WEIGHT	OPEN HOLE		STRING		
CASING SIZE	8 5/8	TUBING CONDITION			TUBING		
CASING DEPTH	700.74	TREATMENT VIA				TYPE OF TREATMENT	TREATMENT RATE

[illegible]

INSTRUCTIONS PRIOR TO JOB
Rising, Safety Meeting, Bar Company, Man, Lic. # 406615 H²O with KCl + Oxy in 1.2% to 1.6%
Mix pump tell Dye is seen then pump Tub only at 1.52 lbs. 1.27 yield, Drop plug, Displace 41.8 bbls.
H²O, Pump plug at 1.50 P.S. over 1st P.S. wait 5 min. then bleed off P.S., Wash up Rig down.
H²O Tested good, we have 450 SKS, 32.02 Dye, 10 qts KCl.

DESCRIPTION OF JOB EVENTS	TIME
JOBS SUMMARY	
Safety meetings	2:00 pm, 4:10 pm then 4:27 pm, 4:35 pm

Drop Plug 5:16 pm, Displace 5:17 pm.
1066/5 10 psi, 5:28 pm? 666/m
2066/5, 110 psi, 5:44 pm? 666/m
3066/5, 230 psi, 5:46 pm? 566/m
41866/5, 170 psi, 5:49 pm, 1066/5/m
Bumping Plug 250 psi at 5:49 pm

Did not get cement to surface flat collar held
 used 10% excess = 251 sks, 56.77 bbls slurry
 top job used 79 sks, 17.86 bbls slurry
 total job used 45% excess = 330 sks, 74.64 bbls slurry
 0 bbls slurry to the pit