Company: Laramie Energy, Inc.
Well: Ellis 43-17
Field: Mamm Creek
County: Garfield
State: Colorado
Location: 1,000' FNL & 1,000' FEL
Sec. 17 T. 6S R. 93W
Permanent Datum: Ground Level
Elevation: 6,000 ft
Log Measured From: KB, 18 ft above Perm. Datum
Drilling Measured From: KB
Date: 10-16-2011
Run Number: One
Depth Driller: 7,400 ft
Depth Logger: 7,400 ft
Bottom Logged Interval: 7,400 ft
Top Logged Interval: 1,000 ft
Type Fluid in Hole: Water
Salinity, PPM Cl: 1,000
Density: 8.4 lb/gal
Viscosity: 26 s/qt
Fluid Loss: 10 cc
Source of Sample: Flowline
Rm @ Meas Temp: 0.75 @ 70 °F
Rmf @ Meas Temp: 0.56 @ 70 °F
Rmc @ Meas Temp: 1.1 @ 70 °F
Source of Rmf and Rmc: Measured
Rm @ BHT: 0.37 @ 150 °F
Time Circulation Stopped: 03:00
Time Logger on Bottom: 08:00
Maximum Recorded Temperature: 150 °F
Equipment Number: 3
Location: Rifle
Recorded By: Jeff Hoffman
Witnessed By: Jeff Hoffman

All data supplied by the customer based on references that are believed to be reliable but are not guaranteed to be correct, and accordingly Precision Energy Services, Inc. and its employees will not be responsible for damages or liability suffered or sustained by anyone by reason of any use or interpretation of the data. In consideration of the foregoing, the customer agrees to indemnify and hold Precision Energy Services, Inc. and its employees harmless against any and all claims, suits, or damages, whether caused by the negligence of Precision Energy Services, Inc. and its employees or otherwise, arising out of the use or interpretation of the data furnished hereunder.

COMMENTS

Annular volume calculated for 4.5" casing
Ensign Drilling Rig 55
Thank you for using Rowes Surveys.
API # 05-123-34835-00

Tolerance Per: CNW-IB
Dataset Pathname: field
Dataset Creation: Tue Oct 18 16:08:09 2011
Charted Depth: Starts Bott Loaded 1 Min

Cal (in) 6 16 | Density Caliper (in) 6 16
GR (API) 0 200 | Gamma Ray (GAPI) 0 200
SP (mV) -100 100 | SP (mV) -100 100

Deep Resistivity (Ohm-m) .2000 20 | Density Porosity (pu) 45 -15
Medium Resistivity (Ohm-m) .2000 20 | Neutron Porosity (pu) 45 -15
Shallow Resistivity (Ohm-m) .2000 20
Rt (Ohm-m) .2000

1:240 (5" / 100ft)

1:60 (1" / 100ft)

1:120 (2.5" / 100ft)

Tolerance Per: CNW-IB
Dataset Pathname: field
Dataset Creation: Tue Oct 18 16:08:09 2011
Charted Depth: Starts Bott Loaded 1 Min

Cal (in) 6 16 | Density Caliper (in) 6 16
GR (API) 0 200 | Gamma Ray (GAPI) 0 200
SP (mV) -100 100 | SP (mV) -100 100

Deep Resistivity (Ohm-m) .2000 20 | Density Porosity (pu) 45 -15
Medium Resistivity (Ohm-m) .2000 20 | Neutron Porosity (pu) 45 -15
Shallow Resistivity (Ohm-m) .2000 20
Rt (Ohm-m) .2000

1:240 (5" / 100ft)

1:60 (1" / 100ft)

1:120 (2.5" / 100ft)