

FORM  
5A

Rev  
06/12

State of Colorado  
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

400314240

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 100322  
2. Name of Operator: NOBLE ENERGY INC  
3. Address: 1625 BROADWAY STE 2200  
City: DENVER State: CO Zip: 80202  
4. Contact Name: Andrea Rawson  
Phone: (303) 228-4253  
Fax: (303) 228-4286

5. API Number 05-123-17554-00  
6. County: WELD  
7. Well Name: KUIPERS RED V  
Well Number: 12-2  
8. Location: QtrQtr: NWNE Section: 12 Township: 2N Range: 67W Meridian: 6  
9. Field Name: WATTENBERG Field Code: 90750

Completed Interval

FORMATION: CODELL Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 01/25/2012 End Date: 01/25/2012 Date of First Production this formation: 04/11/1994

Perforations Top: 7349 Bottom: 7364 No. Holes: 45 Hole size: 0.22

Provide a brief summary of the formation treatment: Open Hole: ☐

Tri-Frac'd Codell w/ 140237 gals of Slick Water and Vistar with 247831#'s of Ottawa sand.

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 3339 Max pressure during treatment (psi): 5232

Total gas used in treatment (mcf): 0 Fluid density at initial fracture (lbs/gal):

Type of gas used in treatment: Max frac gradient (psi/ft): 0.84

Total acid used in treatment (bbl): Number of staged intervals: 6

Recycled water used in treatment (bbl): Flowback volume recovered (bbl):

Fresh water used in treatment (bbl): Disposition method for flowback: RECYCLE

Total proppant used (lbs): 247831 Rule 805 green completion techniques were utilized: ☒

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 03/09/2012 Hours: 24 Bbl oil: 6 Mcf Gas: 118 Bbl H2O: 4

Calculated 24 hour rate: Bbl oil: 6 Mcf Gas: 118 Bbl H2O: 4 GOR: 19667

Test Method: Flowing Casing PSI: 562 Tubing PSI: 519 Choke Size: 38

Gas Disposition: SOLD Gas Type: WET Btu Gas: 1321 API Gravity Oil: 55

Tubing Size: 2 + 1/16 Tubing Setting Depth: 7315 Tbg setting date: 01/31/2012 Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:

--

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Andrea Rawson

Title: Regulatory Specialist Date: \_\_\_\_\_ Email arawson@nobleenergyinc.com  
:

### **Attachment Check List**

Att Doc Num	Name
400314243	WELLBORE DIAGRAM

Total Attach: 1 Files

### **General Comments**

<b><u>User Group</u></b>	<b><u>Comment</u></b>	<b><u>Comment Date</u></b>

Total: 0 comment(s)