

P&A Procedure for the N Parachute WF03D A15 596

Encana Oil and Gas

15-5S-96W Garfield County, Colo.

9 5/8" @ 2,470' TOC at Surface

PBTD at surface casing shoe, well never finished

MIRU, NDWH, NUBOP

RIH with work string to TD

Set 40 sxs of cement (105' in 9 5/8")

POH, NDBOP

RIH to 100' circulate cement to surface

Cut off the wellhead

Top off cement if necessary in annulus

Weld a plate with well information, RDMO

All cement is 15.8# class G neat with a 1.15 cuft/sack yield

N Parachute WF03D A15 596

API #: 05045106060000

Location: Sec. 15-5S-96W

KB: 6,532 (20' AGL)

GL: 6,512'

County/St: Garfield, CO

Created By: T. Gallagher

Date: 7/30/2012

Current Wellbore



16" Hole
13-3/8" Conductor set @ 90'
Cemented to surface



12-1/4" Hole
9-5/8", 36#, J-55 csg set @ 2,470'
Cemented to surface w/ 810 sx

N Parachute WF03D A15 596

API #: 05045106060000

Location: Sec. 15-5S-96W

KB: 6,532 (20' AGL)

GL: 6,512'

County/St: Garfield, CO

Created By: T. Gallagher

Date: 7/30/2012

Proposed Wellbore

