

FORM  
5A

Rev  
06/12

State of Colorado  
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

400317360

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 100322  
2. Name of Operator: NOBLE ENERGY INC  
3. Address: 1625 BROADWAY STE 2200  
City: DENVER State: CO Zip: 80202  
4. Contact Name: Tania McNutt  
Phone: (303) 228-4392  
Fax: (303) 228-4286

5. API Number 05-123-34677-00  
6. County: WELD  
7. Well Name: PANTHER C  
Well Number: 11-28D  
8. Location: QtrQtr: SESE Section: 2 Township: 4N Range: 64W Meridian: 6  
9. Field Name: WATTENBERG Field Code: 90750

Completed Interval

FORMATION: CODELL Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 04/23/2012 End Date: 04/23/2012 Date of First Production this formation: 05/07/2012

Perforations Top: 7236 Bottom: 7248 No. Holes: 48 Hole size: 0.41

Provide a brief summary of the formation treatment: Open Hole: ☐

Pumped 241,202 lbs of Ottawa Proppant and 115,829 gallons of 15% HCL and Slick Water.

This formation is commingled with another formation: ☒ Yes ☐ No

Total fluid used in treatment (bbl): 3068 Max pressure during treatment (psi): 4011

Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment: Max frac gradient (psi/ft): 0.85

Total acid used in treatment (bbl): Number of staged intervals: 1

Recycled water used in treatment (bbl): Flowback volume recovered (bbl):

Fresh water used in treatment (bbl): Disposition method for flowback: RECYCLE

Total proppant used (lbs): 241202 Rule 805 green completion techniques were utilized: ☒

Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: Hours: Bbl oil: Mcf Gas: Bbl H2O:

Calculated 24 hour rate: Bbl oil: Mcf Gas: Bbl H2O: GOR:

Test Method: Casing PSI: Tubing PSI: Choke Size:

Gas Disposition: Gas Type: Btu Gas: API Gravity Oil:

Tubing Size: Tubing Setting Depth: Tbg setting date: Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA-CODELL Status: PRODUCING Treatment Type: \_\_\_\_\_

Treatment Date: \_\_\_\_\_ End Date: \_\_\_\_\_ Date of First Production this formation: 05/07/2012

Perforations Top: 7052 Bottom: 7248 No. Holes: 96 Hole size: \_\_\_\_\_

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole: ☐

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_

Type of gas used in treatment: \_\_\_\_\_ Max frac gradient (psi/ft): \_\_\_\_\_

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_

Total proppant used (lbs): \_\_\_\_\_ Rule 805 green completion techniques were utilized: ☐

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: 05/11/2012 Hours: 8 Bbl oil: 57 Mcf Gas: 142 Bbl H2O: 8

Calculated 24 hour rate: Bbl oil: 57 Mcf Gas: 142 Bbl H2O: 8 GOR: 2491

Test Method: FLOWING Casing PSI: 1020 Tubing PSI: \_\_\_\_\_ Choke Size: 12/64

Gas Disposition: SOLD Gas Type: WET Btu Gas: 1309 API Gravity Oil: 51

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 04/24/2012 End Date: 04/24/2012 Date of First Production this formation: 05/07/2012

Perforations Top: 7052 Bottom: 7136 No. Holes: 48 Hole size: 0.73

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole: ☐

Pumped 249,567 lbs of Ottawa Proppant and 155,516 gallons of Slick Water and Silverstim

This formation is commingled with another formation: ☒ Yes ☐ No

Total fluid used in treatment (bbl): 3975 Max pressure during treatment (psi): 4590

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment: \_\_\_\_\_ Max frac gradient (psi/ft): 0.95

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: 1

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: RECYCLE

Total proppant used (lbs): 249567 Rule 805 green completion techniques were utilized: ☒

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: \_\_\_\_\_ Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_

Calculated 24 hour rate: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_

Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_

Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

Comment: \_\_\_\_\_

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Tania McNutt

Title: Regulatory Analyst Date: \_\_\_\_\_ Email: tmcnutt@nobleenergyinc.com

**Attachment Check List**

Att Doc Num	Name

Total Attach: 0 Files

**General Comments**

User Group	Comment	Comment Date

Total: 0 comment(s)