



FORMATION: CODELL Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 11/11/2011 End Date: 11/11/2011 Date of First Production this formation: 11/15/2011  
Perforations Top: 7791 Bottom: 7802 No. Holes: 44 Hole size: 0.42

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole:

Pumped 245,771 lbs of Ottawa Proppant and 116,839 gallons of 15% HCL, Slick Water, and Silverstim.  
The Codell is producing through a composite flow through plug.  
Commingle the Niobrara and Codell.

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): 2782 Max pressure during treatment (psi): 4053

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment: \_\_\_\_\_ Max frac gradient (psi/ft): 0.79

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: 7

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: RECYCLE

Total proppant used (lbs): 245771 Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: \_\_\_\_\_ Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_

Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_

Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_

Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: J-NIOBRARA-CODELL Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 11/03/2011 End Date: 11/12/2011 Date of First Production this formation: 11/15/2011

Perforations Top: 7429 Bottom: 8251 No. Holes: 200 Hole size: \_\_\_\_\_

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole:

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_

Type of gas used in treatment: \_\_\_\_\_ Max frac gradient (psi/ft): \_\_\_\_\_

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_

Total proppant used (lbs): \_\_\_\_\_ Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: 11/18/2011 Hours: 24 Bbl oil: 19 Mcf Gas: 3 Bbl H2O: 21

Calculated 24 hour rate: Bbl oil: 19 Mcf Gas: 3 Bbl H2O: 21 GOR: 158

Test Method: Flowing Casing PSI: 220 Tubing PSI: 0 Choke Size: 12/64

Gas Disposition: SOLD Gas Type: WET Btu Gas: 1333 API Gravity Oil: 51

Tubing Size: 2 + 3/8 Tubing Setting Depth: 8211 Tbg setting date: 03/14/2012 Packer Depth: \_\_\_\_\_

Reason for Non-Production:

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: J SAND Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 11/03/2011 End Date: 11/11/2011 Date of First Production this formation: 11/15/2011  
Perforations Top: 8226 Bottom: 8251 No. Holes: 76 Hole size: 0.4

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole:

Pumped 272,355 lbs of Ottawa Proppant, 12,745 lbs of SB Excel Proppant and 155,863 gallons of Slick Water and Silverstim. The J-Sand is producing through a composite flow through plug.

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): 3711 Max pressure during treatment (psi): 3858

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment: \_\_\_\_\_ Max frac gradient (psi/ft): 0.63

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: 10

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: RECYCLE

Total proppant used (lbs): 285100 Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on [FracFocus.org](http://FracFocus.org)**

**Test Information:**

Date: \_\_\_\_\_ Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_

Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_

Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_

Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: \_\_\_\_\_

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIORARA-CODELL Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 11/11/2011 End Date: 11/12/2011 Date of First Production this formation: 11/15/2011

Perforations Top: 7429 Bottom: 7802 No. Holes: 124 Hole size: \_\_\_\_\_

Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole:

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_

Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_

Type of gas used in treatment: \_\_\_\_\_ Max frac gradient (psi/ft): \_\_\_\_\_

Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_

Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_

Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_

Total proppant used (lbs): \_\_\_\_\_ Rule 805 green completion techniques were utilized:

Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: \_\_\_\_\_ Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_

Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_

Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_

Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_

Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production:

Date formation Abandoned: \_\_\_\_\_ Squeeze:  Yes  No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA Status: COMMINGLED Treatment Type: FRACTURE STIMULATION

Treatment Date: 11/11/2011 End Date: 11/12/2011 Date of First Production this formation: 11/15/2011  
Perforations Top: 7429 Bottom: 7643 No. Holes: 80 Hole size: 0.72

Provide a brief summary of the formation treatment: Open Hole:

Pumped 147,628 lbs of Ottawa Proppant and 97,500 gallons of Slick Water and Silverstim. Commingle the Niobrara and Codell.

This formation is commingled with another formation:  Yes  No

Total fluid used in treatment (bbl): 2321 Max pressure during treatment (psi): 4330

Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal): 8.34

Type of gas used in treatment: Max frac gradient (psi/ft): 0.86

Total acid used in treatment (bbl): Number of staged intervals: 7

Recycled water used in treatment (bbl): Flowback volume recovered (bbl):

Fresh water used in treatment (bbl): Disposition method for flowback: RECYCLE

Total proppant used (lbs): 147628 Rule 805 green completion techniques were utilized:

Reason why green completion not utilized:

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Date: Hours: Bbl oil: Mcf Gas: Bbl H2O:

Calculated 24 hour rate: Bbl oil: Mcf Gas: Bbl H2O: GOR:

Test Method: Casing PSI: Tubing PSI: Choke Size:

Gas Disposition: Gas Type: Btu Gas: API Gravity Oil:

Tubing Size: Tubing Setting Depth: Tbg setting date: Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze:  Yes  No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: Print Name: Sarah Finnegan

Title: Regulatory Analyst Date: Email sfinnegan@nobleenergyinc.com

**Attachment Check List**

Att Doc Num	Name

Total Attach: 0 Files

**General Comments**

User Group	Comment	Comment Date

Total: 0 comment(s)