| | |
|---|---|
| Company: | MERCHANT ENERGY PARTNERS LLC |
| Well: | ABC FEE 1 |
| Field: | ABC FIELD |
| County: | LOGAN |
| State: | COLORADO |
| Location: | 1234 FSL 1234 FEL |
| Elevation: | KB: 4,000 ft<br>GL: 3,990 ft |
| Log Date: | 10-Jan-2026 |
| Run No: | ONE |
| Depth Driller: | 5,000 ft |
| Depth Logger: | 5,000 ft |
| Bottom Log Interval: | 4,998 ft |
| Top Log Interval: | 3,000 ft |
| Casing Driller: | 8.625 in @ 1,000 ft |
| Casing Logger: | 1,000 ft |
| Bit Size: | 7.875 in |
| Type Fluid: | WBM |
| Density: | 9.2 ppg |
| Viscosity: | 48 s/qt |
| Fluid Loss: | 6.4 cc |
| Source Sample: | CIRC |
| Rm @ Meas Temp: | 0.18 @ 72 °F |
| Rmf @ Meas Temp: | 0.14 @ 72 °F |
| Rmc @ Meas Temp: | 0.24 @ 72 °F |
| Source Rmf / Rmc: | MEAS / CALC |
| Rm @ BHT: | 0.11 @ 168 °F |
| Time Since Circ: | 6 hr |
| Max Rec Temp: | 168 °F |
| Equipment / Base: | 1234 |
| Recorded By: | J. SMITH |
| Witnessed By: | M. JONES |

**CRESTWOOD OPERATING CO.**
COLLEGE CAPITAL FORMATION LLC
ABC FEE 1
ABC FIELD
LOGAN COUNTY, COLORADO
1234 FSL 1234 FEL
Sec 12 Twp 10N Rng 54W

JW WIRELINE

**Comments**

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our General Terms and Conditions set forth in our current price schedule.

THANK YOU FOR CHOOSING JW WIRELINE

| Service | Offset (ft) | Schematic | Description | Len (ft) | OD (in) | ID (in) |
|---|---|---|---|---|---|---|
| CCL | 14.52 | | CCL - 3 Sheave, 15TC<br>OD: 3.62 in, Sub and Prog | 1.96 | 3.75 | 2.00 |
| | | | CBHT-TBG/CCL-15TC | 2.73 | 2.25 | 10.00 |
| 45.4°/0.0 | 11.38 | | | | | |
| 45.4°/0.0 | 11.38 | | GUN, TBG/CCL/15TC (1/11) | 9.08 | 2.79 | 106.00 |
| 45.4°/0.0 | 11.38 | | Perfs 11 SPF, 11.5 g, 0.36 in, 11 holes | | | |
| 45.4°/0.0 | 11.38 | | | | | |
| 45.4°/0.0 | 11.38 | | | | | |
| 45.4°/0.0 | 11.38 | |