

Company	Texaco Exploration and Production Inc.		
Well	Green Canyon Block 205 #1		
Field	Green Canyon		
County, State			
Location			
Elevation			
Permanent Datum	Mean Sea Level	Elevation	0 ft
Log Measured From	Rotary Table		0 ft above Perm. Datum
Drilling Measured From	Rotary Table		
Date	10-Jun-2000		
Run Number	ONE		
Depth Driller	10,000 ft		
Schlumberger Depth	10,000 ft		
Bottom Log Interval	9,998 ft		
Top Log Interval	9,000 ft		
Casing Driller Size @ Depth	9.625 in @ 9,000 ft		
Casing Schlumberger	9,000 ft		
Bit Size	8.5 in		
Type Fluid in Hole	Water Based Mud		
Density / Viscosity	10.2 lb/gal / 45 s		
PH / Fluid Loss	9.5 / 4.2 cc		
Source of Sample	Flowline		
Rm @ Meas. Temp	0.18 ohmm @ 150 degF		
Rmf @ Meas. Temp	0.15 ohmm @ 150 degF		
Rmc @ Meas. Temp	0.22 ohmm @ 150 degF		
Source Rmf / Rmc	Measured / Measured		
Rm @ BHT	0.12 ohmm @ 210 degF		
Time Since Circulation	12 hr		
Time Since Last Log	1 hr		
Max Recorded Temp	210 degF		
Equipment Number	1		
Location	Green Canyon Block 205		
Recorded By	J. Smith		
Witnessed By	M. Johnson		

Run 1 Logged 10-Jun-2000 00:00 to 10-Jun-2000 12:00

Schlumberger

PORT COLLAR



Company	Texaco Exploration and Production Inc.
Well	Green Canyon Block 205 #1
Field	Green Canyon
County, State	
Location	
Elevation	
Permanent Datum	Mean Sea Level
Log Measured From	Rotary Table
Drilling Measured From	Rotary Table
Date	10-Jun-2000
Run Number	ONE
Depth Driller	10,000 ft
Schlumberger Depth	10,000 ft
Bottom Log Interval	9,998 ft
Top Log Interval	9,000 ft
Casing Driller Size @ Depth	9.625 in @ 9,000 ft
Casing Schlumberger	9,000 ft
Bit Size	8.5 in
Type Fluid in Hole	Water Based Mud
Density / Viscosity	10.2 lb/gal / 45 s
PH / Fluid Loss	9.5 / 4.2 cc
Source of Sample	Flowline
Rm @ Meas. Temp	0.18 ohmm @ 150 degF
Rmf @ Meas. Temp	0.15 ohmm @ 150 degF
Rmc @ Meas. Temp	0.22 ohmm @ 150 degF
Source Rmf / Rmc	Measured / Measured
Rm @ BHT	0.12 ohmm @ 210 degF
Time Since Circulation	12 hr
Time Since Last Log	1 hr
Max Recorded Temp	210 degF
Equipment Number	1
Location	Green Canyon Block 205
Recorded By	J. Smith
Witnessed By	M. Johnson

Run 1 Logged 10-Jun-2000 00:00 to 10-Jun-2000 12:00

Schlumberger

MAIN PASS



Company	Texaco Exploration and Production Inc.
Well	Green Canyon Block 205 #1
Field	Green Canyon
County, State	
Location	
Elevation	
Permanent Datum	Mean Sea Level
Log Measured From	Rotary Table
Drilling Measured From	Rotary Table
Date	10-Jun-2000
Run Number	ONE
Depth Driller	10,000 ft
Schlumberger Depth	10,000 ft
Bottom Log Interval	9,998 ft
Top Log Interval	9,000 ft
Casing Driller Size @ Depth	9.625 in @ 9,000 ft
Casing Schlumberger	9,000 ft
Bit Size	8.5 in
Type Fluid in Hole	Water Based Mud
Density / Viscosity	10.2 lb/gal / 45 s
PH / Fluid Loss	9.5 / 4.2 cc
Source of Sample	Flowline
Rm @ Meas. Temp	0.18 ohmm @ 150 degF
Rmf @ Meas. Temp	0.15 ohmm @ 150 degF
Rmc @ Meas. Temp	0.22 ohmm @ 150 degF
Source Rmf / Rmc	Measured / Measured
Rm @ BHT	0.12 ohmm @ 210 degF
Time Since Circulation	12 hr
Time Since Last Log	1 hr
Max Recorded Temp	210 degF
Equipment Number	1
Location	Green Canyon Block 205
Recorded By	J. Smith
Witnessed By	M. Johnson

Run 1 Logged 10-Jun-2000 00:00 to 10-Jun-2000 12:00

Schlumberger

REPEAT SECTION



Company	Texaco Exploration and Production Inc.
Well	Green Canyon Block 205 #1
Field	Green Canyon
County, State	
Location	
Elevation	
Permanent Datum	Mean Sea Level
Log Measured From	Rotary Table
Drilling Measured From	Rotary Table
Date	10-Jun-2000
Run Number	ONE
Depth Driller	10,000 ft
Schlumberger Depth	10,000 ft
Bottom Log Interval	9,998 ft
Top Log Interval	9,000 ft
Casing Driller Size @ Depth	9.625 in @ 9,000 ft
Casing Schlumberger	9,000 ft
Bit Size	8.5 in
Type Fluid in Hole	Water Based Mud
Density / Viscosity	10.2 lb/gal / 45 s
PH / Fluid Loss	9.5 / 4.2 cc
Source of Sample	Flowline
Rm @ Meas. Temp	0.18 ohmm @ 150 degF
Rmf @ Meas. Temp	0.15 ohmm @ 150 degF
Rmc @ Meas. Temp	0.22 ohmm @ 150 degF
Source Rmf / Rmc	Measured / Measured
Rm @ BHT	0.12 ohmm @ 210 degF
Time Since Circulation	12 hr
Time Since Last Log	1 hr
Max Recorded Temp	210 degF
Equipment Number	1
Location	Green Canyon Block 205
Recorded By	J. Smith
Witnessed By	M. Johnson

Run 1 Logged 10-Jun-2000 00:00 to 10-Jun-2000 12:00

Schlumberger

Calibration Casing Diameter:	5.500	in
Calibration Depth:	5006.792	ft

Master Calibration, performed Tue Jul 10 07:18:54 2012:

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.013	1.625	0.000	71.921	44.625	-0.596
CAL	1.882	1.855				
5'	0.013	1.594	0.000	71.921	45.497	-0.610
SUM						
S1	0.010	1.578	0.000	100.000	63.763	-0.629
S2	0.012	1.600	0.000	100.000	62.989	-0.766
S3	0.013	1.632	0.000	100.000	61.751	-0.792
S4	0.013	1.668	0.000	100.000	60.408	-0.763
S5	0.013	1.666	0.000	100.000	60.497	-0.785
S6	0.015	1.631	0.000	100.000	61.864	-0.912
S7	0.014	1.579	0.000	100.000	63.918	-0.895
S8	0.014	1.555	0.000	100.000	64.909	-0.918

Internal Reference Calibration, performed Wed Dec 31 17:00:00 1969:

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	1.882	1.855	1.000	0.000

Air Zero Calibration, performed Tue Jul 10 07:06:33 2012:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000