

**DRILLING PLAN - Horizontal / Niobrara**

<b>PROSPECT/FIELD</b>		Niobrara (exploration) / D-J Basin		<b>COUNTY/STATE</b>		Arapahoe / Colorado															
<b>OPERATOR</b>		ConocoPhillips																			
<b>WELL NAME / No.</b>		State of Colorado 36-1H																			
<b>LOCATION</b>		NESE 36 T3S-R64W		Surface Location:	1980' FSL	250' FEL															
		NWSW 3 T5S-R64W		Bottom Hole Location:	1980' FSL	480' FWL															
<b>EST. T.D.</b>		Leg #1 11,658' MD		<b>GROUND ELEVATION:</b>		5,566' (est)	Finished Grade														
		TOTAL LATERALS:		#1 4,010'																	
<b>PROGNOSIS:</b>				Based on 5,580' RKB Elevation (est)																	
<b>FORMATION</b>				<b>DEPTH TVD</b>		<b>DATUM</b>															
Fox Hills Aquifer				N/A		Fresh Water															
Pierre Shale				1,620			3,960														
Surface Casing				1,820			3,760														
Sharon Springs Shale				7,118			(1,538)														
Niobrara				7,154	Gas / Oil		(1,574)														
Niobrara B				7,236	Gas / Oil		(1,656)														
Niobrara C Chalk				7,291	Gas / Oil		(1,711)														
Horizontal Target Zone				7,321	Gas / Oil		(1,741)														
Niobrara D Chalk				7,356	Gas / Oil		(1,776)														
Fort Hays Limestone				7,489	Gas / Oil		(1,909)														
Carlisle Shale				7,524	Gas / Oil		(1,944)														
Greenhorn				7,582	Gas / Oil		(2,002)														
TD Pilot Hole				7,682			(2,102)														
<b>LOGS:</b>				<table border="0" style="width:100%;"> <tr> <td><b>Type</b></td> <td><b>Interval</b></td> </tr> <tr> <td>Open Hole:</td> <td>Triple Combo / HNGS / RTScanner / SonicScanner</td> </tr> <tr> <td>(pilot hole)</td> <td>From 7,983' to 6,000'</td> </tr> <tr> <td>LWD-MWD:</td> <td>GR &amp; Sonic Scanner From 6,000' to Surface</td> </tr> <tr> <td></td> <td>MWD-GR in Curve Build Section (6,748' to 7,648')</td> </tr> <tr> <td></td> <td>LWD Density / Neutron / Resistivity / Sonic / Imaging</td> </tr> <tr> <td></td> <td>Lateral Section (7,648' to 11,658')</td> </tr> </table>				<b>Type</b>	<b>Interval</b>	Open Hole:	Triple Combo / HNGS / RTScanner / SonicScanner	(pilot hole)	From 7,983' to 6,000'	LWD-MWD:	GR & Sonic Scanner From 6,000' to Surface		MWD-GR in Curve Build Section (6,748' to 7,648')		LWD Density / Neutron / Resistivity / Sonic / Imaging		Lateral Section (7,648' to 11,658')
<b>Type</b>	<b>Interval</b>																				
Open Hole:	Triple Combo / HNGS / RTScanner / SonicScanner																				
(pilot hole)	From 7,983' to 6,000'																				
LWD-MWD:	GR & Sonic Scanner From 6,000' to Surface																				
	MWD-GR in Curve Build Section (6,748' to 7,648')																				
	LWD Density / Neutron / Resistivity / Sonic / Imaging																				
	Lateral Section (7,648' to 11,658')																				
<b>DEVIATION:</b>				<table border="0" style="width:100%;"> <tr> <td>Surf:</td> <td>2.0° max., DLS 1°/100'; survey every 500' (Gyro at TD)</td> </tr> <tr> <td>Int:</td> <td>2.0° max., DLS 0.6/100'; survey every 90' (MWD-GR)</td> </tr> <tr> <td>Prod (lateral):</td> <td>90° Plan Lateral, DLS 0.5/100'; survey every 90' (MWD surveys every 30' in curve build sections)</td> </tr> </table>				Surf:	2.0° max., DLS 1°/100'; survey every 500' (Gyro at TD)	Int:	2.0° max., DLS 0.6/100'; survey every 90' (MWD-GR)	Prod (lateral):	90° Plan Lateral, DLS 0.5/100'; survey every 90' (MWD surveys every 30' in curve build sections)								
Surf:	2.0° max., DLS 1°/100'; survey every 500' (Gyro at TD)																				
Int:	2.0° max., DLS 0.6/100'; survey every 90' (MWD-GR)																				
Prod (lateral):	90° Plan Lateral, DLS 0.5/100'; survey every 90' (MWD surveys every 30' in curve build sections)																				
<b>DST'S:</b>				None Planned																	
<b>CORES:</b>				None Planned																	
<b>SAMPLES:</b>				<table border="0" style="width:100%;"> <tr> <td>Mudlogging:</td> <td>From 6,000' to TD (Weatherford Logging)</td> </tr> <tr> <td>(Two-Man Unit)</td> <td>Dry samples every 10'</td> </tr> <tr> <td></td> <td>Wet samples every 30'</td> </tr> </table>				Mudlogging:	From 6,000' to TD (Weatherford Logging)	(Two-Man Unit)	Dry samples every 10'		Wet samples every 30'								
Mudlogging:	From 6,000' to TD (Weatherford Logging)																				
(Two-Man Unit)	Dry samples every 10'																				
	Wet samples every 30'																				
<b>BOP:</b>				<table border="0" style="width:100%;"> <tr> <td>11" x 5M psi (Rams &amp; Annular) / Choke Manifold (two 2" wings) 5M psi</td> </tr> <tr> <td>Stack Up Configuration:</td> </tr> <tr> <td>Rotating Head</td> </tr> <tr> <td>Annular</td> </tr> <tr> <td>Pipe Rams</td> </tr> <tr> <td>Blind Rams</td> </tr> <tr> <td>Choke &amp; Kill Valves / Lines</td> </tr> <tr> <td>Pipe Rams</td> </tr> </table>				11" x 5M psi (Rams & Annular) / Choke Manifold (two 2" wings) 5M psi	Stack Up Configuration:	Rotating Head	Annular	Pipe Rams	Blind Rams	Choke & Kill Valves / Lines	Pipe Rams						
11" x 5M psi (Rams & Annular) / Choke Manifold (two 2" wings) 5M psi																					
Stack Up Configuration:																					
Rotating Head																					
Annular																					
Pipe Rams																					
Blind Rams																					
Choke & Kill Valves / Lines																					
Pipe Rams																					
<b>WELLHEAD:</b>				<table border="0" style="width:100%;"> <tr> <td>SH2R Type "Multi-Bowl" Wellhead (GE Oil &amp; Gas)</td> </tr> <tr> <td>Upper Flange 11" x 5M psi (Drilling Spool)</td> </tr> <tr> <td>Lower Flange 11" x 5M psi (Casing Head)</td> </tr> </table>				SH2R Type "Multi-Bowl" Wellhead (GE Oil & Gas)	Upper Flange 11" x 5M psi (Drilling Spool)	Lower Flange 11" x 5M psi (Casing Head)											
SH2R Type "Multi-Bowl" Wellhead (GE Oil & Gas)																					
Upper Flange 11" x 5M psi (Drilling Spool)																					
Lower Flange 11" x 5M psi (Casing Head)																					
<b>Max. Anticipated BHP:</b>		0.49 psi/ft	3,764 psi	09.4 ppg (EMW)	<b>Estimated BH Static Temperature (°F):</b>			225													
<b>MUD:</b>		<b>Interval</b>	<b>Type</b>	<b>Hole</b>	<b>WT</b>	<b>Vis</b>	<b>LGS %</b>	<b>WL</b>	<b>Remarks</b>												
Surface:		0' - 1,820'	FW / Gel-Lime Sweeps	12-1/4"	8.4 - 9.0	28-45	< 6%	NC	Closed Loop												
Intermediate:		1,820' - 7,648'	Oil Base Mud (Integrate)	8-3/4"	9.0 - 9.9	35-45	< 6%	<6 (HpH)	Closed Loop												
Production (lateral):		7,648' - 11,658'	FW / LSND / Gel-Polymer	6-1/8"	9.4 - 9.9	35-45	< 6%	<6	Closed Loop												
<b>CASING:</b>		<b>Size</b>	<b>Wt ppf</b>	<b>Hole</b>	<b>Depth</b>	<b>Cement Top</b>	<b>Excess</b>	<b>WOC</b>	<b>Remarks</b>												
Surface:		9-5/8"	36 # J55 STC	12-1/4"	1,820'	To Surface	140%	8 hrs	500' Tail Cement												
Intermediate:		7"	26# P110 LTC	8-3/4"	7,648'	1720'	10%	8 hrs	500' Tail above Niobrara												
Production (liner):		4-1/2"	13.5# P110 BTC	6-1/8"	11,658'	Un-Cemented			6,648' Top of Liner												
<b>CENTRALIZATION:</b>																					
Surface Casing: 1/joint on bottom four joints; 1/4th joint to surface (bow-spring type)																					
Cementing baskets placed at 120' and 1,400'																					
Intermediate Casing: 1/joint on bottom two joints; 1/4th joint to 6,600'; 1/5th joint from 6,600' to surface (bow-spring type)																					
<b>DIRECTIONAL PLAN</b>																					
		<b>MD</b>	<b>TVD (RKB elev.)</b>			<b>AZ</b>															
Surface (RKB):		0'	0'	1980' FSL	250' FEL	36-T3S-R64W	0.00	Survey Company: Halliburton Sperry													
Vertical KOP (90° curve):		6,748'	6,748'	1980' FSL	250' FEL	36-T3S-R64W	0.00	Vertical Build Rate: 10.0 '100'													
Curve Landing / End Build:		7,648'	7,321'	1980' FSL	823' FEL	36-T3S-R64W	271.17	Int Leg Turn Rate: 0.0 '100'													
Intermediate Casing Point:		7,648'	7,321'	1980' FSL	823' FEL	36-T3S-R64W	271.17	Land curve at 90° inc. and 270.42° Az.													
Lateral TD - BHL:		11,658'	7,321'	1980' FSL	480' FWL	36-T3S-R64W	271.17	Hold 90° Inclination on 270.42° Azimuth													
Setback Boundary Distance to Section Lines = 460'																					
<b>Comments:</b>																					
MWD Surveys will be taken every 30' while building curve and every 90' while drilling lateral.																					
<b>Prep By:</b>		Gary Hamilton		<b>Date:</b>		7/26/12		<b>Doc:</b> REV 0													

