

Header Information	measured depth (ft)	inclination (°)	azimuth (°)	true vertical depth (ft)	northing +N/-S (ft)	easting +E/-W (ft)
Operator Name	0.00	0.00	0	0	0	0
Chevron	100.00	0.00	0	100	0	0
Operator Number	200.00	0.00	0	200	0	0
	250.00	0.00	0	250	0	0
Well Name and Number	300.00	0.5	3.39	300	0.22	0.01
FEE 163X	400.00	1.5	3.39	399.98	1.96	0.12
API Number (if available)	500.00	2.5	3.39	499.92	5.44	0.32
	600.00	3.5	3.39	599.78	10.67	0.63
Location: QQ SEC TWP RGE	681.12	4.31	3.39	680.71	16.18	0.96
Sec 33 T2N R102W	700.00	4.31	3.39	699.54	17.6	1.04
Citing Type: Planned or Actual	800.00	4.31	3.39	799.26	25.1	1.49
Planned	900.00	4.31	3.39	898.97	32.61	1.93
Deviation Indicator	1,000.00	4.31	3.39	998.69	40.11	2.38
Directional ▼	1,100.00	4.31	3.39	1098.41	47.62	2.82
North Reference	1,200.00	4.31	3.39	1198.13	55.12	3.26
True ▼	1300	4.31	3.39	1297.84	62.63	3.71
Grid Type	1400	4.31	3.39	1397.56	70.13	4.15
▼	1500	4.31	3.39	1497.28	77.63	4.6
	1600	4.31	3.39	1596.99	85.14	5.04
	1700	4.31	3.39	1696.71	92.64	5.49
	1800	4.31	3.39	1796.43	100.15	5.93
	1900	4.31	3.39	1896.14	107.65	6.38
	2000	4.31	3.39	1995.86	115.15	6.82
	2100	4.31	3.39	2095.58	122.66	7.26
	2200	4.31	3.39	2195.3	130.16	7.71
	2300	4.31	3.39	2295.01	137.67	8.15
	2400	4.31	3.39	2394.73	145.17	8.6
	2500	4.31	3.39	2494.45	152.68	9.04

2600	4.31	3.39	2594.16	160.18	9.49
2700	4.31	3.39	2693.88	167.68	9.93
2800	4.31	3.39	2793.6	175.19	0.38
2900	4.31	3.39	2893.32	182.69	0.82
3000	4.31	3.39	2993.03	190.2	1.26
3100	4.31	3.39	3092.75	197.7	1.71
3200	4.31	3.39	3192.47	205.2	2.15
3300	4.31	3.39	3292.18	212.71	2.6
3400	4.31	3.39	3391.9	220.21	3.04
3500	4.31	3.39	3491.62	227.72	3.49
3600	4.31	3.39	3591.33	235.22	3.93
3700	4.31	3.39	3691.05	242.72	4.38
3800	4.31	3.39	3790.77	250.23	4.82
3900	4.31	3.39	3890.49	257.73	5.26
4000	4.31	3.39	3990.2	265.24	5.71
4100	4.31	3.39	4089.92	272.74	6.15
4200	4.31	3.39	4189.64	280.25	6.6
4300	4.31	3.39	4289.35	287.75	7.04
4400	4.31	3.39	4389.07	295.25	7.49
4500	4.31	3.39	4488.79	302.76	7.93
4600	4.31	3.39	4588.5	310.26	8.38
4700	4.31	3.39	4688.22	317.77	8.82
4800	4.31	3.39	4787.94	325.27	9.26
4900	4.31	3.39	4887.66	332.77	9.71
5000	4.31	3.39	4987.37	340.28	0.15
5100	4.31	3.39	5087.09	347.78	0.6
5200	4.31	3.39	5186.81	355.29	1.04
5300	4.31	3.39	5286.52	362.79	1.49
5400	4.31	3.39	5386.24	370.3	1.93
5500	4.31	3.39	5485.96	377.8	2.38
5600	4.31	3.39	5585.68	385.3	2.82
5700	4.31	3.39	5685.39	392.81	3.26
5800	4.31	3.39	5785.11	400.31	3.71
5900	4.31	3.39	5884.83	407.82	4.15

6000	4.31	3.39	5984.54	415.32	4.6
6100	4.31	3.39	6084.26	422.82	5.04
6200	4.31	3.39	6183.98	430.33	5.49
6300	4.31	3.39	6283.69	437.83	5.93
6400	4.31	3.39	6383.41	445.34	6.37
6487.84	4.31	3.39	6471	451.93	6.77