

FORM  
5A

Rev  
06/12

State of Colorado  
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

400314880

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 10261  
2. Name of Operator: BAYSWATER EXPLORATION AND PRODUCTION  
3. Address: 730 17TH ST STE 610  
City: DENVER State: CO Zip: 80202  
4. Contact Name: JONATHAN RUNGE  
Phone: (970) 669-7411  
Fax: (970) 669-4077

5. API Number 05-123-34953-00  
6. County: WELD  
7. Well Name: Gittlein  
Well Number: 2-4  
8. Location: QtrQtr: NWNE Section: 4 Township: 1N Range: 67W Meridian: 6  
9. Field Name: SPINDLE Field Code: 77900

Completed Interval

FORMATION: CODELL Status: PRODUCING Treatment Type: FRACTURE STIMULATION

Treatment Date: 06/01/2012 End Date: 06/01/2012 Date of First Production this formation: 07/13/2012

Perforations Top: 7648 Bottom: 7666 No. Holes: 88 Hole size: 042/100

Provide a brief summary of the formation treatment: Open Hole: ☐

271773 gals, 181773 gals SLF, 181540 lbs 30/50 White

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 10798 Max pressure during treatment (psi): 5220

Total gas used in treatment (mcf): 0 Fluid density at initial fracture (lbs/gal): 0.25

Type of gas used in treatment: Min frac gradient (psi/ft): 0.79

Total acid used in treatment (bbl): 0 Number of staged intervals: 1

Recycled water used in treatment (bbl): 0 Flowback volume recovered (bbl): 6471

Fresh water used in treatment (bbl): 6471 Disposition method for flowback: DISPOSAL

Total proppant used (lbs): 181540 Rule 805 green completion techniques were utilized: ☐

Reason why green completion not utilized: PIPELINE

Fracture stimulations must be reported on FracFocus.org

Test Information:

Date: 07/15/2012 Hours: 23 Bbl oil: 105 Mcf Gas: 172 Bbl H2O: 34

Calculated 24 hour rate: Bbl oil: 110 Mcf Gas: 179 Bbl H2O: 35 GOR: 1638

Test Method: FLOWING Casing PSI: 1650 Tubing PSI: Choke Size: 010/64

Gas Disposition: SOLD Gas Type: WET Btu Gas: 1331 API Gravity Oil: 46

Tubing Size: Tubing Setting Depth: Tbg setting date: Packer Depth:

Reason for Non-Production:

Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt

\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:

--

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Jonathan Runge

Title: Consultant Date: \_\_\_\_\_ Email jrunge@petersonenergy.com  
:

### **Attachment Check List**

Att Doc Num	Name
400314889	WELLBORE DIAGRAM

Total Attach: 1 Files

### **General Comments**

<b><u>User Group</u></b>	<b><u>Comment</u></b>	<b><u>Comment Date</u></b>

Total: 0 comment(s)